INTERNATIONAL STANDARD

First edition 2009-02-15

Rubber and plastics hoses, non-collapsible, for fire-fighting service —

Part 1: Semi-rigid hoses for fixed systems

Tuyaux en caoutchouc et en plastique, non aplatissables, pour la lutte contre l'incendie —

Partie 1: Tuyaux semi-rigides pour systèmes fixes



Reference number ISO 4642-1:2009(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below

This document is a preview denerated by Fig.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

Contents

Forewo	ord	iv
Introdu	ntroduction	
1	Scope	. 1
2	Normative references	. 1
3	Terms and Gefinitions	2
4 4.1 4.2 4.3	Classification General Classification by types (hose construction) Classification by class (materials for lining and cover)	2
5 5.1 5.2	Dimensions, tolerances and maximum mass Inside diameter and maximum mass Length and tolerances on tergth	3
6 6.1 6.2 6.3 6.4 6.5 6.6 6.7 6.8 6.9 7	Performance requirements of inished hose Hydrostatic requirements Adhesion Accelerated ageing Low temperature flexibility Hot surface resistance Bending and crush resistance UV resistance (xenon arc lamp) Loss in mass on heating Frequency of testing Type tests Test report Recommendation for packaging and storage Marking A (normative) Kink pressure test B (normative) Accelerated ageing test C (normative) Hot surface resistance test D (normative) Bending and crush resistance test	3 4 4 4 4 5 5
8	Type tests	. 5 E
9 10	Recommendation for packaging and storage	5
11	Marking	5
Annex	A (normative) Kink pressure test	. 7
Annex	B (normative) Accelerated ageing test	. 8
Annex	C (normative) Hot surface resistance test	9
Annex	D (normative) Bending and crush resistance test	14
Annex	E (normative) Type test and routine test	16
	F (informative) Production test	
Bibliog	raphyŕ	18

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 4642-1 was prepared by Technical Committee ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 1, *Hoses (rubber and plastics)*.

This first edition, together with ISO 4642-2, cancels and replaces ISO 4642:1978 which has been technically revised.

ISO 4642 consists of the following parts, under the general title *Rubber and plastics hoses, non-collapsible, for fire-fighting service*:

- Part 1: Semi-rigid hoses for fixed systems
- Part 2: Semi-rigid hoses (and hose assemblies) for pumps and whicles

Introduction

A fixed system is a manually operated unit installed in a building in order to make it possible for the occupants to control and extinguish a small fire. The system consists of fixed units mounted on walls or in cabinets permanently connected to a water supply. The fixed units are composed of a coupling, a valve, a semi-rigid water-filled hose with its support and a nozzle.

a. ding, with its s this document is a preview generated by the second s

this document is a preview denerated by EUS

Rubber and plastics hoses, non-collapsible, for fire-fighting service —

Part 1: Semi-rigid hoses for fixed systems

1 Scope

This part of ISO 4642 specifies the requirements and test methods for semi-rigid reel hoses for fire-fighting purposes for use with fixed systems. The hoses are intended for use at a maximum working pressure of 1,2 MPa for hoses of 19 mm and 25 mm inside diameter and 0,7 MPa for hoses of 33 mm inside diameter.

Hoses conforming to this part of ISO 4642 are intended for applications where long intervals can occur between the occasions of use, for example on fixed fire hose reels in buildings and other construction works.

This part of ISO 4642 applies exclusive ∞ hoses for fire-fighting purposes intended for use at ambient conditions in non-aggressive or non-corrosive atmospheres within the temperature range -20 °C to +60 °C.

NOTE 1 Hoses for use at temperatures lower than 20 °C can be supplied at the request of the purchaser.

NOTE 2 All pressures are expressed in megapascals where 1 MPa = 10 bar.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 176:2005, Plastics — Determination of loss of plasticizers — Activated carbon method

ISO 188, Rubber, vulcanized or thermoplastic — Accelerated ageing and heat resistance tests

ISO 1307, Rubber and plastics hoses — Hose sizes, minimum and maximum inside diameters, and tolerances on cut-to-length hoses

ISO 1402, Rubber and plastics hoses and hose assemblies — Hydrostatic testing

ISO 4671, Rubber and plastics hoses and hose assemblies — Methods of measurement of the dimensions of hoses and the lengths of hose assemblies

ISO 4672:1997, Rubber and plastics hoses — Sub-ambient temperature flexibility tests

ISO 7326:2006, Rubber and plastics hoses — Assessment of ozone resistance under static conditions

ISO 8033, Rubber and plastics hose — Determination of adhesion between components

ISO 8330, Rubber and plastics hoses and hose assemblies — Vocabulary

ISO 8331, Rubber and plastics hoses and hose assemblies — Guidelines for selection, storage, use and maintenance