INTERNATIONAL STANDARD

ISO 3186

Second edition 2008-08-15

Aerospace — Bolts, large bihexagonal head, normal shank, short or medium length MJ threads, metallic material, coated or uncoated, strength classes 1 250 MPa to 1 800 MPa — Dimensions

Aéronautique et espace — Vis à tête bihexagonale large, avec tige normale et filetages MJ courts ou de longueur moyenne, en matériau métallique, revêtues ou non revêtues, des classes de résistance 1 250 MPa à 1 800 MPa — Dimensions



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below





COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 3186 was prepared by Technical committee ISO/TC 20, Aircraft and space vehicles, Subcommittee SC 4, Aerospace fastener systems.

This second edition cancels and replaces the first edition (ISO 3186:1994), which has been technically revised.

© ISO 2008 – All rights reserved iii

Inis document is a preview denetated by EUS

Aerospace — Bolts, large bihexagonal head, normal shank, short or medium length MJ threads, metallic material, coated or uncoated, strength classes 1 250 MPa to 1 800 MPa — Dimensions

1 Scope

This International Standard specifies the dimensions of large bihexagonal head bolts, with close or large tolerance normal shank and shart or medium length MJ threads, in metallic material, coated or uncoated, with strength classes 1 250 MPa to 300 MPa.

This International Standard is applicable to the compilation of aerospace product standards.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 286-2, ISO system of limits and fits — Part 2: Tables of standard tolerance grades and limit deviations for holes and shafts

ISO 3353-1, Aerospace — Lead and runout threads — Part 1: Rolled external threads

ISO 4095, Aerospace — Bihexagonal drives — Wrenching configuration — Metric series

ISO 5855-2, Aerospace — MJ threads — Part 2: Limit dimensions for bolts and nuts

ISO 7913, Aerospace — Bolts and screws, metric — Tolerances of form and position

3 Configuration and dimensions

See Figure 1 and Table 1.

Dimensions and tolerances are expressed in millimetres. They are applicable after any coating (tolerance on shank diameter before coating is also specified for heat cured matrix coatings), but before the application of any lubricant.

Details of form not stated are left to the manufacturer's discretion.

Tolerances of form and position shall be as specified in ISO 7913 if not otherwise stated on product standard.

© ISO 2008 – All rights reserved