

ICS 17.140.30, 93.080.30

English version

Road traffic noise reducing devices - Test method for  
determining the acoustic performance - Part 4: Intrinsic  
characteristics - In situ values of sound diffraction

Dispositifs de réduction du bruit du trafic routier – Méthode  
d'essai pour la détermination des performances  
acoustiques – Partie 4 : Caractéristiques intrinsèques –  
Valeurs in situ de la diffraction acoustique

Lärmschutzeinrichtungen an Straßen - Prüfverfahren zur  
Bestimmung der akustischen Eigenschaften - Teil 4:  
Produktspezifische Merkmale - Insitu-Werte der  
Schallbeugung

This Technical Specification (CEN/TS) was approved by CEN on 6 June 2003 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Slovakia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

## Contents

Foreword.....	4
Introduction .....	5
1 Scope .....	4
2 Normative references .....	5
3 Definitions and symbols .....	5
3.1 Definitions.....	5
3.2 Symbols .....	6
4 Diffraction index difference measurements.....	7
4.1 General principle.....	7
4.2 Dimensions and specifications .....	7
4.3 Positions of the sound source .....	8
4.4 Position of the microphones .....	8
4.5 Free-field measurements .....	9
4.6 Measured quantity .....	14
4.7 Measuring equipment.....	16
4.8 Data processing .....	18
4.9 Positioning of the measuring equipment.....	21
4.10 Diffraction index difference .....	22
4.11 Single-number rating of diffraction index difference $DL_{ADI}$ .....	22
4.12 Sample surface and meteorological conditions.....	23
4.13 Measuring procedure .....	23
4.14 Test report .....	24
Annex A (Informative) Definition and usage of the MLS signal.....	26
Annex B (Informative) Indoor measurements for product qualification.....	28
Annex C (Informative) Bibliography .....	29

## Foreword

This document (CEN/TS 1793-4:2003) has been prepared by Technical Committee CEN/TC 226 "Road equipment", the secretariat of which is held by AFNOR.

It should be read in conjunction with :

EN 1793-1, *Road traffic noise reducing devices - Test method for determining the acoustic performance – Part 1 : Intrinsic characteristics of sound absorption*

EN 1793-2, *Road traffic noise reducing devices - Test method for determining the acoustic performance – Part 2 : Intrinsic characteristics of airborne sound insulation*

EN 1793-3, *Road traffic noise reducing devices - Test method for determining the acoustic performance – Part 3 : Normalized traffic noise spectrum*

CEN/TS 1793-5, *Road traffic noise reducing devices - Test method for determining the acoustic performance – Part 5: Intrinsic characteristics – In situ values of sound reflection and airborne sound insulation.*

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Slovakia, Spain, Sweden, Switzerland and the United Kingdom.

## Introduction

Part of the market of road traffic noise reducing devices is constituted of products to be added on the top of noise reducing devices and intended to contribute to sound attenuation acting primarily on the diffracted sound field. These products will be called added devices. This standard has been developed to specify a test method for determining the acoustic performance of added devices.

The test method can be applied in situ, i.e. where the traffic noise reducing devices and the added devices are installed. The method can be applied without damaging the traffic noise reducing devices or the added devices.

The method can be used to qualify products before the installation along roads as well as to verify the compliance of installed added devices to design specifications. Repeated application of the method can be used to verify the long term performance of added devices.

NOTE – This method could be used to qualify added devices for other applications, e.g. to be installed along railways or nearby industrial sites. In this case special care has to be taken into account in considering the location of the noise sources and the single-number ratings should be calculated using an appropriate spectrum.

No other national or international standard exists about the subject of this standard.

## 1 Scope

This document describes a test method for determining the intrinsic characteristics of sound diffraction of added devices installed on the top of traffic noise reducing devices. The test method prescribes measurements of the sound pressure level at several reference points near the top edge of a noise reducing device with and without the added device installed on its top. The effectiveness of the added device is calculated as the difference between the measured values with and without the added devices, correcting for any change in height.

The test method is intended for the following applications:

- preliminary qualification, outdoors or indoors, of added devices to be installed on noise reducing devices;
- determination of sound diffraction index difference of added devices in actual use;
- comparison of design specifications with actual performance data after the completion of the construction work;
- verification of the long term performance of added devices (with a repeated application of the method).

The test method can be applied both in situ and on samples purposely built to be tested using the method described here.

Results are expressed as a function of frequency, in one-third octave bands between 100 Hz and 5 kHz. If it is not possible to get valid measurements results over the whole frequency range indicated, the results shall be given in the restricted frequency range and the reasons of the restriction(s) shall be clearly reported. A single-number rating is calculated from frequency data.

For indoor measurements see Annex B.

## 2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate place in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication applies.

EN 1793-3: 1997, *Road traffic noise reducing devices - Test method for determining the acoustic performance - Part 3: Normalized traffic noise spectrum*.

EN 60651: 1979, *Sound level meters*.

## 3 Definitions and symbols

### 3.1 Definitions

For the purpose of this standard the following definitions apply:

#### 3.1.1

##### **structural elements**

those elements whose primary function is to support or hold in place acoustic elements

#### 3.1.2

##### **acoustical elements**

those elements whose primary function is to provide the acoustic performance of the device

#### 3.1.3

##### **noise barrier**

noise reducing device which obstructs the direct transmission of airborne sound emanating from road traffic

#### 3.1.4

##### **added device**

acoustic element added on the top of a noise reducing device and intended to contribute to sound attenuation acting primarily on the diffracted sound field

#### 3.1.5

##### **roadside exposure**

The use of the product as a noise reducing device installed alongside roads

#### 3.1.6

##### **diffraction index**

The result of a sound diffraction test described by formula (1).  $DI_{refl}$  refers to measurements on a reflective reference wall.  $DI_{abs}$  refers to measurements on an absorptive reference wall.  $DI_{situ}$  refers to in situ measurements

#### 3.1.7

##### **diffraction index difference**

difference between the results of sound diffraction tests on the same reference wall with and without an added device on the top, described by formula (4)

#### 3.1.8

##### **test construction**

construction on which the added device is placed. For in situ measurements it is an installed noise reducing device; for qualification tests it is a reference wall (see 4.2)