RAPPORT TECHNIQUE

CLC/TR 50173-99-2

RAPPORT TECHNIQUE TECHNISCHER BERICHT

March 2010

ICS 35.110

English version

Information technology Implementation of BCT applications using cabling in accordance with EN 50173-4

Technologies de l'information -Mise en oeuvre des applications BCT utilisant un câblage réalisé selon la EN 50173-4 Informationstechnik -Realisierung von RuK-Netzanwendungen mit Verkabelung nach EN 50173-4

This Technical Report was approved by CENELEC on 2010-01-01.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: Avenue Marnix 17, B - 1000 Brussels

Foreword

This Technical Report was prepared by the Technical Committee CENELEC TC 215, Electrotechnical aspects of telecommunication equipment, in cooperation with experts from CENELEC TC 209/WG 4, System performance requirements.

The text of the draft was submitted to vote and was approved by CENELEC as CLC/TR 50173-99-2 on 2010-01-01.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent

We to the Carry and C. The Carry and C.

Contents

Int	roduction.		5
1	Scope		5
2	Normative	e references	6
3	Definition	ns and abbreviations	6
	3.1	Definitions	6
	3.2	Abbrevations	8
4	Cabling structure		
	4.1	General	8
	4.2	Functional elements of networks in accordance with EN 60728	9
	4.3	Cabling subsystems of networks in accordance with EN 60728	9
	4.4	Accommodation of functional elements	11
	4.5	Interfaces	12
	4.6	Dimensioning and configuring	13
5	Slope req	juirements	13
6	Slope requirements		
	6.1	Balanced cabling	15
	6.2	Coaxial cabling	19
An	nex A (info	ormative) Example implementations of BCT applications	23
	A.1	General	
	A.2	System components	24
	A.3	Passive or active coaxial home networks	24
	A.4	Home network with balanced type cables (Case A and Case B)	25
	A.5	Amplifiers at the home distributor	27
Та	ble 1 – Mai	n functional elements of networks in accordance with EN 60728 series	9
Та	ble 2 – Slop	be performance of balanced cabling in accordance with EN 50173-4	14
Та	ble 3 – Slop	pe performance of coaxial cabling in accordance with EN 50173-4	14
Та	ble 4 – Bala	anced BCT-B-L permanent link lengths for a range of cord lengths	18
Та	ble 5 – Bala	anced BCT-B-M permanent link lengths for a range of cord lengths	19

Table A.1 – Typical attenuation performance of splitters	24
Table A.2 – Example of home network implementation with coaxial cabling (passive) from HNI1 to SO 24	
Table A.3 – Example of home network implementation with coaxial cabling (active) from HNI2 to SO 25	
Table A.4 – Example of home network implementation with balanced pair cables (active) from HNI3 to coaxial TI (Case A)	26
Table A.5 – Example of home network implementation with balanced pair cables (active) from HNI3 to coaxial SO (Case B)	26
Figure 1 – Structure of generic cabling for BCT applications (CATV)	9
Figure 2 – Structure of genetic cabling for BCT applications (MATV/SMATV)	10
Figure 3 – Examples of location of HNI for various home network types	11
Figure 4 – Schematic of generic cabling for BCT applications according to EN 50173-4	12
Figure 5 – Slope interfaces (direct connection of HNI to BO)	13
Figure 6 – Slope interfaces (HNI to BO via plitter/amplifier equipment)	13
Figure 7 – Multi-stage slope compensation in homes containing SHDs	15
Figure 8 – Home cabling configurations for BCT-Bapplications	16
Figure 9 – Home cabling configurations for BCT-C applications	20
Figure A.1 – Examples of home network implementation using coaxial or balanced cables	23

Introduction

EN 50173-4 specifies generic cabling in homes, installed to support one or more of the following groups of applications and based upon balanced and coaxial cabling as appropriate:

- a) Information and Communication Technologies (ICT);
- b) Broadcast and Communication Technologies (BCT);
- c) Command, Controls and Communications in Buildings (CCCB).

EN 50173-4 also provides requirements for backbone cabling subsystems within premises containing multiple homes by reference to:

- 1) EN 50173-1 for cooling to support ICT applications;
- 2) standards of the EN 60728 series to support BCT applications.

EN 50083 and EN 60728 standards deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television signals, sound signals and their associated data signals and for processing, interfacing and transmitting all kinds of signals for interactive services using all applicable transmission media including community antenna television (CATV) and master antenna television/satellite master antenna television (MATV/SMATV) networks.

This Technical Report describes the following:

- the functional elements and structure of the cabling, external to homes, supporting community antenna television (CATV) and master antenna television/satellite master antenna television (MATV/SMATV) networks in accordance with N 60728-1;
- the location and accommodation of the home network interface (HNI) in accordance with EN 60728-1;
- requirements for additional cabling performants requirements (i.e. insertion loss slope between 47 MHz and 862 MHz) and necessary amendments of the reference implementations of generic cabling within the home in accordance with EN 50173-4 in order to support the CATV, MATV/SMATV networks in accordance with EN 60728-1.

1 Scope

This Technical Report describes the following:

- a) the functional elements and structure of the cabling, external phomes, supporting community antenna television (CATV) and master antenna television/satellite master antenna television (MATV/SMATV) networks in accordance with EN 60728-1:
- b) the location and accommodation of the home network interface (HNI) in accordance with EN 60728-1;
- c) requirements for additional cabling performance requirements (i.e. insertion loss slope between 47 MHz and 862 MHz) and necessary amendments of the reference implementations of generic cabling within the home in accordance with EN 50173-4 in order to support the CATV, MATV/SMATV networks in accordance with EN 60728-1.

Safety (electrical safety and protection, optical power, fire, etc.) and electromagnetic compatibility (EMC) requirements are outside the scope of this Technical Report and are covered by standards and regulations. However information given in this Technical Report may be of assistance in meeting these standards and regulations.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50173-1:2007 Information technology – Generic cabling systems – Part 1: General requirements

EN 50173-4 Information technology – Generic cabling systems – Part 4: Homes

EN 50174 series normation technology – Cabling installation

EN 60728-1:2008, Čable networks for television signals, sound signals and interactive services – Part 1: System performance of forward paths (IEC 60728-1:2007)

EN 60728-1-1:2010, Cable networks for television signals, sound signals and interactive services – Part 1-1: RF cabling for two way home networks (IEC 60728-1-1:2010)

EN 60728-5, Cable networks to television signals, sound signals and interactive services – Part 5: Headend equipment (IEC 60728-5:2007)

EN 60728-11, Cable networks for television signals, sound signals and interactive services – Part 11: Safety (IEC 60728-11:2005, modified)

3 Definitions and abbreviations

3.1 Definitions

For the purposes of this document the following definitions apply in addition to those of EN 50173-1 and EN 50173-4.

3.1.1

branch feeder

feeder used for connecting a distribution point to a building network interface (BNI) or home network interface (HNI), as appropriate

3.1.2

building network

network for transmission of television signal, sound signals and interactive services inside a multi-dwelling building (excluding the home networks within the dwellings)

3.1.3

building network interface

interface between external network and the building network within a multi-dwelling building for the network for the transmission of television signal, sound signals and interactive services

NOTE This point is also called "transfer point" or "external network interface".

3.1.4

community antenna television

system which is designed to provide sound and television signals received by terrestrial, satellite antennas or provided by locally generated sources to the outlets of a large group of buildings