

TECHNICAL REPORT

CLC/TR 50426

RAPPORT TECHNIQUE

TECHNISCHER BERICHT

December 2004

ICS 13.230; 29.260.20; 33.060.20

English version

**Assessment of inadvertent initiation of bridge wire
electro-explosive devices by radio-frequency radiation –
Guide**

Evaluation de la création
par inadvertance de dispositifs
électro-explosifs par pont métallique,
par rayonnement de radiofréquence –
Guide

Leitfaden zur Verhinderung
des unbeabsichtigten Auslösens
einer Zündeinrichtung mit Brückendraht
durch hochfrequente Strahlung

This Technical Report was approved by CENELEC on 2004-08-28.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

This Technical Report was prepared by the Technical Committee CENELEC TC 31, Electrical apparatus for explosive atmospheres - General requirements.

The text of the draft was submitted to the formal vote and was approved by CENELEC as CLC/TR 50426 on 2004-08-28.

This document is a preview generated by EVS

Contents

Introduction.....	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
4 Symbols and abbreviations.....	8
4.1 Modulation codes	8
4.2 Polarization codes.....	9
5 General considerations	9
5.1 Radio-frequency hazard	9
5.2 Philosophy of the systematic method of approach	10
5.3 Responsibility for making the hazard assessment.....	10
5.4 Recommended practices for radio silence in offshore operations.....	11
6 Transmitters and transmitter output parameters.....	11
6.1 Types of transmitters.....	11
6.2 Frequency range	11
6.3 Transmitter output power.....	12
6.4 Antenna gain.....	12
6.5 Modulation factors.....	12
6.5.1 General	12
6.5.2 Frequency modulation (FM).....	12
6.5.3 Amplitude modulation (AM).....	12
6.5.4 Single sideband (SSB) operation.....	13
6.5.5 Pulsed radar.....	13
7 Circuits for blasting and well perforation	13
7.1 General	13
7.2 Typical blasting circuit layouts.....	14
7.2.1 General	14
7.2.2 Extended line blasts	14
7.2.3 Benching or 3-dimensional blasts	15
7.2.4 Multipattern blasts	16
7.2.5 Shaft sinking.....	16
7.2.6 Demolition work.....	17
7.3 Circuits formed during well-perforating using wireline	18
8 Electro-explosive devices	21
8.1 General	21
8.2 Commercial EED	21
8.3 EED hazard threshold	23
8.4 Common mode operation	24
9 Methods of assessment for determining potential RF ignition hazards on a site where EED are used	24
9.1 General.....	24

9.2	Basis of the theoretical assessments for land sites.....	28
9.2.1	General.....	28
9.3	Initial assessment for land sites.....	36
9.3.1	Initial assessment of the risk from a particular transmitter site.....	36
9.3.2	Initial assessment for a particular site using EED.....	36
9.4	Full assessment procedure for land sites.....	37
9.4.1	Procedure.....	37
9.4.2	Information to be obtained.....	37
9.4.3	Calculation of effective field strength.....	38
9.5	Safe field strength.....	45
9.5.1	General.....	45
9.5.2	Single EED.....	45
9.5.3	Single EED with extended leading wires.....	46
9.5.4	EED in typical quarry/demolition firing circuits.....	46
9.5.5	EED in well-perforating drilling operations.....	61
9.6	Multiple transmissions.....	63
9.6.1	General.....	63
9.6.2	Multiple-transmission assessments for quarry/demolition sites.....	64
9.6.3	Multiple transmission assessments for well-perforating drilling operations... ..	65
9.7	Assessments for offshore drilling operations.....	68
10	Practical on-site testing.....	68
11	Safety procedures.....	69
11.1	General procedures.....	69
11.2	Alternative means of firing.....	69
12	Special applications.....	69
12.1	Semi-permanent installations.....	69
12.2	Flammable hazard situations.....	69
12.3	Use of transmitters in mines and quarries.....	70
12.4	Safety in transit.....	70
Annex A	(informative) Extraction of energy from the electromagnetic field.....	71
Annex B	(informative) Measurement of electromagnetic fields.....	72
Annex C	(informative) Sources of information and addresses of advisory bodies - UK ONLY.....	76
Annex D	(informative) Electromagnetic radiated fields and examples of radiating antennas and unintended receiving antenna characteristics.....	78
Annex E	(informative) The effective resistance of the leading wires of an EED.....	86
Annex F	(informative) Derivation of minimum distances of safe approach for Table 2 and Table 3.....	92
Annex G	(informative) Ground-wave propagation (vertical polarization): calculation of field strength.....	94
Annex H	(informative) Worked examples to demonstrate the effects of antenna gain.....	96
Annex I	(informative) The effects of leading wire resistance, safety resistors and the use of EED with different characteristics.....	97
Annex J	(informative) Derivation of Figure 12a) to Figure 12g) for EED alone incorporating the resistance of leading wires and safety resistances.....	100
	Bibliography.....	101

Introduction

Electromagnetic waves produced by radio-frequency (RF) transmitters (e.g. radio, television and radar) will induce electric currents and voltages in any firing circuit including leading wires of the electro-explosive device (EED) on which they impinge. The magnitude of the induced current and voltages depends upon the configuration of the firing circuit and leading wires relative to the wavelength of the transmitted signal and on the strength of the electromagnetic field. If the induced current which is transferred to the EED is in excess of the no fire current then the EED could initiate. This European Technical Report provides a systematic approach to assist transmitter operators, quarry managers and all others concerned with a logical method for the assessment and elimination of the initiation of EED by RF. The assessment procedures contained in this European Technical Report are based on measurements of the powers and current that can be extracted from typical firing circuits and leading wires and on the physical electrical parameters of various types of EED.

1 Scope

This European Technical Report provides guidance on assessing the possibility of inadvertent extraction of energy from an electromagnetic field propagated from radio frequency (RF), radar or other transmitter antennas and the coupling of this energy to an electro-explosive device (EED) in a manner capable of causing initiation. The frequency range covered by this European Technical Report is 9 kHz to 60 GHz. This European Technical Report only applies to bridge-wire devices which are directly initiated by radio frequency current and does not apply to special detonators, for example, electronic detonators. It does not cover the similar hazard arising from electromagnetic fields generated by other means, for example electric storms, electricity generating plant or power transmission lines.

This European Technical Report does not apply to the following equipment:

- air bag igniters for automotive applications (including the igniters before they are fitted);
- special pyrotechnic devices;
- pyromechanisms;
- igniters for fireworks;
- special military devices;
- special safety equipment.

NOTE The methods of assessment from 9 GHz to 60 GHz are based on extrapolation of data for frequencies below 9 GHz.

2 Normative references

No normative references are made in this standard.

3 Terms and definitions

For the purposes of this European Technical Report the following terms and definitions apply.

3.1

duty cycle

product of pulse duration (in seconds) and the pulse repetition frequency (in pulses per second)

3.2

electro-explosive device (EED)

one shot explosive or pyrotechnic device initiated by the application of electrical energy

NOTE EED is used to refer to either a single electro-explosive device or several devices, to comply with general practice within the industry.

3.3

hazard

potential source of danger to life, limb or health, or of discomfort to a person or persons, or of damage to property

3.4

safe distance

distance outside which it is considered that there is no potential hazard