### **TECHNICAL REPORT**

## **CLC/TR 50460**

### RAPPORT TECHNIQUE

## **TECHNISCHER BERICHT**

August 2005

ICS 33.060.40

English version

## Cable networks for television signals, sound signals and interactive services – System guidelines for analogue optical transmission systems

Réseaux de distribution par câbles pour signaux de télévision, signaux de radiodiffusion sonore et services interactifs – Lignes directrices pour les systèmes de transmission optique analogiques Kabelnetze für Fernsehsignale, Tonsignale und interaktive Dienste – System-Leitfaden für analoge optische Übertragungssysteme

This Technical Report was approved by CENELEC on 2005-05-21.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

# CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

#### **Foreword**

Standards are very important sources of information on terms, definitions and minimum requirements for technical products. EN 60728-6 is such a standard for optical equipment used in cable networks for television signals, sound signals and interactive services. However, a lot of additional information and knowledge is needed for designing and planning complete optical transmission systems. This kind of information is not suitable for a standard because system engineers need freedom in their methods of finding economical solutions for special needs. CENELEC TC 209 therefore decided to develop this Technical Report which provides guidelines in how to use EN 60728-6 for planning analogue optical transmission systems.

This Technical Report was prepared by the Technical Committee CENELEC TC 209, Cable networks for television signals, sound signals and interactive services.

The text of the draft was submitted to the formal vote and was approved by CENELEC as Saprouion Sonorated De Files CLC/TR 50460 on 2005-05-21.

### Contents

1	Scop	e	5			
	1.1	General	5			
	1.2	Scope of this Technical Report	5			
2 Normative references						
3	Terms, definitions, symbols and abbreviations					
	3.1	Symbols	6			
	3.2	Abbreviations	6			
4	Topologies used for optical transmission systems in cable networks					
	4.1	Point to point system	7			
	4.2	Point to multi-point system	7			
	4.3	Multi-point to point system	7			
	4.4	Real wavelength division multiplex system				
	4.5	Combinations	8			
5	Influences of equipment and fibre parameters on the system performance					
6	Optic	al modulation index	9			
	6.1	Single wavelength system				
	6.2	WDM systems	11			
	6.3	Choosing the right input level at the transmitter				
7						
	7.1	Short haul links with a single transmitter12				
	7.2	Long haul point to point link	13			
		7.2.1 Long haul links with DFB lasers	13			
		7.2.2 Long haul links with externally modulated transmitters				
	7.3	Multiple transmitter systems (WDM)				
	7.4					
8						
	8.1	Composite Second Order (CSO)				
		8.1.1 CSO of 1 310 nm systems				
		8.1.2 CSO of 1 550 nm systems				
	8.2	Composite Triple Beat (CTB)				
9		ess				
10	) Outpi	ut level	19			
Ar	nex A	(informative) Brillouin scattering in optical fibres	20			
		(informative) Noise sources of optical transmission systems				
	B.1	Intensity noise				
	B.2	Shot noise of the receiver				
	B.3	Thermal noise				
	B.4	Carrier to noise ratio				

C.1 Non-linear products definition C.2 Non-linear products weighting C.3 Distortion generators in direct modulation cable network transmissions C.4 Third order modelling C.5 "Summation" of distortion products  Bibliography  Figure 1 - Point to point (PTP) system  Figure 2 - Point to multi-point (PMP) system  Figure 3 - Multipoint-to-point (WDM) system  Figure 3 - Definition of OMI for an optical transmitter  Figure 5 - Definition of OMI for an optical transmitter  Figure C.1 - (a) second and (b) third order distortion of Volterra series expansion  Figure C.2 - Weighted second and third order distortions repartition for the 42 carriers frequency allocation map defined in EN 50083-3 (software window capture)  Figure C.3 - Polarisation-mode dispersion in single-mode fibre  Figure C.4 - static curve of a laser showing the clipping effect.  Figure C.5 - Transmitted and backscattered power in the range of the Brillouin threshold  Figure C.6 - Cause of self phase modulation.  Figure C.7 - CSO caused by laser chirping and chromatic dispersion  Figure C.9 - CSO degradation with PDL = 0.5 dB [12].  Figure C.10 - Simulated and measured intermodulation due to laser clipping  Figure C.11 - Zoom on a CTB.  Table 1 - Interdependencies between equipment and system properties and the performance parameters.  Table C.1 - Weightings of HD2, HD3, IMD2 and IMD3	
C.3 Distortion generators in direct modulation cable network transmissions.  C.4 Third order modelling	27
C.4 Third order modelling  C.5 "Summation" of distortion products  Bibliography  Figure 1 - Point to point (PTP) system  Figure 2 - Point to multi-point (PMP) system  Figure 3 - Multipoint-to-point (WDM) system  Figure 4 - Real WDM system  Figure 5 - Definition of OMI for an optical transmitter  Figure C.1 - (a) second and (b) third order distortion of Volterra series expansion  Figure C.2 - Weighted second and third order distortions repartition for the 42 carriers frequency allocation map defined in EN 50083-3 (software window capture).  Figure C.3 - Polarisation-mode dispersion in single-mode fibre  Figure C.4 - static curve of a laser showing the clipping effect  Figure C.5 - Transmitted and backscattered power in the range of the Brillouin threshold  Figure C.7 - CSO caused by laser chirping and chromatic dispersion  Figure C.8 - CSO degradation without PDL  Figure C.9 - CSO degradation with PDL = 0,5 dB [12]  Figure C.10 - Simulated and measured intermodulation due to laser clipping  Figure C.11 - Zoom on a CTB  Table 1 - Interdependencies between equipment and system properties and the performance parameters	21
C.5 "Summation" of distortion products	28
Figure 1 - Point to point (PTP) system  Figure 2 - Point to multi-point (PMP) system  Figure 3 - Multipoint-to-point (WDM) system  Figure 4 - Real WDM system  Figure 5 - Definition of OMI for an optical transmitter  Figure C.1 - (a) second and (b) third order distortion of Volterra series expansion  Figure C.2 - Weighted second and third order distortions repartition for the 42 carriers frequency allocation map defined in EN 50083-3 (software window capture)  Figure C.3 - Polarisation-mode dispersion in single-mode fibre  Figure C.4 - static curve of a laser showing the clipping effect  Figure C.5 - Transmitted and backscattered power in the range of the Brillouin threshold  Figure C.6 - Cause of self phase modulation  Figure C.7 - CSO caused by laser chirping and chromatic dispersion  Figure C.9 - CSO degradation without PDL  Figure C.9 - CSO degradation with PDL = 0,5 dB [12]  Figure C.10 - Simulated and measured intermodulation due to laser clipping  Figure C.11 - Zoom on a CTB	37
Figure 1 - Point to point (PTP) system  Figure 2 - Point to multi-point (PMP) system  Figure 3 - Multipoint-to-point (WDM) system  Figure 4 - Real WDM system  Figure 5 - Definition of OMI for an optical transmitter  Figure C.1 - (a) second and (b) third order distortion of Volterra series expansion  Figure C.2 - Weighted second and third order distortions repartition for the 42 carriers frequency allocation map defined in EN 50083-3 (software window capture)  Figure C.3 - Polarisation-mode dispersion in single-mode fibre  Figure C.4 - static curve of a laser showing the clipping effect  Figure C.5 - Transmitted and backscattered power in the range of the Brillouin threshold  Figure C.6 - Cause of self phase modulation  Figure C.7 - CSO caused by laser chirping and chromatic dispersion  Figure C.9 - CSO degradation without PDL  Figure C.9 - CSO degradation with PDL = 0,5 dB [12]  Figure C.10 - Simulated and measured intermodulation due to laser clipping  Figure C.11 - Zoom on a CTB	38
Figure 1 - Point to point (PTP) system  Figure 2 - Point to multi-point (PMP) system  Figure 3 - Multipoint-to-point (WDM) system  Figure 4 - Real WDM system  Figure 5 - Definition of OMI for an optical transmitter  Figure C.1 - (a) second and (b) third order distortion of Volterra series expansion  Figure C.2 - Weighted second and third order distortions repartition for the 42 carriers frequency allocation map defined in EN 50083-3 (software window capture)  Figure C.3 - Polarisation-mode dispersion in single-mode fibre  Figure C.4 - static curve of a laser showing the clipping effect  Figure C.5 - Transmitted and backscattered power in the range of the Brillouin threshold  Figure C.6 - Cause of self phase modulation  Figure C.7 - CSO caused by laser chirping and chromatic dispersion  Figure C.9 - CSO degradation without PDL  Figure C.9 - CSO degradation with PDL = 0,5 dB [12]  Figure C.10 - Simulated and measured intermodulation due to laser clipping  Figure C.11 - Zoom on a CTB	
Figure 2 - Point to multi-point (PMP) system	40
Figure 2 - Point to multi-point (PMP) system	_
Figure 3 - Multipoint-to-point (WDM) system.  Figure 4 - Real WDM system.  Figure 5 - Definition of OMI for an optical transmitter  Figure C.1 - (a) second and (b) third order distortion of Volterra series expansion.  Figure C.2 - Weighted second and third order distortions repartition for the 42 carriers frequency allocation map defined in EN 50083-3 (software window capture).  Figure C.3 - Polarisation-mode dispersion in single-mode fibre.  Figure C.4 - static curve of a laser showing the clipping effect.  Figure C.5 - Transmitted and backscattered power in the range of the Brillouin threshold.  Figure C.6 - Cause of self phase modulation.  Figure C.7 - CSO caused by laser chirping and chromatic dispersion.  Figure C.8 - CSO degradation without PDL.  Figure C.9 - CSO degradation with PDL = 0,5 dB [12].  Figure C.10 - Simulated and measured intermodulation due to laser clipping.  Figure C.11 - Zoom on a CTB.	
Figure 4 - Real WDM system	
Figure 5 - Definition of OMI for an optical transmitter  Figure C.1 - (a) second and (b) third order distortion of Volterra series expansion  Figure C.2 - Weighted second and third order distortions repartition for the 42 carriers frequency allocation map defined in EN 50083-3 (software window capture)  Figure C.3 - Polarisation-mode dispersion in single-mode fibre  Figure C.4 - static curve of a laser showing the clipping effect  Figure C.5 - Transmitted and backscattered power in the range of the Brillouin threshold  Figure C.6 - Cause of self phase modulation  Figure C.7 - CSO caused by laser chirping and chromatic dispersion  Figure C.8 - CSO degradation without PDL  Figure C.9 - CSO degradation with PDL = 0,5 dB [12]  Figure C.10 - Simulated and measured intermodulation due to laser clipping  Figure C.11 - Zoom on a CTB	
Figure C.1 - (a) second and (b) third order distortion of Volterra series expansion  Figure C.2 - Weighted second and third order distortions repartition for the 42 carriers frequency allocation map defined in EN 50083-3 (software window capture)  Figure C.3 - Polarisation-mode dispersion in single-mode fibre  Figure C.4 - static curve of a laser showing the clipping effect  Figure C.5 - Transmitted and backscattered power in the range of the Brillouin threshold  Figure C.6 - Cause of self phase modulation  Figure C.7 - CSO caused by laser chirping and chromatic dispersion  Figure C.8 - CSO degradation without PDL  Figure C.9 - CSO degradation with PDL = 0,5 dB [12]  Figure C.10 - Simulated and measured intermodulation due to laser clipping  Figure C.11 - Zoom on a CTB	
Figure C.2 - Weighted second and third order distortions repartition for the 42 carriers frequency allocation map defined in EN 50083-3 (software window capture)	
allocation map defined in EN 50083-3 (software window capture)	27
Figure C.3 - Polarisation-mode dispersion in single-mode fibre  Figure C.4 - static curve of a laser showing the clipping effect  Figure C.5 - Transmitted and backscattered power in the range of the Brillouin threshold  Figure C.6 - Cause of self phase modulation  Figure C.7 - CSO caused by laser chirping and chromatic dispersion  Figure C.8 - CSO degradation without PDL  Figure C.9 - CSO degradation with PDL = 0,5 dB [12]  Figure C.10 - Simulated and measured intermodulation due to laser clipping  Figure C.11 - Zoom on a CTB	28
Figure C.4 - static curve of a laser showing the clipping effect  Figure C.5 - Transmitted and backscattered power in the range of the Brillouin threshold  Figure C.6 - Cause of self phase modulation  Figure C.7 - CSO caused by laser chirping and chromatic dispersion  Figure C.8 - CSO degradation without PDL  Figure C.9 - CSO degradation with PDL = 0,5 dB [12]  Figure C.10 - Simulated and measured intermodulation due to laser clipping  Figure C.11 - Zoom on a CTB  Figure C.11 - Interdependencies between equipment and system properties and the performance parameters	
Figure C.5 - Transmitted and backscattered power in the range of the Brillouin threshold	
Figure C.6 - Cause of self phase modulation  Figure C.7 - CSO caused by laser chirping and chromatic dispersion  Figure C.8 - CSO degradation without PDL  Figure C.9 - CSO degradation with PDL = 0,5 dB [12]  Figure C.10 - Simulated and measured intermodulation due to laser clipping  Figure C.11 - Zoom on a CTB  Figure C.11 - Interdependencies between equipment and system properties and the performance parameters	
Figure C.7 - CSO caused by laser chirping and chromatic dispersion  Figure C.8 - CSO degradation without PDL  Figure C.9 - CSO degradation with PDL = 0,5 dB [12]  Figure C.10 - Simulated and measured intermodulation due to laser clipping  Figure C.11 - Zoom on a CTB  Figure C.11 - Interdependencies between equipment and system properties and the performance parameters	
Figure C.8 - CSO degradation without PDL  Figure C.9 - CSO degradation with PDL = 0,5 dB [12]  Figure C.10 - Simulated and measured intermodulation due to laser clipping  Figure C.11 - Zoom on a CTB  Figure C.11 - Interdependencies between equipment and system properties and the performance parameters	
rigure C.10 - Simulated and measured intermodulation due to laser clipping	
Figure C.11 - Zoom on a CTB  Table 1 - Interdependencies between equipment and system properties and the performance parameters	34
able 1 - Interdependencies between equipment and system properties and the performance parameters	35
parameters	39
parameters	
	0
able C.1 - Weightings of Tib2, Tib3, IIVib2 and IIVib3	

### 1 Scope

#### 1.1 General

Standards of the EN 50083 and EN 60728 series deal with cable networks for television signals, sound signals and interactive services including equipment, systems and installations

- for headend-reception, processing and distribution of sound and television signals and their associated data signals and
- for processing, interfacing and transmitting all kinds of signals for interactive services using all applicable transmission media.

All kinds of networks like

- CATV-networks
- MATV- and SMATV-networks
- individual receiving networks

and all kinds of equipment, systems and installations installed in such networks, are within this scope.

The extent of this standardisation work is from the antennas, special signal source inputs to the headend or other interface points to the network up to the terminal input.

The standardisation of any user terminals (i.e. tuners, receivers, decoders, multimedia terminals etc.) as well as of any coaxial and optical cables and accessories thereof is excluded.

#### 1.2 Scope of this Technical Report

This Technical Report provides guidelines and procedures for determining the overall performance of optical transmissions systems used in cable networks for television signals, sound signals and interactive services. It is based on the requirements for optical equipment defined in the standard EN 60728-6 (Cable networks for television signals, sound signals and interactive services – Part 6: Optical equipment) and should be used together with this standard. The information provided is meant to help field engineers and network planners (system designers) in planning and designing optical systems. Though this content is less dense than in a standard, basic knowledge about system parameters of cable networks is needed.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50083-3	2002	Cable networks for television signals, sound signals and interactive services - Part 3: Active wideband equipment for coaxial cable networks
EN 50083-7 + A1	1996 2000	Cable networks for television signals, sound signals and interactive services - Part 7, System performance
EN 60728-6	2003	Cable networks for television signals, sound signals and interactive services - Part 6, Optical equipment (IEC 60728-6:2003)
EN 60793-2	2004	Optical fibres - Part 2: Product specifications - General (IEC 60793-2:2003)
IEC/TR 61931	1998	Fibre optics – Terminology