

**Railway applications –  
Communication, signalling and processing systems –  
European Rail Traffic Management System –  
Driver-Machine Interface  
Part 2: Ergonomic arrangements of ERTMS/GSM-R information**

Applications ferroviaires –  
Systèmes de signalisation, de  
télécommunications et de traitement –  
Système européen de gestion du trafic  
ferroviaire –  
Interface de conduite  
Partie 2: Dispositions ergonomiques  
des informations ERTMS/GSM-R

Bahnanwendungen –  
Telekommunikationstechnik, Signal-  
technik und Datenverarbeitungssysteme –  
Europäisches Leitsystem für den  
Schienenverkehr –  
Mensch-Maschine Schnittstelle  
Teil 2: Ergonomische Anordnung  
der ERTMS/GSM-R Informationen

This Technical Specification was approved by CENELEC on 2005-05-07.

CENELEC members are required to announce the existence of this TS in the same way as for an EN and to make the TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Central Secretariat: rue de Stassart 35, B - 1050 Brussels**

## Foreword

This Technical Specification was prepared by SC 9XA, Communication, signalling and processing systems, of Technical Committee CENELEC TC 9X, Electrical and electronic applications for railways.

The text of the draft was submitted to the vote and was approved by CENELEC as CLC/TS 50459-3 on 2005-05-07.

The following date was fixed:

- latest date by which the existence of the CLC/TS  
has to be announced at national level (doa) 2005-11-07

This Technical Specification has been prepared under mandates M/024 and M/334 given to CENELEC by the European Commission and the European Free Trade Association.

## Contents

	Page
Introduction .....	5
1 Scope.....	6
2 Normative references .....	6
3 Terms, definitions and abbreviated terms .....	7
3.1 Definitions .....	7
3.2 Symbols and abbreviated terms.....	7
4 General DMI-related principles.....	7
4.1 General ergonomic principles.....	7
4.2 DMI possibilities.....	8
4.3 Hardware .....	8
4.4 Task structure.....	8
4.5 Flashing .....	9
4.6 Sounds .....	9
4.7 Lists .....	10
5 GSM-R functions shown on the integrated DMI .....	10
5.1 Introduction .....	10
5.2 General functions .....	11
5.3 Call-related functions: outgoing.....	15
5.4 Call-related functions: incoming.....	27
5.5 Other call related functions.....	35
5.6 Special functions not required directly by GSM-R.....	42
5.7 Summary of key sequences .....	42
Annex A (informative) Examples of DMI solutions .....	44
A.1 Standalone solution on a touch screen device.....	44
A.2 Combined / integrated solution on a touch screen device .....	45
A.3 Vertical standalone solution with soft keys.....	46
A.4 Horizontal standalone solution with soft keys .....	47
Bibliography .....	48
Figure 1 — Areas of the DMI Display .....	9
Figure 2 — Register Train Running Number.....	12
Figure 3 — Loss of Radio Network .....	14
Figure 4 — Window with no call activity .....	15
Figure 5 — Call status information during outgoing call to Primary Controller .....	15
Figure 6 — Call Primary Controller .....	17
Figure 7 — Group Call to other drivers in the same area .....	18
Figure 8 — Group Call to Group 846 .....	19
Figure 9 — Broadcast Call to Group 846 .....	20
Figure 10 — Areas on the second level .....	21
Figure 11 — Selecting other drivers on train.....	22
Figure 12 — Drivers connected in a Multi-party Call.....	22
Figure 13 — Calling a stored number .....	23
Figure 14 — Call a valid number .....	24
Figure 15 — Call the last contacted address .....	25
Figure 16 — Accessing train staff menu .....	26
Figure 17 — Selection of member of staff.....	26
Figure 18 — Receiving a point-to-point call .....	27
Figure 19 — Receiving a Broadcast Call .....	28
Figure 20 — Receiving a Group Call.....	29
Figure 21 — Receiving a Railway Emergency Call.....	30
Figure 22 — Receiving a text message .....	31
Figure 23 — Multi-party call.....	32
Figure 24 — Put call on hold and forward call.....	33
Figure 25 — Answer incoming call that is waiting .....	34

Figure 26 — Initiate Public Address call .....	35
Figure 27 — Initiate Intercom .....	36
Figure 28 — Activate GSM-R Shunting Group Number 20 .....	36
Figure 29 — Selecting a language .....	37
Figure 30 — Select Direct Mode Radio Channel 3 .....	38
Figure 31 — Enter GSM-R Shunting Mode .....	39
Figure 32 — Forward call to hand-portable .....	40
Figure 33 — Third level menu .....	41
Figure A.1 — Basic functions on first level .....	44
Figure A.2 — Last calls overview on second level .....	44
Figure A.3 — Secondary functions on third level .....	44
Figure A.4 — Free dial window on third level .....	44
Figure A.5 — Basic functions on first level .....	45
Figure A.6 — Last calls overview on second level .....	45
Figure A.7 — Secondary functions on third level .....	45
Figure A.8 — Free dial window on third level .....	45
Figure A.9 — Vertical Standalone device .....	46
Figure A.10 — Horizontal standalone device .....	47
Table 1 — Description of functions used in each area .....	10
Table 2 — Summary of Key Sequences .....	42

This document is a preview generated by EVS

## Introduction

This Technical Specification forms Part 3 of a series, the other parts being:

- CLC/TS 50459-1 for ergonomic principles for the presentation of ERTMS/ETCS/GSM-R information
- CLC/TS 50459-2, for ergonomic arrangements of ERTMS/ETCS information
- CLC/TS 50459-4 for data entry procedure for ERTMS/ETCS/GSM-R
- CLC/TS 50459-5 for symbols for ERTMS/ETCS/GSM-R
- CLC/TS 50459-6 for audible information for ERTMS/ETCS/GSM-R

These Technical Specifications contain the ergonomic arrangements of information on the ERTMS DMI Display. Most items are illustrated with an example.

## 1 Scope

This Technical Specification describes from an ergonomic point of view how ERTMS information shall be arranged and displayed. This Technical Specification describes more ergonomic details than currently provided by the ERTMS/ETCS/GSM-R specifications.

This Technical Specification defines the ergonomics for the Driver-Machine Interface (DMI) for the ERTMS/ETCS Train Control System, and for the integrated ERTMS/GSM-R Train Control and Train Radio Systems, and for the stand alone ERTMS/GSM-R Train Radio Systems and for other technical systems currently provided on the engines.

The ergonomics covers the

- general arrangements (dialogue structure, sequences, layout philosophy, colour philosophy),
- symbols,
- audible information,
- data entry arrangements.

The aims of the ERTMS/ETCS/GSM-R Train Control and Train Radio Systems are standardised systems facilitating interoperable movement of trains and permitting economies of scale in procurement and operations. The objective of this Technical Specification is to define the minimum requirements on the DMI that are necessary to enable these objectives to be achieved. Hence the Technical Specification is limited to ergonomic considerations and does not define the technology to be used for the implementation.

The reasons for defining the ergonomics of the DMI are as follows:

- achieving harmonised and coherent presentation for ERTMS/ETCS and STM information. Given the large number of STM's requiring the use the ERTMS/ETCS DMI, only a harmonised approach is feasible;
- defining Driver-Machine Interface ergonomics that is compatible with agreed interoperable ERTMS specifications;
- to reduce the risk of incorrect operation by a driver working with different trains fitted with ERTMS/ETCS and ERTMS/GSM-R;
- facilitating train operation with a unified ergonomics, hence reducing the cost of driver training.

This Technical Specification is applicable on all trains fitted with the ERTMS/ETCS and also for trains fitted with train radio (GSM-R) DMI.

The scope of Part 3 of the Technical Specification CLC/TS 50459 series is to define ergonomic arrangements of ERTMS/GSM-R information only.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

*Council Directive 96/48/EC of 23 July 1996 on the interoperability of the trans-European high-speed rail system, Official Journal L 235 , 17/09/1996 P. 0006 – 0024*

*CLC/TS 50459-1, Railways applications – Communication, signalling and processing systems – European Rail Traffic Management System – Driver-Machine Interface – Part 1: Ergonomic principles for the presentation of ERTMS/ETCS/GSM-R information*

CLC/TS 50459-2, *Railways applications – Communication, signalling and processing systems - European Rail Traffic Management System - Driver-Machine Interface - Part 2: Ergonomic arrangements of ERTMS/ETCS information*

CLC/TS 50459-4, *Railways applications – Communication, signalling and processing systems - European Rail Traffic Management System - Driver-Machine Interface - Part 4: Data entry for the ERTMS/ETCS/GSM-R systems*

CLC/TS 50459-5, *Railways applications – Communication, signalling and processing systems - European Rail Traffic Management System - Driver-Machine Interface - Part 5: Symbols*

CLC/TS 50459-6, *Railways applications – Communication, signalling and processing systems - European Rail Traffic Management System - Driver-Machine Interface - Part 6: Audible information*

UIC 651, *Layout of driver's cabs in locomotives, railcars, multiple-unit trains and driving trailers*

### **3 Terms, definitions and abbreviated terms**

#### **3.1 Definitions**

For the purposes of this document, the terms and definitions given in CLC/TS 50459-1 apply.

#### **3.2 Symbols and abbreviated terms**

PA        Public Address

PTT       Push To Talk

NOTE     For practical reasons, in this document GSM-R is used instead of ERTMS/GSM-R.

### **4 General DMI-related principles**

#### **4.1 General ergonomic principles**

The GSM-R DMI shall follow the main ergonomic principles as described in CLC/TS 50459 -1.

All ERTMS/GSM-R DMI procedures and layout principles shall be consistent with the ERTMS/ETCS DMI and the ERTMS/ETCS DMI philosophy as far as it concerns the integrated ERTMS/ETCS/GSM-R DMI.

When there is a GSM-R call, this shall not disturb the ERTMS/ETCS information.

When there is a call to other on-train users/devices using GSM-R this, shall not disturb the ERTMS/ETCS information. This requirement is applicable to the integrated option only.

The principle for navigation for the integrated ERTMS/ETCS/GSM-R DMI shall be consistent with the rules defined in CLC/TS 50459-1. For the stand alone GSM-R DMI it is strongly recommended to have the same consistency.

Any additional requirements that are specific to GSM-R are defined in this clause.