



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

WORKSHOP AGREEMENT

CWA 13937-3

August 2000

ICS 35.240.40

J/eXtensions for Financial Services (J/XFS) for the Java Platform - Part
3: Magnetic Stripe & Chip Card Device Class Interface - Programmer's
Reference

This CEN Workshop Agreement can in no way be held as being an official standard
as developed by CEN National Members.

© 2000 CEN

All rights of exploitation in any form and by any means reserved world-wide for
CEN National Members

Ref. No CWA 13937-3:2000 E

Foreword

This CWA contains the specifications that define the J/eXtensions for Financial Services (J/XFS) for the Java™ Platform, as developed by the J/XFS Forum and endorsed by the CEN/ISSS J/XFS Workshop. J/XFS provides an API for Java applications which need to access financial devices. It is hardware independent and, by using 100% pure Java, also operating system independent.

The CEN/ISSS J/XFS Workshop gathers suppliers (among others the J/XFS Forum members), service providers as well as banks and other financial service companies. A list of companies participating in this Workshop and in support of this CWA is available from the CEN/ISSS Secretariat. The specification was agreed upon by the J/XFS Workshop Meeting of 1999-12-15/16 in Geneva and a subsequent electronic review by the Workshop participants, and the final version was sent to CEN for publication on 2000/06-21.

The specification is continuously reviewed and commented in the CEN/ISSS J/XFS Workshop. It is therefore expected that an update of the specification will be published in due time as a CWA, superseding this one. The information published in this CWA is furnished for informational purposes only. CEN/ISSS makes no warranty expressed or implied, with respect to this document. Updates of the specification will be available from the CEN/ISSS J/XFS Workshop public web pages pending their integration in a new version of the CWA (see: <http://www.cenorm.be/iss/worshop/j-XFS/cwa-updates>).

The J/XFS specifications are now further developed in the CEN/ISSS J/XFS Workshop. CEN/ISSS Workshops are open to all interested parties offering to contribute. Parties interested in participating should contact the CEN/ISSS Secretariat (iss@cenorm.be). To submit questions and comments for the J/XFS specifications, please contact the CEN/ISSS Secretariat (iss@cenorm.be) who will be forwarding them to the J/XFS Workshop.

Questions and comments can also be submitted to the members of the J/XFS Forum, who are all CEN/ISSS J/XFS Workshop members, through the J/XFS Forum web-site <http://www.jxfs.com>

This CWA is composed of the following parts:

- Part 1: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Base Architecture - Programmer's Reference
- Part 2: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Pin Keypad Device Class Interface - Programmer's Reference
- Part 3: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Magnetic Stripe & Chip Card Device Class Interface - Programmer's Reference
- Part 4: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Text Input/Output Device Class Interface - Programmer's Reference
- Part 5: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Cash Dispenser, Recycler and ATM Interface - Programmer's Reference
- Part 6: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Printer Device Class Interface - Programmer's Reference
- Part 7: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Alarm Device - Programmer's Reference
- Part 8: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Sensors and Indicators Unit Device Class Interface - Programmer's Reference
- Part 9: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Depository Device Class Interface - Programmer's Reference
- Part 10: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Check Reader/Scanner Device Class Interface - Programmer's Reference

Note: Java and all Java-based trademarks and logos are trademarks of Sun Microsystems, Inc. The Java Trademark Guidelines are currently available on the web at http://java.sun.com/nav/business/trademark_guidelines.html. All other trademarks are trademarks of their respective owners.

Contents

1	SCOPE.....	4
2	OVERVIEW	5
2.1	DESCRIPTION.....	5
2.2	CLASSES AND INTERFACES.....	7
2.3	SUPPORT CLASSES.....	8
3	DEVICE BEHAVIOR.....	9
3.1	DEVICE OPEN()	9
4	CLASSES AND INTERFACES.....	10
4.1	ACCESS TO PROPERTIES.....	10
4.2	EXCEPTIONS	10
4.3	IJXFSMAGSTRIPECONTROL.....	11
4.4	IJXFSCHIPCARDCONTROL.....	15
4.5	IJXFSMOTORIZEDCARD.....	19
4.6	IJXFSMSDSECURE.....	23
5	SUPPORT CLASSES.....	27
5.1	JXFSMSDTRACKS	27
5.2	JXFSMSDTRACKSELECTION	29
5.3	JXFSMSDREADDATA	30
5.4	JXFSCCDDATA	32
5.5	JXFSMSDWMDATA.....	33
5.6	JXFSMSDSECUREMODE	34
5.7	JXFSMSDREADDATASECURE.....	35
6	CODES	37
6.1	ERROR CODES	37
6.2	STATUS CODES.....	37
6.3	OPERATION CODES.....	38
6.4	CONSTANTS.....	38

1 Scope

This document describes the Magnetic Stripe Device (MSD) as well as Chip Card Device (CCD) classes based on the basic architecture of J/XFS which is similar to the JavaPOS architecture. It is event driven and asynchronous.

Three basic levels are defined in JavaPOS. For J/XFS this model is extended by a communication layer, which provides device communication that allows distribution of applications and devices within a network. So we have the following layers in J/XFS :

- Application
- Device Control and Device Manager
- Device Communication
- Device Service

Application developers program against control objects and the Device Manager which reside in the Device Control layer. This is the usual interface between applications and J/XFS devices. Device Control objects access the Device Manager to find an associated Device Service. Device Service objects provide the functionality to access the real device (i.e. like a device driver).

During application startup the Device Manager is responsible for locating the desired Device Service object and attaching this to the requesting Device Control object. Location and/or routing information for the Device Manager reside in a central repository.

To support Magnetic Stripe devices and Chip Card devices the basic Device Control structure is extended with various properties and methods specific to this device which are described on the following pages.