



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

WORKSHOP AGREEMENT

CWA 13937-6

August 2000

ICS 35.240.40

J/eXtensions for Financial Services (J/XFS) for the Java Platform - Part
6: Printer Device Class Interface - Programmer's Reference

This CEN Workshop Agreement can in no way be held as being an official standard
as developed by CEN National Members.

© 2000 CEN

All rights of exploitation in any form and by any means reserved world-wide for
CEN National Members

Ref. No CWA 13937-6:2000 E

Foreword

This CWA contains the specifications that define the J/eXtensions for Financial Services (J/XFS) for the Java™ Platform, as developed by the J/XFS Forum and endorsed by the CEN/ISSS J/XFS Workshop. J/XFS provides an API for Java applications which need to access financial devices. It is hardware independent and, by using 100% pure Java, also operating system independent.

The CEN/ISSS J/XFS Workshop gathers suppliers (among others the J/XFS Forum members), service providers as well as banks and other financial service companies. A list of companies participating in this Workshop and in support of this CWA is available from the CEN/ISSS Secretariat. The specification was agreed upon by the J/XFS Workshop Meeting of 1999-12-15/16 in Geneva and a subsequent electronic review by the Workshop participants, and the final version was sent to CEN for publication on 2000/06-21.

The specification is continuously reviewed and commented in the CEN/ISSS J/XFS Workshop. It is therefore expected that an update of the specification will be published in due time as a CWA, superseding this one. The information published in this CWA is furnished for informational purposes only. CEN/ISSS makes no warranty expressed or implied, with respect to this document. Updates of the specification will be available from the CEN/ISSS J/XFS Workshop public web pages pending their integration in a new version of the CWA (see: <http://www.cenorm.be/iss/wkshop/j-XFS/cwa-updates>).

The J/XFS specifications are now further developed in the CEN/ISSS J/XFS Workshop. CEN/ISSS Workshops are open to all interested parties offering to contribute. Parties interested in participating should contact the CEN/ISSS Secretariat (iss@cenorm.be). To submit questions and comments for the J/XFS specifications, please contact the CEN/ISSS Secretariat (iss@cenorm.be) who will be forwarding them to the J/XFS Workshop.

Questions and comments can also be submitted to the members of the J/XFS Forum, who are all CEN/ISSS J/XFS Workshop members, through the J/XFS Forum web-site <http://www.jxfs.com>

This CWA is composed of the following parts:

- Part 1: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Base Architecture - Programmer's Reference
- Part 2: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Pin Keypad Device Class Interface - Programmer's Reference
- Part 3: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Magnetic Stripe & Chip Card Device Class Interface - Programmer's Reference
- Part 4: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Text Input/Output Device Class Interface - Programmer's Reference
- Part 5: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Cash Dispenser, Recycler and ATM Interface - Programmer's Reference
- Part 6: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Printer Device Class Interface - Programmer's Reference
- Part 7: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Alarm Device - Programmer's Reference
- Part 8: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Sensors and Indicators Unit Device Class Interface - Programmer's Reference
- Part 9: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Depository Device Class Interface - Programmer's Reference
- Part 10: J/eXtensions for Financial Services (J/XFS) for the Java Platform - Check Reader/Scanner Device Class Interface - Programmer's Reference

Note: Java and all Java-based trademarks and logos are trademarks of Sun Microsystems, Inc. The Java Trademark Guidelines are currently available on the web at http://java.sun.com/nav/business/trademark_guidelines.html. All other trademarks are trademarks of their respective owners.

Contents

1	SCOPE.....	5
2	OVERVIEW	6
2.1	DESCRIPTION.....	6
2.2	CLASS HIERARCHY.....	7
2.3	CLASS AND INTERFACE SUMMARY.....	8
3	DEVICE BEHAVIOR.....	10
3.1	DEVICE OPEN().....	10
4	CLASSES AND INTERFACES.....	11
4.1	ACCESS TO PROPERTIES.....	11
4.2	EXCEPTIONS.....	11
4.3	IJXFSPRINTERCONTROL.....	12
4.3.1	Summary.....	12
4.3.2	Properties.....	13
4.3.3	Methods.....	14
4.3.4	Events.....	21
4.4	IJXFSJECT.....	23
4.4.1	Summary.....	23
4.4.2	Properties.....	23
4.4.3	Methods.....	24
4.4.4	Events.....	25
4.5	IJXFSRETRACT.....	26
4.5.1	Summary.....	26
4.5.2	Properties.....	26
4.5.3	Methods.....	27
4.5.4	Events.....	28
4.6	IJXFSMEDIATURN.....	29
4.6.1	Summary.....	29
4.6.2	Properties.....	29
4.6.3	Methods.....	30
4.7	IJXFSREAD.....	31
4.7.1	Summary.....	31
4.7.2	Properties.....	31
4.7.3	Methods.....	32
4.7.4	Events.....	34
5	SUPPORT CLASSES.....	35
5.1	JXFSPTRCTRLMEDIACAPABILITY.....	36
5.1.1	Summary.....	36
5.1.2	Properties.....	36
5.1.3	Methods.....	37
5.2	JXFSPTRCTRLTURNCAPABILITY.....	39
5.2.1	Summary.....	39
5.2.2	Properties.....	39
5.2.3	Methods.....	39
5.3	JXFSPTREXTENTCAPABILITY.....	41
5.3.1	Summary.....	41
5.3.2	Properties.....	41
5.3.3	Methods.....	41
5.4	JXFSPTRFIELD.....	42
5.4.1	Summary.....	42
5.4.2	Properties.....	42
5.5	JXFSPTRFIELDFAILURE.....	44
5.5.1	Summary.....	44
5.5.2	Properties.....	44
5.6	JXFSPTRFORM.....	45
5.6.1	Summary.....	45
5.6.2	Properties.....	46
5.7	JXFSPTRFORMSCONFIG.....	48
5.7.1	Summary.....	48

5.7.2	Properties	49
5.8	JXFSPTRIMAGE	51
5.8.1	Summary	51
5.8.2	Properties	51
5.9	JXFSPTRMAXRETRACTCAPABILITY	52
5.9.1	Summary	52
5.9.2	Properties	52
5.10	JXFSPTRMAXSTACKERCAPABILITY	53
5.10.1	Summary	53
5.10.2	Properties	53
5.11	JXFSPTRMEDIA	54
5.11.1	Summary	54
5.11.2	Properties	54
5.12	JXFSPTRMEDIAEXTENTS	58
5.12.1	Summary	58
5.12.2	Properties	58
5.13	JXFSPTRREADFORMCAPABILITY	59
5.13.1	Summary	59
5.13.2	Properties	59
5.13.3	Methods	59
5.14	JXFSPTRREADIMAGECAPABILITY	61
5.14.1	Summary	61
5.14.2	Properties	61
5.14.3	Methods	62
5.15	JXFSPTRRETRACTCOUNT	63
5.15.1	Summary	63
5.15.2	Properties	63
5.15.3	Methods	63
5.16	JXFSPTRWRITEFORMCAPABILITY	64
5.16.1	Summary	64
5.16.2	Properties	64
5.16.3	Methods	64
6	STATUS EVENT CLASSES	66
6.1	JXFSTHRESHOLDSTATUS	66
6.1.1	Summary	66
6.2	JXFSPTRLAMPSTATUS	68
6.2.1	Summary	68
6.2.2	Properties	68
6.2.3	Methods	69
6.3	JXFSMEDIASSTATUS	70
6.4	JXFSPTRSTATUS	71
6.4.1	Summary	71
6.4.2	Properties	71
6.4.3	Events	72
7	CODES	73
7.1	ERROR CODES	73
7.2	EXCEPTION CODES	74
7.3	STATUS CODES	74
7.4	CONSTANTS	76
7.5	OPERATION ID CODES	80
8	DEVICE SERVICE INTERFACE METHODS	81
8.1	FORM, FIELD AND MEDIA DEFINITIONS	82
9	INDEX	83

1 Scope

This document describes the printer device class based on the basic architecture of J/XFS which is similar to the JavaPOS architecture. It is event driven and asynchronous.

Three basic levels are defined in JavaPOS. For J/XFS this model is extended by a communication layer, which provides device communication that allows distribution of applications and devices within a network. So we have the following layers in J/XFS :

- Application
- Device Control and Manager
- Device Communication
- Device Service

Application developers program against control objects and the Device Manager which reside in the Device Control Layer. This is the usual interface between applications and J/XFS Devices. Device Control Objects access the Device Manager to find an associated Device Service. Device Service Objects provide the functionality to access the real device (i.e. like a device driver).

During application startup the Device Manager is responsible for locating the desired Device Service Object and attaching this to the requesting Device Control Object. Location and/or routing information for the Device Manager reside in a central repository.

To support printers the basic Device Control structure is extended with various properties and methods specific to this device which are described on the following pages.