
**Safety of machinery — Positioning of
safeguards with respect to the approach
speeds of parts of the human body**

*Sécurité des machines — Positionnement des moyens de protection
par rapport à la vitesse d'approche des parties du corps*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope.....	1
2 Normative references	2
3 Terms, definitions, symbols and abbreviated terms	2
3.1 Terms and definitions	2
3.2 Symbols and abbreviated terms	4
4 Methodology	5
5 General equation for the calculation of the overall system stopping performance and minimum distances	7
5.1 Overall system stopping performance	7
5.2 Minimum distance	8
6 Calculation of minimum distances for electro-sensitive protective equipment employing active opto-electronic protective systems.....	8
6.1 General	8
6.2 Detection zone orthogonal to the direction of approach	9
6.3 Detection zone parallel to the direction of approach	12
6.4 Detection zone angled to the direction of approach	14
6.5 Addressing possible circumventing of electro-sensitive protective equipment by reaching over the detection zone	16
6.6 Indirect approach — Path from detection zone to hazard zone restricted by obstacles.....	19
7 Method of calculating the positioning of pressure-sensitive mats or floors	21
7.1 General	21
7.2 Step mounting	22
8 Two-hand control devices	22
9 Interlocking guards without guard locking.....	22
Annex A (informative) Worked examples	24
Annex B (informative) Termination of hazardous machine functions.....	33
Annex C (informative) Example for considering indirect approaches	34
Annex D (informative) Measurement and calculation of overall system stopping performance	36
Annex E (informative) Number of beams and their height above the reference plane.....	38
Bibliography.....	39

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 13855 was prepared by Technical Committee ISO/TC 199, *Safety of machinery*.

This second edition cancels and replaces the first edition (ISO 13855:2002), which has been technically revised.

Introduction

The structure of safety standards in the field of machinery is as follows:

- a) type-A standards (basic safety standards) giving basic concepts, principles for design, and general aspects that can be applied to all machinery;
- b) type-B standards (generic safety standards) dealing with one safety aspect or one or more type(s) of safeguard that can be used across a wide range of machinery:
 - type-B1 standards on particular safety aspects (e.g. safety distances, surface temperature, noise);
 - type-B2 standards on safeguards (e.g. two-hand controls, interlocking devices, pressure-sensitive devices, guards);
- c) type-C standards (machine safety standards) dealing with detailed safety requirements for a particular machine or group of machines.

This document is a type-B standard as stated in ISO 12100-1.

The requirements of this document can be supplemented or modified by a type-C standard.

For machines which are covered by the scope of a type-C standard and which have been designed and built according to the requirements of that type-C standard, the following applies: if the requirements of that type-C standard deviate from the requirements in type-B standards, the requirements of that type-C standard take precedence over the provisions of other standards.

The effectiveness of certain types of safeguard described in this International Standard to minimize risk relies, in part, on the relevant parts of that equipment being correctly positioned in relation to the hazard zone. In deciding on these positions, a number of aspects are taken into account, such as:

- the necessity of a risk assessment according to ISO 14121-1;
- the practical experience in the use of the machine;
- the overall system stopping performance;
- the time taken to ensure the safe condition of the machine following operation of the safeguard, for example to stop the machine;
- the bio-mechanical and anthropometric data;
- any intrusion by a part of the body towards the hazard zone until the protective device is actuated;
- the path taken by the body part when moving from the detection zone towards the hazard zone;
- the possible presence of a person between the safeguard and the hazard zone;
- the possibility of undetected access to the hazard zone.

This document is a preview generated by EVS

Safety of machinery — Positioning of safeguards with respect to the approach speeds of parts of the human body

1 Scope

This International Standard establishes the positioning of safeguards with respect to the approach speeds of parts of the human body.

It specifies parameters based on values for approach speeds of parts of the human body and provides a methodology to determine the minimum distances to a hazard zone from the detection zone or from actuating devices of safeguards.

The values for approach speeds (walking speed and upper limb movement) in this International Standard are time tested and proven in practical experience. This International Standard gives guidance for typical approaches. Other types of approach, for example running, jumping or falling, are not considered in this International Standard.

NOTE 1 Other types of approach can result in approach speeds that are higher or lower than those defined in this International Standard.

Safeguards considered in this International Standard include:

- a) electro-sensitive protective equipment [see IEC 61496 (all parts)], including:
 - light curtains and light grids (AOPDs);
 - laser scanners (AOPDDR) and two-dimensional vision systems;
- b) pressure-sensitive protective equipment (see ISO 13856-1, ISO 13856-2 and ISO 13856-3), especially pressure-sensitive mats;
- c) two-hand control devices (see ISO 13851);
- d) interlocking guards without guard locking (see ISO 14119).

This International Standard specifies minimum distances from the detection zone, plane, line, point or interlocking guard access point to the hazard zone for hazards caused by the machine (e.g. crushing, shearing, drawing-in).

Protection against the risks from hazards arising from the ejection of solid or fluid materials, emissions, radiation and electricity are not covered by this International Standard.

NOTE 2 Anthropometric data from the 5th to the 95th percentile of persons of 14 years and older were used in the determination of the intrusion distance value “C” in the equations.

NOTE 3 The data in this International Standard are based on experience of industrial application; it is the responsibility of the designer to take this into account when using this International Standard for non-industrial applications.

NOTE 4 Data specifically for children have not been used in this International Standard. Until specific data are available for approach speeds for children, it is the responsibility of the designer to calculate the distances taking into account that children might be quicker and that a child might be detected later.

The International Standard is not applicable to safeguards (e.g. pendant two-hand control devices) that can be moved, without using tools, nearer to the hazard zone than the calculated minimum distance.

The minimum distances derived from this International Standard are not applicable to safeguards used to detect the presence of persons within an area already protected by a guard or electro-sensitive protective equipment.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12100-1, *Safety of machinery — Basic concepts, general principles for design — Part 1: Basic terminology, methodology*

ISO 13857:2008, *Safety of machinery — Safety distances to prevent hazard zones being reached by the upper and lower limbs*

ISO 14121-1:2007, *Safety of machinery — Risk assessment — Part 1: Principles*

IEC 61496-1:2004, *Safety of machinery — Electro-sensitive protective equipment — Part 1: General requirements and tests*

3 Terms, definitions, symbols and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12100-1 and the following apply.

3.1.1

actuation

(safeguards) physical initiation of the safeguard when it detects a body or parts of a body

3.1.2

overall system stopping performance

T

time interval between the actuation of the sensing function and the termination of the hazardous machine function

NOTE Adapted from IEC 61496-1:2004.

3.1.3

detection capability

d

sensing function parameter limit specified by the supplier that will cause actuation of the protective equipment

[IEC/TS 62046:2008, 3.1.4]

3.1.4

electro-sensitive protective equipment

ESPE

assembly of devices and/or components working together for protective tripping or presence-sensing purposes and comprising at a minimum:

— a sensing device,