
**Natural gas — Calculation of
compression factor —**

**Part 1:
Introduction and guidelines**

Gaz naturel — Calcul du facteur de compression —

Partie 1: Introduction et lignes directrices



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
1 Scope	1
2 Normative references	2
3 Terms and definitions.....	2
4 General principles.....	4
5 Guidelines.....	5
5.1 Pipeline quality natural gases	5
5.2 Other gases and other applications.....	8
Annex A (normative) Symbols and units	11
Annex B (informative) Computer program.....	12
Bibliography	13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12213-1 was prepared by Technical Committee ISO/TC 193, *Natural gas*, Subcommittee SC 1, *Analysis of natural gas*.

This second edition cancels and replaces the first edition (ISO 12213-1:1997), of which it constitutes a minor revision (the year of publication of Reference [5] in the Bibliography has been corrected).

ISO 12213 consists of the following parts, under the general title *Natural gas — Calculation of compression factor*:

- *Part 1: Introduction and guidelines*
- *Part 2: Calculation using molar-composition analysis*
- *Part 3: Calculation using physical properties*

Natural gas — Calculation of compression factor —

Part 1: Introduction and guidelines

1 Scope

ISO 12213 specifies methods for the calculation of compression factors of natural gases, natural gases containing a synthetic admixture and similar mixtures at conditions under which the mixture can exist only as a gas.

It is divided into three parts: this part of ISO 12213 gives an introduction and provides guidelines for the methods of calculation described in ISO 12213-2 and ISO 12213-3.

Part 2 gives a method for use where the detailed molar composition of the gas is known. Part 3 gives a method for use where a less detailed analysis, comprising superior calorific value (volumetric basis), relative density, carbon dioxide content and (if non-zero) hydrogen content, is available.

Both methods are applicable to dry gases of pipeline quality within the range of conditions under which transmission and distribution, including metering for custody transfer or other accounting purposes, are normally carried out. In general, such operations take place at temperatures between about 263 K and 338 K (approximately -10°C to 65°C) and pressures not exceeding 12 MPa (120 bar). Within this range, the uncertainty of prediction of both methods is about $\pm 0,1\%$ provided that the input data, including the relevant pressure and temperature, have no uncertainty.

NOTE Pipeline quality gas is used in this International Standard as a concise term for gas which has been processed so as to be suitable for use as industrial, commercial or domestic fuel. Although there is no formal international agreement upon the composition and properties of a gas which complies with this concept, some quantitative guidance is provided in 5.1.1. A detailed gas quality specification is usually a matter for contractual arrangements between buyer and seller.

The method given in Part 2 is also applicable (with increased uncertainty) to broader categories of natural gas, including wet or sour gases, within a wider range of temperatures and to higher pressures, for example for reservoir or underground storage conditions or for vehicular (NGV) applications.

The method given in Part 3 is applicable to gases with a higher content of nitrogen, carbon dioxide or ethane than normally found in pipeline quality gas. The method may also be applied over wider ranges of temperature and pressure but with increased uncertainty.

For the calculation methods described to be valid, the gas must be above its water and hydrocarbon dewpoints at the prescribed conditions.

This International Standard gives all of the equations and numerical values needed to implement both methods. It is planned to make verified computer programs available (see Annex B).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6976, *Natural gas — Calculation of calorific values, density, relative density and Wobbe index from composition*

ISO 13443, *Natural gas — Standard reference conditions*

3 Terms and definitions

For the purposes of the various parts of this International Standard, the following terms and definitions apply.

3.1 compression factor

Z

ratio of the volume of an arbitrary mass of gas, at a specified pressure and temperature, to the volume of the same mass of gas under the same conditions as calculated from the ideal-gas law, as follows:

$$Z = V_{\text{m}}(\text{real})/V_{\text{m}}(\text{ideal}) \quad (1)$$

where

$$V_{\text{m}}(\text{ideal}) = RT/p \quad (2)$$

NOTE 1 Thus

$$Z(p, T, y) = pV_{\text{m}}(p, T, y)/(RT) \quad (3)$$

where

p is the absolute pressure;

T is the thermodynamic temperature;

y is a set of parameters which uniquely characterizes the gas (in principle, the latter may be the complete molar composition or a distinctive set of dependent physico-chemical properties, or a mixture of both);

V_{m} is the molar volume of the gas;

R is the molar gas constant, in coherent units.

NOTE 2 The compression factor is a dimensionless quantity usually close to unity.

NOTE 3 The terms “compressibility factor” and “Z-factor” are synonymous with compression factor.

3.2 density

ρ

mass of a given quantity of gas divided by its volume at specified conditions of pressure and temperature

3.3 molar composition

term used when the proportion of each component in a homogeneous mixture is expressed as a mole (or molar) fraction, or mole (molar) percentage, of the whole