INTERNATIONAL STANDARD

ISO/IEC 14543-3-2

First edition 2006-09

Information technology – Home electronic system (HES) architecture –

Part 3-2:

Communication layers – Transport, network and general parts of data link layer for network based control of HES Class 1



Inis document is a preview denetated by EUS

INTERNATIONAL **STANDARD**

ISO/IEC 14543-3-2

First edition 2006-09

Information technology – Home electronic system (HES) architecture –

Part 3-2:

Communication layers -

Transport network and general parts of data link Transport Network and general parts of data line layer for network based control of HES Class 1

Copyright © 2006 ISO/IEC, Geneva — All rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



PRICE CODE



CONTENTS

FΟ	REW	ORD		5			
IN٦	TRODUCTION6						
1	Scor	Scope					
2	Norn	native r	eferences	7			
3	Terms, definitions and abbreviations						
	3.1		and definitions				
	3.2		viations				
4	_	4					
5	Requirements for the physical layer and independent data link layer						
	5.1						
	5.2						
	5.3	ink layer services					
	0.0	5.3.1	Data link layer modes				
		5.3.2	L_Data service				
		5.3.3	L SystemBroadcast service				
		5.3.4	L_Poll_Data service and protocol				
		5.3.5	L_Busmon service				
		5.3.6	L_Service_Informationservice				
	5.4	Data I	ink layer protocol	18			
		5.4.1	Protocol	18			
		5.4.2	Protocol Recommendations for duplication prevention	18			
	5.5	Param	neters of layer-2	18			
	5.6	Specif	fic devices	19			
		5.6.1	Layer-2 of a bridge	19			
		5.6.2	Layer-2 of a router	19			
6	Requ	uiremen	its for the network layer	19			
	6.1	Functi	ions of the network layer	19			
	6.2	Netwo	ork layer services and protocol	21			
		6.2.1	Network layer protocol data unit (NPDU)	21			
		6.2.2	Network layer services	21			
	6.3	Param	neters of the network layer	27			
	6.4	Netwo	JIK layer State Illactililes	∠ /			
		6.4.1	Overview	27			
		6.4.2	State machine of network layer for normal devices	27			
		6.4.3	State machine of network layer for bridges	27			
		6.4.4	State machine of network layer for routers	28			
7	Requirements for the transport layer						
	7.1	7.1 Functionality of the transport layer					
	7.2	7.2 Transport layer Protocol Data Unit (TPDU)					
	7.3	Overv	iew communication modes	31			
		7.3.1	Point-to-multipoint, connection-less (multicast) communication mode	31			
		7.3.2	Point-to-domain, connection-less (broadcast) communication mode	32			
		7.3.3	Point-to-all-points, connection-less (SystemBroadcast) communication				
		_	mode				
		7.3.4	Point-to-point, connection-less communication mode	32			

	7.3.5	Point-to-point, connection-oriented communication mode	32			
	7.3.6	Algorithm for the identifier of communication	33			
7	7.4 Trans	sport layer services	33			
	7.4.1	General	33			
	7.4.2	P T_Data_Group service	33			
	7.4.3	B T_Data_Tag_Group service	34			
	7.4.4	T_Data_Broadcast service	36			
	7.4.5	T_Data_SystemBroadcast service	37			
	7.4.6	T_Data_Individual service	38			
	7.4.7	Connect service	39			
		B TcDisconnect service				
	7.4.9	T_Data_Connected service	41			
7	7.5 Para	meters of transport layer	42			
7	7.6 State	e machine of connection-oriented communication mode	43			
	7.6.1	General C.	43			
	7.6.2	States States	43			
	7.6.3	Required actors	44			
	7.6.4	Transition table of the connection oriented transport layer state machine	46			
	7.6.5					
_	. 4 - 4	mative) Examples of trasport layer connection oriented state machine ams	54			
Δ10	Connect ar	amsnd disconnect				
/	1 1 Conn	nect from a remote device	5 <i>1</i>			
,	A.1.2 Connect from a remote device					
,	A.1.2 Connect from a remote device during an existing connection					
,	A.1.3 Disconnect from a remote device					
	A.1.5 Connect from the local user to a non existing device					
	A.1.6 Connect from the local user during an existing connection					
	4 4 0 D!	onnect from the local useronnect from the local user without an existing connection	50 56			
,	1.1.0 DISCO	position timeout	50			
7 ۸ ۷ ۵	Pecention	onnect from the local user without an existing connection				
ر ۲.۷	No 4 Daga	or uata				
F	4.2.1 Rece	eption of a correct N_Data_Individual	57			
F	A.2.2 Reception of a repeated N_Data_Individual A.2.3 Reception of data N_Data_Individual with wrong sequence number					
		eption of data N_Data_Individual with wrong source address	58			
		ion of data	58			
	A.S. 1 _DATA-Request from the local user					
	A.3.2 Reception of a T_ACK_PDU with wrong sequence number					
	A.3.3 Reception of T_ACK_PDU with wrong connection address					
	A.3.4 Reception of T_NACK_PDU with wrong sequence number					
		eption of T_NACK_PDU with correct sequence number				
		eption of T_NACK_PDU and maximum number of repetitions is reached				
		eption of T_NACK_PDU with wrong connection address				
DIDIIO	ograpny		62			

Figure 1 – Individual address	8
Figure 2 – Group address	8
Figure 3 – Interaction of the data link layer	10
Figure 4 – Exchange of primitives for the L_Data-Service	11
Figure 5 – Frame_format Parameter	14
Figure 6 – Coding of Extended Frame Format	14
Figure 7 – Interaction of the network layer (not for Bridges or Routers)	20
Figure 8 – General functionality of a router or a bridge	20
Figure 9 – Format of the NPDU (Example)	21
Figure 10 – Interaction the transport layer	30
Figure 11 – Format of the PDU (Example)	
Figure 12 – Transport control ield	31
Table 1. Heave of rejective	
Table 1 – Usage of priority	13
Table 2 – Actions of the connection oriented state machine	44
Table 3 – Transition table – Style 1	46
Table 4 – Transition table – Style 1-rationalized	48
Table 5 – Transition table – Style 2	50
Table 4 – Transition table – Style 1-rationalized	52

2 Senerated by the

INFORMATION TECHNOLOGY – HOME ELECTRONIC SYSTEM (HES) ARCHITECTURE –

Part 3-2: Communication layers – Transport, network and general parts of data link layer for network based control of HES Class 1

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any SQ and IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC or ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO National Committees.
- 4) IEC, ISO or ISO/IEC Publications have the form of recommendations for international use and are accepted by IEC and ISO National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO or ISO/IEC Tubications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO National Committees undertake to apply IEC, ISO or ISO/IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC Publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO or IEC provide no marking procedure to indicate the approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC Publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reference upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications
- 9) Attention is drawn to the normative references cited in this publication. Use the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this International standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 14543-3-2 was prepared by subcommittee 25. Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

This International Standard together with ISO/IEC 14543-3-1 cancels and replaces ISO/IEC TR 14543-3, published in 2000. It constitutes a complete revision of the principles outlined in ISO/IEC TR 14543-3 and provides the specifications essential for an international standard.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

INTRODUCTION

This standard specifies the Media independent requirements for the data link layer and the requirements for the network layer and the transport layer for Home Electronic Systems.

This standard provides the communication stack targeted for providing the services specified in ISO/IEC 14543-3-3 (EN 50090-3-2) "User Process" and ISO/IEC 14543-3-1 "Application Layer for networked based control of HES Class 1". It can be used as communication stack on the physical layers as specified in ISO/IEC 14543-3-5, ISO/IEC 14543-3-6 and ISO/IEC 14543-3-7 (EN 50090-5-x).

Currently, ISO/IEC 14543, Information technology — Home Electronic System (HES) architecture, consists of the following parts:

Part 2-1:	Introduction and device modularity
Part 3-1:	Communication layers – Application layer for network based control of HES Class 1
Part 3-2:	Communication ayers – Transport, network and general parts of data link layer for
	network based control of HES Class 1
Part 3-3:	User process for hetwork based control of HES Class 1 (under consideration)
Part 3-4:	System management - Management procedures for network based control of HES Class 1 (under consideration)
Part 3-5:	Media and media dependent layers – Power line for network based control of HES Class 1 (under consideration)
Part 3-6:	Media and media depender bayers – Twisted pair for network based control of HES Class 1 (under consideration)
Part 3-7:	Media and media dependent layers – Radio frequency for network based control of HES Class 1 (under consideration)
Part 4:	Home and building automation in a mixed-use building (technical report)
Part 5-1:	Intelligent grouping and resource sharing for HES Class 2 and Class 3 – Core ptotocol
Part 5-2:	Intelligent grouping and resource sharing for HES Class 2 and Class 3 – Device certification
	Additional parts may be added later.
	Certification Additional parts may be added later.

INFORMATION TECHNOLOGY – HOME ELECTRONIC SYSTEM (HES) ARCHITECTURE –

Part 3-2: Communication layers – Transport, network and general parts of data link layer for network based control of HES Class 1

1 Scope

This part of ISO/IEC 14543 specifies the services and protocol in a physical layer independent way for the data link layer and for the network layer and the transport layer for usage in Home Electronic Systems

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 7498 (all parts), Information technology – Open Systems Interconnection – Basic reference model

ISO/IEC 14543-2-1, Information technology – Home Electronic System (HES) Architecture – Part 2-1: Introduction and device modularity

ISO/IEC 14543-3-1 Information technology — Home Electronic System (HES) Architecture — Part 3-1: Communication layers — Application layer for network based control of HES Class 1

NOTE 1 The provisions of the referenced specifications, as intiffied in this subclause, are valid within the context of this International Standard. The reference to a specification within this International Standard does not give it any further status within ISO/IEC; in particular, it does not give the referenced specification the status of an International Standard.

EN 50090-5 (all parts), Home and Building Electronic Systems (HBES) – Part 5: Media and media dependent layers

NOTE 2 Reference to EN 50090-5-x is to be considered as deleted as soon as ISO/IEC 14543-3-5, ISO/IEC 14543-3-6 and ISO/IEC 14543-3-7 are approved.

3 Terms, definitions and abbreviations

3.1 Terms and definitions

For the purposes of this part the terms and definitions given in ISO/IEC44543-2-1 and the following apply.

3.1.1

individual address

IΑ

unique identifier for every device in a network

NOTE The individual address is a 2-octet value that consists of an 8-bit subnetwork address and an 8-bit device address.