# INTERNATIONAL STANDARD

ISO 21438-2

First edition 2009-12-15

Workplace atmospheres — Determination of inorganic acids by ion chromatography —

#### Part 2:

Volatile acids, except hydrofluoric acid (hydrochloric acid, hydrobromic acid and nitric acid)

Air des lieux de travail — Détermination des acides inorganiques par chromatographie ionique —

Partie 2: Acides volatils, sauf acide fluorhydrique (acide chlorhydrique, acide bromhydrique et acide nitrique)



#### PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



#### COPYRIGHT PROTECTED DOCUMENT

#### © ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

#### **Contents**

Page

Foreword				
Introductionv				
1	Scope.	1		
2	Normative references	1		
3	Terms and definitions			
3.1	General definitions			
3.2	Particle size fraction definitions			
3.3	Sampling definitions			
3.4				
3.5	Statistical terms	5		
4	Principle	e		
_		-		
5	Requirement	1		
6	Analytical definitions Statistical terms Principle Requirement Reagents Apparatus Sampling equipment Laboratory apparatus	7		
7	Apparatus	ç		
7.1	Sampling equipment	9		
7.2	Laboratory apparatus	11		
•	Occupational exposure assessment  General  Personal sampling  Static sampling  Selection of measurement conditions and measurement pattern	4.		
8	Occupational exposure assessment.	13		
8.1 8.2	Developed compling	13		
8.3	Personal sampling	13		
6.3 8.4	Selection of measurement conditions and measurement nattern	13		
0.4	Selection of measurement conditions and measurement pattern	10		
9	Sampling	14		
9.1	Preliminary considerations	14		
9.2	Preparation for sampling	16		
9.3	Sampling position	17		
9.4	Collection of samples	17		
9.5	Sampling Preliminary considerations Preparation for sampling Sampling position Collection of samples Transportation Analysis Preparation of test and calibration solutions Instrumental analysis Estimation of detection and quantification limits Ouality control	17		
10	Analysis	18		
10.1	Preparation of test and calibration solutions	18		
10.2	Instrumental analysis	19		
10.3	Estimation of detection and quantification limits	20		
10.4	Quality control	20		
10.5	Quality control	21		
11	Expression of results	22		
40	Method neuformence	20		
12 12.1	Method performance			
12.1	Quantification limitsQuantification limits			
12.2	Upper limits of the working range			
12.3	Bias and precision			
12.5	Uncertainty of sampling and analysis method			
12.6	Interferences			
_				
13	Test report			
13.1 13.2	Test record  Laboratory report			
Annex	Annex A (informative) Temperature and pressure correction2			

Annex B (normative)	Filter materials	27
Bibliography		28

this document is a preview denetated by EUS

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 21438-2 was prepared by Technical Committee ISO/TC 146, Air quality, Subcommittee SC 2, Workplace atmospheres.

ISO 21438 consists of the following parts, under the general title Workplace atmospheres — Determination of inorganic acids by ion chromatography:

- Part 1: Non volatile acids (sulfuric acid and phosphoric acid)
- Part 2: Volatile acids, except hydrofluoric acid (hy drachloric acid, hydrobromic acid and nitric acid) Jeneraled by EUS
- Part 3: Hydrofluoric acid and particulate fluorides

© ISO 2009 - All rights reserved

#### Introduction

The health of workers in many industries is at risk through exposure by inhalation of volatile inorganic acids. Industrial hygienists and other public health professionals need to determine the effectiveness of measures taken to control workers' exposure, and this is generally achieved by making workplace air measurements. This part of ISO 21438 has been published in order to make available a method for making valid exposure measurements for volatile horganic acids in use in industry, such as hydrochloric acid, hydrobromic acid and nitric acid, but excluding bydrofluoric acid. It is intended to be of benefit to: agencies concerned with health and safety at work; industrial hygienists and other public health professionals; analytical laboratories; industrial users of hydrochloric acid, hydrobromic acid and nitric acid and their workers, etc.

It has been assumed in the drawing of this part of ISO 21438 that the execution of its provisions and the interpretation of the results obtained are entrusted to appropriately qualified and experienced people.

۷i

## Workplace atmospheres — Determination of inorganic acids by ion chromatography —

#### Part 2:

Volatile acids, except hydrofluoric acid (hydrochloric acid, hydrobromic acid and nitric acid)

#### 1 Scope

This part of ISO 21438 specifies a method for the determination of the time-weighted average mass concentration of hydrogen chloride (HCI) gas and hydrochloric acid mist, hydrogen bromide (HBr) vapour and hydrobromic acid mist and nitric acid (HNO $_3$ ) vapour and mist in workplace air by collection on an alkalimpregnated quartz fibre filter and analysis by ion chromatography.

For mist sampling, the method is applicable to the personal sampling of the inhalable fraction of airborne particles, as defined in ISO 7708, and to static (area) sampling.

The analytical method is applicable to the determination of masses of 0,01 mg to 2,5 mg of HCl, HBr and  $HNO_3$  per sample.

The range of concentrations of HCl, HBr and HNO<sub>3</sub> pair for which the measuring procedure is applicable is determined by the sampling method selected by the user. For a 240 l air sample, the working range is approximately 0,04  $\text{mg}\cdot\text{m}^{-3}$  to 10  $\text{mg}\cdot\text{m}^{-3}$  for HCl, HBr and HNO<sub>3</sub>.

The procedure is intended to differentiate between the acids and their corresponding salts. If both are present in the air, particulate salts are trapped on a pre-filter. Co-sampled particulate matter trapped on the pre-filter and/or deposited on the walls of the sampler may be analysed, it is sired.

Acids can react with co-sampled particulate matter on the pre-filter, causing interference with the measurement of the acid concentration.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 648, Laboratory glassware — Single-volume pipettes

ISO 1042, Laboratory glassware — One-mark volumetric flasks

ISO 3585, Borosilicate glass 3.3 — Properties

ISO 7708:1995, Air quality — Particle size fraction definitions for health-related sampling

ISO 8655-1, Piston-operated volumetric apparatus — Part 1: Terminology, general requirements and user recommendations

© ISO 2009 – All rights reserved

ISO 8655-2, Piston-operated volumetric apparatus — Part 2: Piston pipettes

ISO 8655-6, Piston-operated volumetric apparatus — Part 6: Gravimetric methods for the determination of measurement error

ISO 8756, Air quality — Handling of temperature, pressure and humidity data

EN 13205, Workplace atmospheres — Assessment of performance of instruments for measurement of airborne particle concentrations

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

#### 3.1 General definitions

#### 3.1.1

#### chemical agent

any chemical element or compound, on its own or admixed as it occurs in the natural state or as produced, used or released, including release as waste, by any work activity, whether produced intentionally or not and whether placed on the market or not

[EN 1540:1998<sup>[1]</sup>]

#### 3.1.2

#### breathing zone

(general definition) space around the worker's face from where he or she takes his or her breath

#### 3.1.3

#### breathing zone

(technical definition) hemisphere (generally accepted to be 0,4m in radius) extending in front of the human face, centred on the mid point of a line joining the ears, the base of the hemisphere being a plane through this line, the top of the head and the larynx

NOTE 1 The definition is not applicable when respiratory protective equipment used

NOTE 2 Adapted from EN 1540:1998<sup>[1]</sup>.

#### 3.1.4

#### exposure (by inhalation)

situation in which a chemical agent is present in air which is inhaled by a person

#### 3.1.5

#### measuring procedure

procedure for sampling and analysing one or more chemical agents in the air and including storage and transportation of the sample

#### 3.1.6

#### operating time

period during which a sampling pump can be operated at specified flow rate and back pressure without recharging or replacing the battery

[EN 1232:1997<sup>[2]</sup>]