

INTERNATIONAL  
STANDARD

ISO/IEC  
26907

First edition  
2007-03-01

---

---

**Information technology —  
Telecommunications and information  
exchange between systems — High Rate  
Ultra Wideband PHY and MAC Standard**

*Technologies de l'information — Téléinformatique — “High Rate Ultra  
Wideband PHY” et “MAC Standard”*

---

---

Reference number  
ISO/IEC 26907:2007(E)



© ISO/IEC 2007

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

Contents	Page
<b>Foreword</b>	<b>x</b>
<b>Introduction</b>	<b>xi</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Conformance</b>	<b>1</b>
<b>3 Normative references</b>	<b>1</b>
<b>4 Terms and definitions</b>	<b>2</b>
<b>5 Notational conventions</b>	<b>4</b>
<b>6 Abbreviations and acronyms</b>	<b>4</b>
<b>7 General description</b>	<b>7</b>
<b>7.1 PHY general description</b>	<b>7</b>
<b>7.2 MAC general description</b>	<b>8</b>
<b>7.2.1 General description of the architecture</b>	<b>8</b>
<b>7.2.2 Device address</b>	<b>8</b>
<b>7.2.3 Features assumed from the PHY</b>	<b>8</b>
<b>7.2.4 Overview of MAC service functionality</b>	<b>9</b>
<b>7.2.5 MUX sublayer</b>	<b>13</b>
<b>7.2.6 MAC policies</b>	<b>13</b>
<b>7.2.7 Test vectors</b>	<b>13</b>
<b>8 PHY layer partitioning</b>	<b>13</b>
<b>8.1 PHY function</b>	<b>14</b>
<b>8.2 PLCP sublayer</b>	<b>14</b>
<b>8.3 PMD sublayer</b>	<b>14</b>
<b>8.4 PHY layer management entity (PLME)</b>	<b>14</b>
<b>9 Description of signal</b>	<b>14</b>
<b>9.1 Mathematical framework</b>	<b>14</b>
<b>10 PLCP sublayer</b>	<b>15</b>
<b>10.1 PPDU</b>	<b>15</b>
<b>10.1.1 PSDU rate-dependent parameters</b>	<b>18</b>
<b>10.1.2 Timing-related parameters</b>	<b>18</b>
<b>10.1.3 Frame-related parameters</b>	<b>19</b>
<b>10.2 PLCP preamble</b>	<b>19</b>
<b>10.2.1 Standard PLCP preamble</b>	<b>20</b>
<b>10.2.2 Burst PLCP preamble</b>	<b>21</b>
<b>10.3 PLCP header</b>	<b>32</b>
<b>10.3.1 PHY header</b>	<b>33</b>
<b>10.3.2 Reed-Solomon outer code for the PLCP header</b>	<b>37</b>

<b>10.3.3 Header check sequence .....</b>	<b>39</b>
<b>10.4 PSDU .....</b>	<b>40</b>
<b>10.4.1 Pad bits .....</b>	<b>41</b>
<b>10.5 Data scrambler .....</b>	<b>42</b>
<b>10.6 Tail bits .....</b>	<b>43</b>
<b>10.7 Convolutional encoder .....</b>	<b>43</b>
<b>10.8 Bit interleaving .....</b>	<b>46</b>
<b>10.9 Constellation mapping .....</b>	<b>48</b>
<b>10.9.1 QPSK .....</b>	<b>48</b>
<b>10.9.2 Dual-carrier modulation (DCM) .....</b>	<b>49</b>
<b>10.10 OFDM modulation .....</b>	<b>51</b>
<b>10.10.1 Implementation considerations .....</b>	<b>55</b>
<b>10.10.2 Data subcarriers .....</b>	<b>55</b>
<b>10.10.3 Guard subcarriers .....</b>	<b>59</b>
<b>10.10.4 Pilot subcarriers .....</b>	<b>59</b>
<b>11 General requirements .....</b>	<b>61</b>
<b>11.1 Operating band frequencies .....</b>	<b>61</b>
<b>11.1.1 Operating frequency range .....</b>	<b>61</b>
<b>11.1.2 Band numbering .....</b>	<b>61</b>
<b>11.2 Channelization .....</b>	<b>62</b>
<b>11.3 PHY layer timing .....</b>	<b>64</b>
<b>11.3.1 Interframe spacing .....</b>	<b>65</b>
<b>11.3.2 Receive-to-transmit turnaround time .....</b>	<b>65</b>
<b>11.3.3 Transmit-to-receive turnaround time .....</b>	<b>65</b>
<b>11.3.4 Time between successive transmissions .....</b>	<b>65</b>
<b>11.3.5 Band frequency switch time .....</b>	<b>65</b>
<b>12 Transmitter specifications .....</b>	<b>66</b>
<b>12.1 Transmit PSD mask .....</b>	<b>66</b>
<b>12.2 Transmit centre frequency tolerance .....</b>	<b>66</b>
<b>12.3 Symbol clock frequency tolerance .....</b>	<b>66</b>
<b>12.4 Clock synchronization .....</b>	<b>66</b>
<b>12.5 Phase coherence .....</b>	<b>66</b>
<b>12.6 Transmit power control .....</b>	<b>66</b>
<b>12.7 Transmitter constellation error .....</b>	<b>67</b>
<b>13 Receiver specification .....</b>	<b>68</b>
<b>13.1 Receiver sensitivity .....</b>	<b>68</b>
<b>13.2 Receiver CCA performance .....</b>	<b>69</b>
<b>13.3 Link quality indicator .....</b>	<b>69</b>
<b>14 Ranging and location awareness .....</b>	<b>70</b>
<b>14.1 Ranging requirements .....</b>	<b>70</b>
<b>14.2 Ranging reference signal .....</b>	<b>70</b>
<b>14.3 PHY ranging resources .....</b>	<b>70</b>

<b>14.4 PHY ranging operation .....</b>	<b>70</b>
<b>14.5 Ranging calibration constants .....</b>	<b>70</b>
<b>14.6 Example range measurement (informative) .....</b>	<b>71</b>
<b>15 PHY and MAC service access points (informative) .....</b>	<b>72</b>
<b>15.1 Generic MIB management primitives .....</b>	<b>72</b>
<b>15.1.1 XX-GET.request .....</b>	<b>73</b>
<b>15.1.2 XX-GET.confirm .....</b>	<b>73</b>
<b>15.1.3 XX-SET.request .....</b>	<b>74</b>
<b>15.1.4 XX-SET.confirm .....</b>	<b>74</b>
<b>15.2 PHY SAP interface .....</b>	<b>74</b>
<b>15.2.1 Data transfer .....</b>	<b>75</b>
<b>15.2.2 PHY transmission control .....</b>	<b>76</b>
<b>15.2.3 PHY reception control .....</b>	<b>78</b>
<b>15.2.4 PHY CCA control .....</b>	<b>81</b>
<b>15.3 PLME SAP interface .....</b>	<b>82</b>
<b>15.3.1 PHY reset .....</b>	<b>84</b>
<b>15.3.2 PHY ranging timer control .....</b>	<b>84</b>
<b>15.4 MAC sublayer management primitives .....</b>	<b>85</b>
<b>15.5 MAC management information base (MIB) .....</b>	<b>85</b>
<b>15.6 MLME SAP interface .....</b>	<b>86</b>
<b>15.6.1 Reset .....</b>	<b>86</b>
<b>15.6.2 Scan .....</b>	<b>87</b>
<b>15.6.3 Beacon transmission and reception .....</b>	<b>89</b>
<b>15.6.4 IE management .....</b>	<b>93</b>
<b>15.6.5 PTK establishment .....</b>	<b>95</b>
<b>15.6.6 GTK solicitation/distribution .....</b>	<b>98</b>
<b>15.6.7 Temporal key update .....</b>	<b>100</b>
<b>15.6.8 Security violation report .....</b>	<b>102</b>
<b>15.6.9 Pseudo-random function (PRF) .....</b>	<b>103</b>
<b>15.6.10 Application-specific IE (ASIE) management .....</b>	<b>104</b>
<b>15.6.11 Multicast address binding .....</b>	<b>106</b>
<b>15.6.12 Link events .....</b>	<b>109</b>
<b>15.6.13 Probe .....</b>	<b>112</b>
<b>15.6.14 Hibernation and sleep cycle .....</b>	<b>115</b>
<b>15.6.15 Higher layer synchronization support .....</b>	<b>119</b>
<b>15.6.16 DRP reservation management .....</b>	<b>121</b>
<b>15.6.17 Connection configuration primitives .....</b>	<b>127</b>
<b>15.6.18 Range measurement .....</b>	<b>129</b>
<b>15.6.19 Application-specific command management .....</b>	<b>130</b>
<b>15.7 MAC SAP interface .....</b>	<b>132</b>
<b>15.7.1 MAC-DATA.request .....</b>	<b>133</b>
<b>15.7.2 MAC-DATA.indication .....</b>	<b>134</b>
<b>15.7.3 MAC-DATA.confirm .....</b>	<b>134</b>
<b>16 MAC frame formats .....</b>	<b>135</b>

<b>16.1 Frame format conventions .....</b>	<b>135</b>
<b>16.1.1 Figures .....</b>	<b>135</b>
<b>16.1.2 Octet order .....</b>	<b>135</b>
<b>16.1.3 Encoding .....</b>	<b>135</b>
<b>16.2 General MAC frame format .....</b>	<b>135</b>
<b>16.2.1 Frame control .....</b>	<b>136</b>
<b>16.2.2 DestAddr .....</b>	<b>138</b>
<b>16.2.3 SrcAddr .....</b>	<b>138</b>
<b>16.2.4 Sequence control .....</b>	<b>138</b>
<b>16.2.5 Access information .....</b>	<b>138</b>
<b>16.2.6 Frame payload .....</b>	<b>139</b>
<b>16.2.7 FCS .....</b>	<b>139</b>
<b>16.3 Beacon frames .....</b>	<b>140</b>
<b>16.4 Control frames .....</b>	<b>142</b>
<b>16.4.1 Immediate acknowledgement (Imm-ACK) .....</b>	<b>143</b>
<b>16.4.2 Block acknowledgement (B-ACK) .....</b>	<b>143</b>
<b>16.4.3 Request to send (RTS) .....</b>	<b>144</b>
<b>16.4.4 Clear to send (CTS) .....</b>	<b>144</b>
<b>16.4.5 Unused DRP reservation announcement (UDA) .....</b>	<b>144</b>
<b>16.4.6 Unused DRP reservation response (UDR) .....</b>	<b>144</b>
<b>16.4.7 Application-specific .....</b>	<b>144</b>
<b>16.5 Command frames .....</b>	<b>144</b>
<b>16.5.1 DRP reservation request .....</b>	<b>145</b>
<b>16.5.2 DRP reservation response .....</b>	<b>146</b>
<b>16.5.3 Probe .....</b>	<b>146</b>
<b>16.5.4 Pairwise temporal key (PTK) .....</b>	<b>146</b>
<b>16.5.5 Group temporal key (GTK) .....</b>	<b>147</b>
<b>16.5.6 Range measurement .....</b>	<b>148</b>
<b>16.5.7 Application-specific .....</b>	<b>150</b>
<b>16.6 Data frames .....</b>	<b>150</b>
<b>16.7 Aggregated data frames .....</b>	<b>150</b>
<b>16.8 Information elements .....</b>	<b>150</b>
<b>16.8.1 Application-specific IE (ASIE) .....</b>	<b>152</b>
<b>16.8.2 Application-specific probe IE .....</b>	<b>152</b>
<b>16.8.3 Beacon period occupancy IE (BPOIE) .....</b>	<b>153</b>
<b>16.8.4 BP switch IE .....</b>	<b>154</b>
<b>16.8.5 Channel change IE .....</b>	<b>154</b>
<b>16.8.6 Distributed reservation protocol (DRP) IE .....</b>	<b>154</b>
<b>16.8.7 DRP availability IE .....</b>	<b>156</b>
<b>16.8.8 Hibernation anchor IE .....</b>	<b>156</b>
<b>16.8.9 Hibernation mode IE .....</b>	<b>157</b>
<b>16.8.10 Identification IE .....</b>	<b>157</b>
<b>16.8.11 Link feedback IE .....</b>	<b>159</b>
<b>16.8.12 MAC capabilities IE .....</b>	<b>160</b>
<b>16.8.13 Master key identifier (MKID) IE .....</b>	<b>161</b>

16.8.14 Multicast address binding (MAB) IE .....	161
16.8.15 PCA availability IE .....	161
16.8.16 PHY capabilities IE .....	162
16.8.17 Probe IE .....	163
16.8.18 Relinquish request IE .....	164
16.8.19 Traffic indication map (TIM) IE .....	165
<b>17 MAC sublayer functional description .....</b>	<b>165</b>
<b>17.1 Frame processing .....</b>	<b>165</b>
17.1.1 Frame addresses .....	166
17.1.2 Frame reception .....	166
17.1.3 Frame transaction .....	166
17.1.4 Frame transfer .....	167
17.1.5 Frame retry .....	167
17.1.6 Inter-frame space (IFS) .....	168
17.1.7 Duplicate detection .....	168
17.1.8 RTS/CTS use .....	169
17.1.9 MAC header fields .....	169
17.1.10 Information elements .....	172
<b>17.2 Beacon period .....</b>	<b>174</b>
17.2.1 Beacon slot state .....	174
17.2.2 BP length .....	175
17.2.3 Beacon transmission and reception .....	175
17.2.4 Beacon collision detection .....	176
17.2.5 BP contraction .....	176
17.2.6 Merger of multiple BPs .....	176
<b>17.3 Prioritized contention access (PCA) .....</b>	<b>179</b>
17.3.1 PCA medium availability .....	180
17.3.2 NAV .....	180
17.3.3 Medium status .....	180
17.3.4 PCA parameters .....	181
17.3.5 Obtaining a TXOP .....	181
17.3.6 Using a TXOP .....	182
17.3.7 Invoking a backoff procedure .....	183
17.3.8 Decrementing a backoff counter .....	184
<b>17.4 Distributed reservation protocol (DRP) .....</b>	<b>185</b>
17.4.1 Reservation type .....	185
17.4.2 DRP availability IE .....	186
17.4.3 DRP reservation negotiation .....	186
17.4.4 DRP reservation announcements .....	188
17.4.5 Resolution of DRP reservation conflicts .....	188
17.4.6 BPST realignment and existing DRP reservations .....	190
17.4.7 Modification and termination of existing DRP reservations .....	190
17.4.8 Release of hard or private DRP reservation blocks .....	190
17.4.9 Retransmit procedures in DRP reservations .....	191

<b>17.5 Synchronization of devices .....</b>	<b>191</b>
<b>17.5.1 Clock accuracy .....</b>	<b>192</b>
<b>17.5.2 Synchronization for devices in hibernation mode .....</b>	<b>192</b>
<b>17.5.3 Guard times .....</b>	<b>192</b>
<b>17.6 Fragmentation and reassembly .....</b>	<b>193</b>
<b>17.7 Aggregation .....</b>	<b>194</b>
<b>17.8 Acknowledgement policies .....</b>	<b>194</b>
<b>17.8.1 No-ACK .....</b>	<b>194</b>
<b>17.8.2 Immediate ACK .....</b>	<b>194</b>
<b>17.8.3 Block ACK .....</b>	<b>194</b>
<b>17.9 Probe .....</b>	<b>196</b>
<b>17.10 Dynamic channel selection .....</b>	<b>196</b>
<b>17.11 Multi-rate support .....</b>	<b>197</b>
<b>17.12 Transmit power control .....</b>	<b>197</b>
<b>17.13 Power management mechanisms .....</b>	<b>197</b>
<b>17.13.1 Power management modes .....</b>	<b>197</b>
<b>17.13.2 Device power states .....</b>	<b>197</b>
<b>17.13.3 Power state transitions .....</b>	<b>198</b>
<b>17.13.4 Hibernation mode operation .....</b>	<b>199</b>
<b>17.13.5 Hibernation anchor operation .....</b>	<b>200</b>
<b>17.14 ASIE operation .....</b>	<b>201</b>
<b>17.15 Range measurement operation .....</b>	<b>201</b>
<b>17.16 MAC sublayer parameters .....</b>	<b>204</b>
<b>18 Security .....</b>	<b>205</b>
<b>18.1 Security mechanisms .....</b>	<b>206</b>
<b>18.1.1 Security operation .....</b>	<b>206</b>
<b>18.1.2 4-way handshake .....</b>	<b>206</b>
<b>18.1.3 Key transport .....</b>	<b>206</b>
<b>18.1.4 Freshness protection .....</b>	<b>206</b>
<b>18.1.5 Data encryption .....</b>	<b>206</b>
<b>18.1.6 Frame integrity protection .....</b>	<b>207</b>
<b>18.2 Security modes .....</b>	<b>207</b>
<b>18.2.1 Security mode 0 .....</b>	<b>208</b>
<b>18.2.2 Security mode 1 .....</b>	<b>209</b>
<b>18.2.3 Security mode 2 .....</b>	<b>209</b>
<b>18.3 Temporal keys .....</b>	<b>209</b>
<b>18.3.1 Mutual authentication and PTK derivation .....</b>	<b>210</b>
<b>18.3.2 GTK exchange .....</b>	<b>211</b>
<b>18.3.3 Pseudo-random function (PRF) definition .....</b>	<b>211</b>
<b>18.3.4 PTK and KCK derivation .....</b>	<b>212</b>
<b>18.3.5 PTK MIC generation .....</b>	<b>213</b>
<b>18.3.6 Random number generation .....</b>	<b>213</b>
<b>18.4 Frame reception steps and replay prevention measures .....</b>	<b>214</b>
<b>18.4.1 Frame reception .....</b>	<b>214</b>

18.4.2 Replay prevention .....	214
18.4.3 Implications on GTKs .....	214
18.5 AES-128 CCM Inputs .....	215
18.5.1 Overview .....	215
18.5.2Nonce .....	215
18.5.3CCM blocks .....	215
Annex A (normative) <b>MUX sublayer</b> .....	219
Annex B (normative) <b>MAC Policies</b> .....	221
Annex C (normative) <b>Assigned number document</b> .....	226
Annex D (informative) <b>MAC test vectors</b> .....	230
Annex E (informative) <b>Example encoding of a PHY packet</b> .....	241
Annex F (informative) <b>Recommended out-of-band emission limits</b> .....	286
Annex G (informative) <b>Range measurement calculations</b> .....	287
Bibliography .....	291

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 26907 was prepared by Ecma International (as ECMA-368) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology, SC 6, Telecommunications and information exchange between systems*, in parallel with its approval by national bodies of ISO and IEC.

## Introduction

This International Standard specifies the Ultra Wideband (UWB) physical layer (PHY) and medium access control (MAC) sublayer for a high-speed, short-range wireless network, utilizing all or part of the spectrum between 3 100 MHz and 10 600 MHz supporting data rates of up to 480 Mb/s.

This International Standard divides the spectrum into 14 bands, each with a bandwidth of 528 MHz. The first 12 bands are then grouped into 4 band groups consisting of 3 bands, and the last two bands are grouped into a fifth band group. A MultiBand Orthogonal Frequency Division Modulation (MB-OFDM) scheme is used to transmit information. A total of 110 subcarriers (100 data carriers and 10 guard carriers) are used per band. In addition, 12 pilot subcarriers allow for coherent detection. Frequency-domain spreading, time-domain spreading, and forward error correction (FEC) coding are provided for optimum performance under a variety of channel conditions.

The MAC sublayer is designed to enable mobility, such that a group of devices may continue communicating while merging or splitting from other groups of devices. To maximize flexibility, the functionality of this MAC is distributed among devices. These functions include distributed coordination to avoid interference between different groups of devices by appropriate use of channels and distributed medium reservations to ensure Quality of Service. The MAC sublayer provides prioritized schemes for isochronous and asynchronous data transfer. To do this, a combination of Carrier Sense Multiple Access (CSMA) and Time Division Multiple Access (TDMA) are used. A Distributed Reservation Protocol (DRP) is used to reserve the medium for TDMA access for isochronous and other traffic. For network scalability, Prioritized Contention Access (PCA) is provided using a CSMA scheme. The MAC has policies that ensure equitable sharing of the bandwidth.

Taken together, the PHY and MAC specified in this International Standard are well-suited to high rate, zero infrastructure communications between a mixed population of portable and fixed electronic devices.

This International Standard is not intended to represent the regulatory requirements of any country or region.



# Information technology — Telecommunications and information exchange between systems — High Rate Ultra Wideband PHY and MAC Standard

## 1 Scope

This International Standard specifies a distributed medium access control (MAC) sublayer and a physical layer (PHY) for wireless networks.

## 2 Conformance

Conforming devices implement the MAC sublayer and the PHY layer as specified herein and support:

1. Data rates of 53,3 Mb/s, 106,7 Mb/s and 200 Mb/s for transmitting and receiving;
2. The first band group (lowest three frequency bands);
3. Time-frequency codes using both TFI and FFI.

In addition, conforming devices may implement the MAC/PHY Interface as specified in ISO/IEC 26908.

## 3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC TR 8802-1:2001, *Information technology — Telecommunications and information exchange between systems — Local and metropolitan area networks — Specific requirements — Part 1: Overview of Local Area Network Standards*

ISO/IEC 10646:2003, *Information technology — Universal Multiple-Octet Coded Character Set (UCS)*

ISO/IEC 18033-3:2005, *Information technology — Security techniques — Encryption algorithms — Part 3: Block ciphers*

ISO/IEC 26908:2007, *Information technology — Telecommunications and information exchange between systems — MAC-PHY Interface for ISO/IEC 26907*

IEEE 100, *The Authoritative Dictionary of IEEE Standard Terms, Seventh Edition*

NIST Special Publication 800-38C, *Recommendation for Block Cipher Modes of Operation: The CCM Mode for Authentication and Confidentiality*

NOTE 1 IEEE publications are available from the Institute of Electrical and Electronics Engineers, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ 08855-1331, USA (<http://standards.ieee.org/>).

NOTE 2 The IEEE standards referenced are trademarks belonging to the Institute of Electrical and Electronics Engineers, Inc.

NOTE 3 NIST FIPS publications are available from the National Institute for Standards and Technology, 100 Bureau Drive, Stop 8900, Gaithersburg, MD 20899-8900, USA (<http://www.nist.gov>).