

Railway applications - Track - Rail - Part 4: Vignole
railway rails from 27 kg/m to, but excluding 46 kg/m

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 13674-4:2019 sisaldab Euroopa standardi EN 13674-4:2019 ingliskeelset teksti.	This Estonian standard EVS-EN 13674-4:2019 consists of the English text of the European standard EN 13674-4:2019.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 03.04.2019.	Date of Availability of the European standard is 03.04.2019.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 93.100

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Koduleht www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

English Version

Railway applications - Track - Rail - Part 4: Vignole railway rails from 27 kg/m to, but excluding 46 kg/m

Applications ferroviaires - Voie - Rails - Partie 4 : Rails
Vignole de masse comprise entre 27 kg/m et 46 kg/m,
46 kg/m non compris

Bahnanwendungen - Oberbau - Schienen - Teil 4:
Vignolschienen mit einer längenbezogenen Masse
zwischen 27 kg/m und unter 46 kg/m

This European Standard was approved by CEN on 14 December 2018.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

Page

European foreword.....	4
Introduction	6
1 Scope	8
2 Normative references	8
3 Terms and definitions	8
4 Information to be supplied by the purchaser	9
5 Steel grades	10
6 Dimensions, static properties, linear mass and tolerances.....	11
7 Manufacture	11
7.1 Product integrity	11
7.1.1 Factory production control	11
7.1.2 Best practice manufacture.....	11
7.2 Blooms.....	11
7.3 Rails.....	11
7.4 Identification	11
7.4.1 Branding.....	11
7.4.2 Hot stamping.....	12
7.4.3 Cold stamping.....	12
7.4.4 Other identification	12
8 Qualification of the manufacturer.....	12
9 Acceptance tests	13
9.1 Laboratory tests.....	13
9.1.1 General.....	13
9.1.2 Chemical composition	13
9.1.3 Microstructure	17
9.1.4 Decarburization.....	17
9.1.5 Hardness.....	17
9.1.6 Tensile tests	18
9.1.7 Retest procedures.....	19
9.2 Dimension tolerances.....	19
9.2.1 Profile	19
9.2.2 Straightness and twist	20
9.2.3 Cutting and drilling.....	20
9.3 Gauges	20
9.4 Inspection for internal quality and surface quality.....	21
9.4.1 Internal quality	21
9.4.2 Surface quality.....	23
9.4.3 Checking of automated testing equipment.....	24
Annex A (normative) Rail profiles	34

Annex B (informative) Comparison of steel designations referred to in this European Standard compared to those in EN 10027-2	66
Bibliography	67

This document is a preview generated by EVS

European foreword

This document (EN 13674-4:2019) has been prepared by Technical Committee CEN/TC 256 “Railway applications”, the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2019, and conflicting national standards shall be withdrawn at the latest by October 2019.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 13674-4:2006+A1:2009.

This part of EN 13674 is the fourth one of the series EN 13674, *Railway applications — Track — Rail*, which consists of the following parts:

- *Part 1: Vignole railway rails 46 kg/m and above;*
- *Part 2: Switch and crossing rails used in conjunction with Vignole railway rails 46 kg/m and above;*
- *Part 3: Check rails;*
- *Part 4: Vignole railway rails from 27 kg/m to, but excluding 46 kg/m.*

Other published standards include the following:

- EN 14587-1, *Railway applications – Infrastructure – Flash butt welding of new rails – Part 1: R220, R260, R260Mn, R320Cr, R350HT, R350LHT, R370CrHT and R400HT grade rails in a fixed plant;*
- EN 14587-2, *Railway applications – Track – Flash butt welding of rails – Part 2: New R220, R260, R260Mn and R350HT grade rails by mobile welding machines at sites other than a fixed plant;*
- EN 14587-3, *Railway applications – Track – Flash butt welding of rails – Part 3: Welding in association with crossing construction;*
- EN 14730-1, *Railway applications – Track – Aluminothermic welding of rails – Part 1: Approval of welding processes;*
- EN 14730-2, *Railway applications – Track – Aluminothermic welding of rails – Part 2: Qualification of aluminothermic welders, approval of contractors and acceptance of welds;*
- EN 14811, *Railway applications – Track – Special purpose rail – Grooved rails and associated construction profiles;*
- EN 15594, *Railway applications – Track – Restoration of rails by electric arc welding;*
- EN 16273, *Railway applications – Track – Forged rail transitions.*

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta,

Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

This document is a preview generated by EVS

Introduction

This Introduction provides an explanation of the concepts and reasoning used in the drafting of this document. Its inclusion also ensures that during future revisions, restrictions are removed where technology progresses and held where it does not, thus ensuring continued safety as new manufacturers, products and technologies are introduced.

The most commonly used standards of the world for the supply of railway rails have been reviewed during the preparation of this document. However, modern rail production technology within the European Union has demanded a completely new look at the philosophy and content of this part of EN 13674.

Whenever possible this part of EN 13674 is performance based, recognizes the European Quality System standard EN ISO 9001 and requires manufacturers to offer the latest proven technology to consistently satisfy the demanding quality of the required product.

Rail grading is based on hardness rather than tensile strength.

The acceptance tests have been designed to control those characteristics of the rail steel and rail that are of relevance to the production of high quality rails and the demands of the railway.

The steel grades covered by this part of EN 13674 reflect trends in railway usage and heat-treated rails are included. This document includes rail profiles for Vignole rails having a linear mass from 27 kg/m to, but excluding 46 kg/m.

To ensure the supply of high quality rails, some restrictions on production processes have been imposed.

This document supersedes national standards covered by the Scope. In addition CEN required, where possible, a performance based standard, taking into account safety implications and at the same time addressing modern production technology. It was recognized that there would be few opportunities (and these would have to be for transparent safety considerations) for derogation from this document to operate between the user and the manufacturer.

This document reflects this change in philosophy from the traditional content of rail standards. A review was undertaken of the most commonly used rail standards of the world. All relevant aspects important to both user and manufacturer were considered with the aim of ensuring that all of the content had specific usefulness and relevance. For example rail grading and much of this document has been based on hardness rather than tensile strength. While the two are directly related, hardness is very quick and cheap to carry out and provides more relevant guidance to the user particularly where properties vary in different parts of the profile.

Since many rail manufacturers would not have previously carried out proving trials, this document includes a prerequisite for all manufacturers to prove conformity against a set of qualifying test criteria at the time of tendering. The qualifying tests include all "normal" acceptance test results plus new 'type-casting' features such as fracture toughness, fatigue and residual stress (see EN 13674-1). To provide users with the necessary confidence, acceptance limits have been based on results from rail known to have performed well in demanding track installations.

One aspect of this document, which is a complete break from tradition, is the inclusion of quality assurance and inspection clause as part of product integrity.

So that quality management systems are consistent across all manufacturers and that users have the best assurance for the consistency of required product quality on this safety critical component of the track, the rail standard requires that the manufacturers' quality assurance systems are at least equivalent to the requirements of a quality management standard such as EN ISO 9001. The inclusion of this requirement also reduces the need to incorporate detailed method and calibration descriptions on items such as normal chemical composition determination and the need to define more extensive testing.

Ideally, manufacturing techniques should not be referenced in a product standard. However, some rail attributes are either not known in an exact manner or are not measurable with satisfactory statistical significance. In such cases best practice manufacturing techniques have been included as a last resort. The equipment specified is that which gives the best probability of achieving the required product for use in track. In the future new technology can add to, but preferably will reduce or delete such items.

Examples of areas where the technological state of the art renders the standard less than complete include:

- oxide/oxygen relationships;
- hydrogen test techniques;
- roller straightening effects on residual stresses;
- roller straightening effects on contact scrub;
- measurement and effect of residual stresses throughout the rail.

1 Scope

This document specifies flat bottom Vignole railway rails from 27 kg/m to, but excluding 46 kg/m.

Eight pearlitic steel grades are specified covering a rail hardness range of 200 HBW to 440 HBW and include non-heat-treated non-alloy steels, non-heat-treated alloy steels, heat-treated non-alloy steels and heat-treated alloy steels.

There are 15 rail profiles specified in this document, but these may not be available in all steel grades.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 10027-1, *Designation systems for steels – Part 1: Steel names*

EN 10027-2, *Designation systems for steels – Part 2: Numerical system*

EN 10163-1, *Delivery requirements for surface condition of hot-rolled steel plates, wide flats and sections – Part 1: General requirements*

EN 13674-1:2011+A1:2017, *Railway applications – Track – Rail – Part 1: Vignole railway rails 46 kg/m and above*

EN ISO 6506-1, *Metallic materials – Brinell hardness test -- Part 1: Test method (ISO 6506-1)*

EN ISO 6892-1, *Metallic materials – Tensile testing – Part 1: Method of test at room temperature (ISO 6892-1)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

heat

liquid steel melt tapped out of a converter or electric arc furnace which includes after continuous casting a given number of blooms relating to the weight of the heat and the extension of the mixing zone

Note 1 to entry: In the case of sequence casting the blooms belonging to the mixing zone should be clearly defined.

3.2

sequence

number of heats, of the same steel grade, which undergo continuous casting in tundishes

Note 1 to entry: Tundishes can be used in parallel if the caster has many strands.