INTERNATIONAL STANDARD

Acoustics — Preferred frequencies

Acoustique — Fréquences normales



Foreword

ISO (the International Grganization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and nongovernmental, in liaison with ISO also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % on the member bodies casting a vote.

International Standard ISO 266 was prepared by Technical Committee ISO/TC 43, *Acoustics*.

This second edition cancels and replaces the first edition (ISO 266:1975), which has been technically revised.

Annex A of this International Standard is for information only the Schner Report of the Schne

© ISO 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization Case postale 56 • CH-1211 Genève 20 • Switzerland

Internet central@iso.ch

X.400 c=ch; a=400net; p=iso; o=isocs; s=central

Printed in Switzerland

Introduction

This International Standard specifies a series of preferred frequencies in order to provide a common basis for comparing the results of acoustical measurements.

The frequency series is referred to the reference frequency of 1 000 Hz, which is also the reference frequency for the definition of the phon (see ISO 31-7).

The specification of the preferred frequency series reduces to a minimum number of frequencies at which acoustical data need to be tabulated. Also measurement equipment may be specifically constructed for these frequencies.

The specified series of preferred frequencies uses powers of 10 and is therefore especially convenient for extensions into the infrasonic and ultrasonic (frequency) ranges. Another series of frequencies that is in use is based on the definition of the octave as the frequency ratio 1:2. The frequencies of the series are calculated as powers of two (IEC 1260 basetwo series).

Strictly, these two series are incompatible. However the base-two series may be accepted as a sufficient approximation to the base-ten series because of the fact that $2^{1/3} = 1,259$ 9... is very nearly the same as $10^{1/10} = 1,258$ 9...

Practical considerations make some additional rounding desirable: Thus 500 Hz is listed instead of 501, 187,233... Hz, which is the exact frequency from the base-ten series. The calculated value of the exact frequency expressed to five significant figures is given in the second column of table 1. In this way, the maximum individual deviation, in the frequency range 20 Hz to 20 000 Hz, between the rounded preferred frequencies and the calculated frequencies for the base-ten and base-two series is 0,94 % and 1,59 %, respectively.



This boommont is This page Mentionally left blank The wiew Connectionally left blank

Acoustics — Preferred frequencies

Scope 1

This International Standard spectices preferred frequencies for acoustical measurements. The preferred frequencies are based on the R10 series of preferred numbers in ISO 3 and the reference frequency of 1 000 Hz.

or most acoustic norement is generally p. measurements, a constant freque. The International Standard deals with the geometry frequency increment, or other particular spacing, would the adoption or retention of other frequencies. For most acoustical measurements and presentations of data, a frequency spacing based on a constant percentage increment is generally preferred and the test frequencies then form a geometric series. For certain acoustical

The International Standard deals with the geometric series and is not intended to apply to cases where a constant frequency increment, or other particular spacing, would be more suitable, or where there may be good reasons for

2 Normative reference

The following standard contains provisions which, through reference this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below, members of IEC and ISO maintain registers of currently valid International Standards.

ISO 3:1973, Preferred numbers — Series of preferred numbers.

3 Definitions

For the purposes of this International Standard, the following definitions apply.

3.1 exact frequency: Frequency, expressed in hertz, which is calculated from the formula:

$$f = 10^{n/10} f_r$$

where f_r is the reference frequency 1 000 Hz and n is an integer, positive or negative.

3.2 calculated frequency: Frequency approximating to the exact frequency, expressed to five significant figures.

3.3 preferred frequency: Frequency equal in magnitude to one of the R10 series of preferred numbers defined in ISO 3.

