

---

---

**Paints and varnishes — Evaluation of  
properties of coating systems related to  
the application process —**

**Part 2:**

**Colour stability, process hiding power,  
re-dissolving, overspray absorption,  
wetting, surface texture and mottling**

*Peintures et vernis — Évaluation des propriétés des systèmes de  
revêtement liées au mode d'application —*

*Partie 2: Stabilité des couleurs, pouvoir masquant du procédé,  
détrempe, absorption des pertes de peinture à la pulvérisation,  
mouillage, texture superficielle et marbrures*



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

Foreword .....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references .....	1
3 Terms and definitions .....	1
4 Colour stability .....	1
4.1 General .....	1
4.2 Evaluation.....	1
5 Process hiding power .....	3
5.1 General .....	3
5.2 Evaluation.....	3
6 Re-dissolving .....	3
6.1 General .....	3
6.2 Evaluation.....	4
7 Overspray absorption .....	4
7.1 General .....	4
7.2 Evaluation.....	4
8 Wetting.....	5
8.1 General .....	5
8.2 Evaluation.....	5
9 Surface texture .....	6
9.1 General .....	6
9.2 Evaluation.....	6
9.2.1 General evaluation .....	6
9.2.2 Evaluation of base coats .....	6
9.2.3 Evaluation of clear coats .....	7
10 Mottling.....	8
10.1 General .....	8
10.2 Evaluation.....	8
11 Test report.....	8
Bibliography.....	9

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 28199-2 was prepared by Technical Committee ISO/TC 35, *Paints and varnishes*, Subcommittee SC 9, *General test methods for paints and varnishes*.

ISO 28199 consists of the following parts, under the general title *Paints and varnishes — Evaluation of properties of coating systems related to the application process*:

- *Part 1: Relevant vocabulary and preparation of test panels*
- *Part 2: Colour stability, process hiding power, re-dissolving, overspray absorption, wetting, surface texture and mottling*
- *Part 3: Visual assessment of sagging, formation of bubbles, pinholing and hiding power*

## Introduction

In many areas (e.g. car manufacture, industrial coatings, coatings for plastics) the coating materials used are adapted to the specific application equipment and technologies of the particular user. A coating material is, therefore, understood to be a semi-manufactured product that only receives its final form in combination with the specific application conditions. The adaptation to the application conditions is therefore decisive for the quality of the coated product.

The test methods specified in ISO 28199 are based on studies by a Working Group of the European Council for Automotive R&D (EUCAR).

They may be used for evaluation of coating materials in research, development and production with regard to their suitability and safety for industrial processes, and error analysis. The properties of coating materials and coatings to be evaluated depend on the film thickness, so a coating system of increasing thickness is applied to a test panel under defined conditions.

The following characteristics are measured (in ISO 28199-1):

- film thickness in accordance with ISO 2808;
- surface texture;
- colour in accordance with ISO 7724 (all parts).

In combination with visual assessment, the following properties are determined:

- colour stability, process hiding power, re-dissolving, overspray absorption, wetting, surface texture and mottling (this part of ISO 28199);
- tendency to sagging, formation of bubbles, pinholing and hiding power (ISO 28199-3).

This document is a preview generated by EVS

# Paints and varnishes — Evaluation of properties of coating systems related to the application process —

## Part 2:

## Colour stability, process hiding power, re-dissolving, overspray absorption, wetting, surface texture and mottling

### 1 Scope

This part of ISO 28199 specifies methods for the determination of colour stability, process hiding power, re-dissolving, overspray absorption, wetting, surface texture and mottling of coating materials applied to a test panel under defined conditions.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 28199-1:2009, *Paints and varnishes — Evaluation of properties of coatings related to the application process — Part 1: Relevant vocabulary and preparation of test panels*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 28199-1 apply.

### 4 Colour stability

#### 4.1 General

Colour stability is determined by evaluation of the values measured for a wedge-shaped base coat and constant-thickness clear coat, obtained in accordance with 9.4 of ISO 28199-1: 2009.

#### 4.2 Evaluation

Plot the colour space values determined for the wedge-shaped base coat and constant-thickness clear coat in accordance with ISO 28199-1:2009, 9.4, against the film thickness of the base coat, and evaluate the development of the curve visually. Determine the lowest ( $t_{\min}$ ) and the highest ( $t_{\max}$ ) film thicknesses at which the curve is approximately parallel to the X-axis. With regard to parallelism, a tolerance range or a minimum gradient shall be agreed. Figures 1 and 2 showing examples of film thickness plotted against lightness ( $L^*$ ). The Y-axis can also show the colour values  $a^*$ ,  $b^*$ ,  $C^*$  and  $h$ .

The range of colour stability ends at that film thickness at which the curve is no longer parallel to the X-axis.