INTERNATIONAL STANDARD

ISO 28219

First edition 2009-01-15

Packaging — Labelling and direct product marking with linear bar code and two-dimensional symbols

Emballage — Étiquetage et marquage direct sur le produit avec un code à barres et des symboles bidimensionnels



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below





COPYRIGHT PROTECTED DOCUMENT

© ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Cont	ents F	⊃age
Forewo	ord	iv
Introdu	uction	v
1	Scope	1
2	Normative references	2
3	Terms and definitions	3
4 4.1 4.2 4.3 4.4	Requirements Identification Data format common requirements General layout and location Symbol requirements	5 14
Annex	A (normative) Label adhesive characteristics and mark durability	24
Annex	B (informative) Partial list of commonly used identifiers	31
Annex	C (informative) Subset of ASCIGISO/IEC 646 (table of hexadecimal and decimal values)	32
Annex	D (informative) User guidance for inplementation of the ISO 15434 data syntax	33
Annex	E (informative) Data format for UPPA (UCC-12), EAN-13 and GS1-128 symbols	34
Annex	F (informative) For applications using tode 39 and Code 128 symbologies	39
Annex	G (informative) Using DUNS®, with ASC M410 Data Identifiers (DIs) in linear bar code and two-dimensional symbols	43
Annex	H (informative) Register of issuing agency codes (IACs) for ISO/IEC 15459	45
Bibliog	H (informative) Register of issuing agency codes (IACs) for ISO/IEC 15459	48

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in traison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 28219 was prepared by Technical Committee ISO/TC 122, Packaging.

SISO/TC 122, Packay...

Introduction

Today, global industries widely use machine-readable markings on products for inventory control, quality control, and product life cycle management. Common technologies, data structures, conformance, and applications standards are necessary to enable all trading partners to use such markings internally and throughout the supply chain.

A number of different product labelling and marking standards exist, each designed to meet the requirements of the specific industry sector. For effective and economic use within and between industry sectors one common multi-industry standard is a necessity.

A standard linear bar solte or two-dimensional symbol marked on a product or part will facilitate the automation of inventory cantol, quality control, and product life cycle management. The linear bar code or two-dimensional symbol information on the product may be used as a key to access the appropriate database that contains detailed information about the product, including information transmitted via EDI. In addition a product mark may contain other information as agreed between the trading partners.

© ISO 2009 - All rights reserved

Inis document is a preview denetated by EUS

Packaging — Labelling and direct product marking with linear bar code and two-dimensional symbols

Scope This International Sta defines minimum requirements for identifying items; provides guidelines for item marking with machine-readable symbols; covers both labels and direct arking of items; includes testing procedures for label adhesive characteristics and mark durability; provides guidance for the formatting on the label of data presented in linear bar code, two-dimensional symbol or human readable form: symbol or human readable form; is intended for applications which include, but are not limited to, support of systems that automate the control of items during the processes of: production; inventory; distribution; field service; point of sale; repair, and is intended to include, but it is not limited to, multiple industries including automotive; aerospace; chemical; consumer items; electronics; health care: marine; rail: telecommunications.

The location and application method of the marking are not defined (these will be reviewed and agreed upon by suppliers and manufacturers and their trading partners before implementing this International Standard).

This International Standard does not supersede or replace any applicable safety or regulatory marking or labeling requirements. This International Standard is meant to satisfy the minimum item marking requirements of numerous applications and industry groups and as such its applicability is to a wide range of industries, each of which may have specific implementation guidelines for it. This International Standard is to be applied in addition to any other mandated labeling direct-marking requirements.

The labeling and direct marking requirement of this International Standard and other standards can be combined labeling into on label or marking area or appear as separate labels or marking areas.

This International Standard uses the terms "part marking" and "item marking" interchangeably. Unless otherwise stated, this document will use the term "item marking" to describe both the labeling and direct part marking (DPM) of an item, where DPM includes, but is not limited to, altering (e.g. dot peen, laser etch, chemical etch) as well as additive type processes (e.g. ink jet, vacuum deposition).

The purpose of this International Standard is to establish the machine-readable (linear, two dimensional, and composite symbols) and human readable content for direct marking and labeling of items, parts, and components.

This International Standard provides a means for items, parts and components to be marked, and read in either fixtured or handheld scanning environments at any manufacturer's facility and then read by customers purchasing items for subsequent manufacturing operations or for final end use. Intended applications include, but are not limited to supply chain applications, e.g. inventory, distribution, manufacturing, quality control, acquisition, transportation, supply, repair, and disposal.

The figures are illustrative and not necessarily to scale or to the quality requirements specified in this International Standard.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 646, Information Processing — ISO 7-Bit Coded Character Set for information Interchange

ISO/IEC 3166-1, Codes for the representation of names of countries and the bubdivisions — Part 1: Country Code

ISO/IEC 15415, Information technology, identification and data capture techniques. Bar code symbol print quality test specification — Two-dimensional symbols

ISO/IEC 15416, Information technology, identification and data capture techniques — Bar code print quality test specification — Linear symbols

ISO/IEC 15417, Information technology, identification and data capture techniques — Bar code symbology specification — Code 128

ISO/IEC 15418, Information technology, Automatic identification and data capture techniques — GS1 Application Identifiers and ASC MH10 Data Identifiers

ISO/IEC 15434, Information technology — Automatic identification and data capture techniques — Data Syntax for high capacity ADC media

ISO/IEC 15438, Information technology — Automatic identification and data capture techniques — Bar code symbology specification — PDF417

ISO/IEC 15459-2, Information technology — Unique identifiers — Part 2: Registration procedures

ISO/IEC 16022, Information technology — Automatic identification and data capture techniques — Bar code symbology specification — Data Matrix

ISO/IEC 16388, Information technology — Automatic identification and data capture techniques — Bar code symbology specification — Code 39

ISO/IEC 18004, Information technology — Automatic identification and data capture techniques — QR Code 2005 bar code symbology specification

ISO/IEC 19762 Information technology — Automatic identification and data capture techniques — Harmonized vocabiliary

ISO 21067, Packaging - Vocabulary

ISO/IEC 24723, Information technology — Automatic identification and data capture techniques — Bar code symbology specification — Composite component

ISO/IEC 24728, Information technology — Automatic identification and data capture techniques — Bar code symbology specification — Micro 257417

ANS MH10.8.2, Data Application Identifier Standard

AIM DPM-1, Direct Part Mark (DPM) Quality Guideline

ASTM D1000-93, Pressure-Sensitive Adhesive-Coated Tapes Used for Electrical and Electronic Applications

Dun & Bradstreet, DUNS® Number

GS1 General Specifications

International Symbology Specification — GS1 Composite Symbology

NAMSA, ACodP-1(D), Chapter 2, Subsection 242-243, (NCAGE)

3 Terms and definitions

For the purposes of this document, the terms and definitions given 150/IEC 19762 and ISO 21067 and the following apply.

3.1

cell

smallest element of a two-dimensional matrix symbol

3.2

CLEI[™] code

coding structure maintained by Telcordia that identifies communications equipment, in a concise, uniform feature-oriented language, describing product type, features, source document and associated drawings and vintages

3.3

components

parts (bare printed circuit board, integrated circuits, capacitor, diodes, switch, valve, spring, bearing, bracket, bolt, etc.) of a first level/modular assembly

3.4

data element separator

specified character used to delimit discrete fields of data

© ISO 2009 – All rights reserved