INTERNATIONAL STANDARD

ISO 3536

Third edition 2016-06-01

Romat. Véhicules ro.



Reference number ISO 3536:2016(E)



© ISO 2016, Published in Switzerland

voduced or utilized c te internet or an 'nr ISO's memb All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 35, *Lighting and visibility*.

This third edition cancels and replaces the second edition (ISO 3536:1999), which has been technically revised.

Road vehicles — Safety glazing materials — Vocabulary

1 Scope

This International Standard defines terms relating to safety glazing materials for road vehicles.

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

2.1

safety glazing material

glazing material consisting of organic and/or inorganic materials so constructed or treated to minimize the likelihood of injury to persons as a result of contact with these safety glazing materials when used in a vehicle and which complies with specified requirements for visibility, strength, and durability

2.2

toughened safety glass

glazing material consisting of a single layer of glass which has been subjected to special thermal or chemical treatment to increase its mechanical strength and to condition its fragmentation after shatter

2.3

laminated safety glass

glazing material consisting of two or more layers of glass held together by one or more *interlayers* (2.4)

Note 1 to entry: The following two types are recognized:

- ordinary: when none of the layers of glass, of which it is composed, has been treated, i.e. normal annealed glass;
- treated: when at least one of the layers of glass, of which it is composed, is toughened safety glass (2.2) or glass which has been treated in any controlled process in order to give it increased resistance to mechanical and thermal stress.

2.4

interlayer

plastic material designed to be used to permanently bond together the component layers of *laminated* safety glass (2.3)

2.5

glass-plastic glazing material

glazing material which may comprise one layer of glass and one or more layers of plastic in which a plastic surface faces inward towards the vehicle passenger compartment when installed in the vehicle

2.6

plastic safety glazing material

safety glazing material (2.1) that contains, as an essential ingredient, one or more layers of organic polymeric substances

Note 1 to entry: The following two types are recognized:

- rigid plastic: organic polymeric material which maintains its structural stiffness over the intended use range;
- flexible plastic: organic polymeric material which remains conformable over the intended use range.