
International Standard



486

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Cinematography — 16 mm motion-picture film perforated 8 mm Type R — Cutting and perforating dimensions

Cinématographie — Film cinématographique 16 mm perforé 8 mm type R — Dimensions de coupe et de perforation

Second edition — 1982-08-01

UDC 771.531.352 : 77.021.17

Ref. No. ISO 486-1982 (E)

Descriptors : cinematography, motion-picture film, motion-picture film 8 mm, perforating, cutting, dimensions.

Price based on 3 pages

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been set up has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 486 was developed by Technical Committee ISO/TC 36, *Cinematography*, and was circulated to the member bodies in April 1981.

It has been approved by the member bodies of the following countries :

Austria	Germany, F. R.	South Africa, Rep. of
Belgium	Italy	Spain
Canada	Japan	Sweden
Czechoslovakia	Korea, Dem. P. Rep. of	United Kingdom
Denmark	Korea, Rep. of	USA
Egypt, Arab Rep. of	Mexico	USSR
France	Poland	

No member body expressed disapproval of the document.

This second edition cancels and replaces the first edition (i.e. ISO 486-1974).

Cinematography — 16 mm motion-picture film perforated 8 mm Type R — Cutting and perforating dimensions

1 Scope and field of application

This International Standard specifies the cutting and perforating dimensions for 16 mm motion-picture film which is perforated 8 mm Type R, as well as the width of motion-picture film after processing and slitting.

NOTE — Film perforated in accordance with this International Standard is also referred to as "double 8 mm motion-picture film".

2 Reference

ISO 543, *Cinematography — Motion-picture safety film — Definition, testing and marking*.