
Small craft — Principal data

Petits navires — Données principales



This document is a preview generated by EBS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	v
1 Scope	1
2 Terms and definitions	1
3 Symbols, designations and units	2
4 Measurements	3
4.1 General	3
4.2 Longitudinal	4
4.2.1 General	4
4.2.2 Maximum length, L_{\max}	4
4.2.3 Length of the hull, L_H	4
4.2.4 Waterline length, L_{WL}	7
4.3 Athwartship	8
4.3.1 General	8
4.3.2 Maximum beam, B_{\max}	8
4.3.3 Beam of hull, B_H	8
4.3.4 Beam, waterline, B_{WL}	8
4.3.5 Maximum beam, waterline, $B_{WL\max}$	8
4.3.6 Beam between hull centers, B_{CB}	8
4.4 Vertical	9
4.4.1 Maximum depth, D_{\max}	9
4.4.2 Midship depth, $D_{LWL/2}$	9
4.4.3 Freeboard, F	10
4.4.4 Draught, T	10
4.4.5 Draught, air, H_a	10
4.4.6 Headroom	11
4.5 Other data	11
4.5.1 Deadrise angle, β	11
4.5.2 Reference sail area, A_S	12
4.5.3 Standard sail area, A'_S	12
4.5.4 Windage area, A_{IV}	12
4.5.5 Volume of the craft, V	12
5 Masses	13
5.1 Mass, net shipping, m_N	13
5.2 Mass, gross shipping, m_G	13
5.3 Mass, light craft, m_{LC}	14
5.3.1 Items of equipment included in m_{LC}	14
5.3.2 Items of equipment and other items not included in m_{LC}	15
5.4 Performance test mass, m_P	15
5.5 Mass of the craft when towed on a trailer, m_T	16
5.5.1 General	16
5.5.2 Items of equipment included in m_T	16
5.5.3 Items of equipment not included in m_T	18
5.5.4 Exclusions, inclusions	18
5.6 Maximum load, m_{ML}	18
6 Loading conditions	19
6.1 Test condition	19
6.2 Ready-for-use condition	19
6.3 Fully loaded ready-for-use condition	19
6.4 Empty craft condition	19
6.5 Light craft condition	20
6.6 Minimum operating condition	21
6.7 Loaded arrival condition	21

6.8	Maximum load condition	21
7	Tolerances	21
7.1	Published data	21
7.2	Preliminary specification	22
7.3	Reference lengths	22
	Bibliography	23

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 188, *Small craft*.

This second edition cancels and replaces the first edition (ISO 8666:2002), which has been technically revised with the following main changes:

- definitions [2.7](#) to [2.13](#) have been added;
- list of symbols in [Table 1](#) has been extended;
- [4.3.5](#) and [4.3.6](#) have been added;
- [4.5.2](#), [4.5.3](#) and [4.5.4](#) have been added, and “projected sail area” has been deleted;
- [6.4](#) to [6.8](#) have been added;
- [7.1](#) has been modified and [7.3](#) added;
- clause on owner's manual has been deleted.

Small craft — Principal data

1 Scope

This International Standard establishes definitions of main dimensions and related data and of mass specifications and loading conditions. It applies to small craft having a length of the hull (L_H) of up to 24 m.

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

NOTE For units, see [Clause 3](#).

2.1

waterline

WL

intersection line of the water's surface with the craft's hull when the *craft* ([2.13](#)) is afloat

2.2

maximum load waterline

reference waterline

WL_{ref}

waterline ([2.1](#)) of the *craft* ([2.13](#)) when upright in the maximum *loaded displacement* ([2.5.1](#))

2.3

sheerline

intersection between deck and hull, for rounded deck edges the natural intersection, or, where no deck is fitted or the hull extends above the deck (bulwark), the upper edge of the craft's hull

Note 1 to entry: The upper position of the sheerline depends on the inclination between the hull/deck intersection and the actual deck.

2.4

transom beam

B_T

maximum width of the hull at the transom at or below the *sheerline* ([2.3](#)), excluding extensions, handles and fittings

Note 1 to entry: Where spray rails act as chines or part of the planing surface, they are included in the transom beam measurement.

Note 2 to entry: For *craft* ([2.13](#)) with a rounded or pointed stern or with a transom beam of less than half the maximum beam of the craft, the transom beam, B_T , is the widest beam at or below the sheerline at the aft quarter length of the hull.

2.5

displacement

mass of water displaced by the *craft* ([2.13](#)), including all appendages

2.5.1

loaded displacement

m_{LDC}

mass of water displaced by the *craft* ([2.13](#)), including all appendages, when in the fully loaded ready-for-use condition

Note 1 to entry: Fully loaded ready-for use condition is described in [6.3](#).