
**Road vehicles — Local Interconnect
Network (LIN) —**

**Part 3:
Protocol specification**

Véhicules routiers — Réseau Internet local (LIN) —

Partie 3: Spécification du protocole

This document is a preview generated by EBS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	1
3.1 Terms and definitions	1
3.2 Symbols	4
3.3 Abbreviated terms	4
4 Node concept	5
4.1 General	5
4.2 Concept of operation	6
4.2.1 Master and slave	6
4.2.2 Frames	6
4.2.3 Data transport	7
5 Protocol requirements	7
5.1 Signal	7
5.1.1 Management	7
5.1.2 Types	7
5.1.3 Consistency	7
5.1.4 Packing	7
5.1.5 Reception and transmission	8
5.2 Frame	9
5.2.1 Transfer	9
5.2.2 Structure	9
5.2.3 Frame length	13
5.2.4 Frame types	14
5.3 Schedule tables	19
5.3.1 General	19
5.3.2 Time definitions	19
5.3.3 Frame slot	19
5.3.4 Schedule table handling	20
5.4 Task behaviour model	20
5.4.1 General	20
5.4.2 Master task state machine	20
5.4.3 Slave task state machine	21
5.5 Status management	23
5.5.1 General	23
5.5.2 Concept	23
5.5.3 Event-triggered frames	23
5.5.4 Reporting to the cluster	23
5.5.5 Reporting within own node	24
6 Node configuration and identification	24
6.1 General	24
6.2 LIN product identification	25
6.2.1 Supplier ID, function ID and variant ID	25
6.2.2 Serial number	25
6.2.3 Wildcards	25
6.3 Slave node model	25
6.3.1 Memory model	25
6.3.2 Slave node configuration variants	26
6.3.3 Initial node address	27
6.3.4 PDU structure	27

6.3.5	Node configuration handling	29
6.3.6	Node configuration services	29
Annex A (normative) Definition of properties, frame identifiers and various examples		35
Annex B (informative) LIN history and version compatibility		39
Annex C (informative) LIN auto addressing methods		43
Bibliography		44

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

A list of all parts in the ISO 17987 series can be found on the ISO website.

Introduction

ISO 17987 (all parts) specifies the use cases, the communication protocol and physical layer requirements of an in-vehicle communication network called Local Interconnect Network (LIN).

The LIN protocol as proposed is an automotive focused low speed UART-based network (Universal Asynchronous Receiver Transmitter). Some of the key characteristics of the LIN protocol are signal-based communication, schedule table-based frame transfer, master/slave communication with error detection, node configuration and diagnostic service communication.

The LIN protocol is for low cost automotive control applications, for example, door module and air condition systems. It serves as a communication infrastructure for low-speed control applications in vehicles by providing the following:

- signal-based communication to exchange information between applications in different nodes;
- bit rate support from 1 kbit/s to 20 kbit/s;
- deterministic schedule table based frame communication;
- network management that wakes up and puts the LIN cluster into sleep mode in a controlled manner;
- status management that provides error handling and error signalling;
- transport layer that allows large amount of data to be transmitted (such as diagnostic services);
- specification of how to handle diagnostic services;
- electrical physical layer specifications;
- node description language describing properties of slave nodes;
- network description file describing behaviour of communication;
- application programmer's interface.

ISO 17987 (all parts) is based on the Open Systems Interconnection (OSI) Basic Reference Model as specified in ISO/IEC 7498-1 which structures communication systems into seven layers.

The OSI model structures data communication into seven layers called (top down) *application layer* (layer 7), *presentation layer*, *session layer*, *transport layer*, *network layer*, *data link layer* and *physical layer* (layer 1). A subset of these layers is used in ISO 17987 (all parts).

ISO 17987 (all parts) distinguishes between the services provided by a layer to the layer above it and the protocol used by the layer to send a message between the peer entities of that layer. The reason for this distinction is to make the services, especially the application layer services and the transport layer services, reusable also for other types of networks than LIN. In this way, the protocol is hidden from the service user and it is possible to change the protocol if special system requirements demand it.

ISO 17987 (all parts) provides all documents and references required to support the implementation of the requirements related to.

- ISO 17987-1: This part provides an overview of ISO 17987 (all parts) and structure along with the use case definitions and a common set of resources (definitions, references) for use by all subsequent parts.
- ISO 17987-2: This part specifies the requirements related to the transport protocol and the network layer requirements to transport the PDU of a message between LIN nodes.
- ISO 17987-3: This part specifies the requirements for implementations of the LIN protocol on the logical level of abstraction. Hardware related properties are hidden in the defined constraints.

- ISO 17987-4: This part specifies the requirements for implementations of active hardware components which are necessary to interconnect the protocol implementation.
- ISO/TR 17987-5: This part specifies the LIN API (Application Programmers Interface) and the node configuration and identification services. The node configuration and identification services are specified in the API and define how a slave node is configured and how a slave node uses the identification service.
- ISO 17987-6: This part specifies tests to check the conformance of the LIN protocol implementation according to ISO 17987-2 and ISO 17987-3. This comprises tests for the data link layer, the network layer and the transport layer.
- ISO 17987-7: This part specifies tests to check the conformance of the LIN electrical physical layer implementation (logical level of abstraction) according to ISO 17987-4.

Road vehicles — Local Interconnect Network (LIN) —

Part 3: Protocol specification

1 Scope

This document specifies the LIN protocol including the signal management, frame transfer, schedule table handling, task behaviour and status management and LIN master and slave node. It contains also OSI layer 5 properties according to ISO 14229-7 UDSON-based node configuration and identification services (SID: B0₁₆ to B8₁₆) belonging to the core protocol specification.

A node (normally a master node) that is connected to more than one LIN network is handled by higher layers (i.e. the application) not within the scope of this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 17987-2:2016, *Road vehicles — Local Interconnect Network (LIN) — Part 2: Transport protocol and network layer services*

ISO 17987-4:2016, *Road vehicles — Local Interconnect Network (LIN) — Part 4: Electrical Physical Layer (EPL) specification 12V/24V*

ISO 17987-6:2016, *Road vehicles — Local Interconnect Network (LIN) — Part 6: Protocol conformance test specification*

3 Terms, definitions, symbols and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 17987-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1.1

big-endian

method of storage of multi-byte numbers with the most significant bytes at the lowest memory addresses

3.1.2

broadcast NAD

addressing every slave node on LIN