INTERNATIONAL STANDARD

ISO 16000-28

First edition 2012-03-15

Indoor air —

Part 28:

Determination of odour emissions from building products using test chambers

Air intérieur —

Partie 28: Détermination des émissions d'odeurs des produits de construction au moyen de chambres d'essai





© ISO 2012

duced or utilized in any for a from either ISO at the rAll rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

Page

Contents

Forew	ord	V
Introdu	uction	vii
1	Scope	1
2	Normative references	1
3 3.1 3.2 3.3	Terms, definitions, symbols, units and abbreviated terms Terms and definitions Symbols and units Abbreviated terms	1 4
4	Principle	5
5 5.1 5.2 5.3 5.4 5.5 5.6	Test facilities General Apparatus Test chamber and equipment materials Air supply and mixing facilities Airtightness Odour sampling and assessment devices	5 6 6
6 6.1 6.2 6.3 6.4 6.5 6.6 6.7	Test conditions General Temperature and relative humidity in the test chamber Supply air quality and background concentration in the test chamber Air velocity in the test chamber Area-specific air flow rate and air exchange rate in the test chamber Test chamber airtightness Efficiency of the internal test chamber air mixing Test chamber and test room background odour	8 8 8
7	Test specimens	10
8 8.1 8.2 8.3	Odour testing from emission chamber Test chamber preparation Test specimen location in the test chamber Time of odour measurements	11 11
9 9.1 9.2 9.3 9.4	Odour panels Panel leader Panel selection Code of behaviour of the panel members Panel size and accuracy of the evaluation	11 12 12
10 10.1 10.2 10.3 10.4	Odour assessment General Acceptability using an untrained panel Perceived odour intensity Complementary method — Hedonic tone using an untrained panel	13 13
11	Test report	15
Annex	A (normative) System for quality assurance/quality control	17
Annex	B (informative) Statistical background	18
Annex	C (informative) Examples of diffuser and mask used for odour evaluation	20
Annex	D (informative) Description of a possible sampling and presentation device for air samples collected at the emission chamber outlet	21
Annex	E (informative) Panel selection using the stick method	26

ISO 16000-28:2012(E)

nnex F (informative) Panel selection using five st		
nnex G (informative) Training procedure for the o		
nex H (informative) Examples of area-specific a		
nex I (normative) Acceptability scale for an untr		
nex J (normative) Hedonic scale for an untraine		
oliography		36
ollography		
9		
(0)		
0.		
9		
•	6	
	4.	
	0	
	4	
	<u>O</u>	
	9,	
	, O	
	Q.	
		1
		(1)
		AU - 1 - 1
	© ISO 2012 – A	All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 16000-28 was prepared by Technical Committee ISO/TC 146, Air quality, Subcommittee SC 6, Indoor air.

ISO 16000 consists of the following parts, under the general title Indoor air:

- Part 1: General aspects of sampling strategy
- Part 2: Sampling strategy for formaldehyde
- Part 3: Determination of formaldehyde and other carbonyl compounds in indoor air and test chamber air —
 Active sampling method
- Part 4: Determination of formaldehyde Diffusive sampling method
- Part 5: Sampling strategy for volatile organic compounds (VOCs)
- Part 6: Determination of volatile organic compounds in indoor and test chamber air by active sampling on Tenax TA® sorbent, thermal desorption and gas chromatography using MS or MS-FID
- Part 7: Sampling strategy for determination of airborne asbestos fibre concentrations
- Part 8: Determination of local mean ages of air in buildings for characterizing ventilation conditions
- Part 9: Determination of the emission of volatile organic compounds from building products and furnishing —
 Emission test chamber method
- Part 10: Determination of the emission of volatile organic compounds from building products and furnishing — Emission test cell method
- Part 11: Determination of the emission of volatile organic compounds from building products and furnishing — Sampling, storage of samples and preparation of test specimens
- Part 12: Sampling strategy for polychlorinated biphenyls (PCBs), polychlorinated dibenzo-p-dioxins (PCDDs), polychlorinated dibenzofurans (PCDFs) and polycyclic aromatic hydrocarbons (PAHs)
- Part 13: Determination of total (gas and particle-phase) polychlorinated dioxin-like biphenyls (PCBs) and polychlorinated dibenzo-p-dioxins/dibenzofurans (PCDDs/PCDFs) — Collection on sorbent-backed filters
- Part 14: Determination of total (gas and particle-phase) polychlorinated dioxin-like biphenyls (PCBs) and polychlorinated dibenzo-p-dioxins/dibenzofurans (PCDDs/PCDFs) — Extraction, clean-up and analysis by high-resolution gas chromatography and mass spectrometry
- Part 15: Sampling strategy for nitrogen dioxide (NO2)
- Part 16: Detection and enumeration of moulds Sampling by filtration

ISO 16000-28:2012(E)

- Part 17: Detection and enumeration of moulds Culture-based method
- Part 18: Detection and enumeration of moulds Sampling by impaction
- Part 19: Sampling strategy for moulds
- Part 23: Performance test for evaluating the reduction of formaldehyde concentrations by sorptive building materials
- Part 24: Performance test for evaluating the reduction of volatile organic compound (except formaldehyde) concentrations by sorptive building materials
- Part 25: Determination of the emission of semi-volatile organic compounds by building products Microchamber method
- Part 26: Sampling strategy for carbon dioxide (CO2)
- Part 28: Determination of odour emissions from building products using test chambers

The following parts are under preparation:

- Part 21: Detection and enumeration of moulds Sampling from materials
- Part 27: Determination of settled fibrous dust on surfaces by SEM (scanning electron microscopy) (direct method)
- Part 29: Test methods for VOC detectors
- Part 30: Sensory testing of indoor air
- Part 31: Measurement of flame retardants and plasticizers based on organophosphorus compounds Phosphoric acid ester
- Part 32: Investigation of constructions on pollutants and other injurious factors Inspections

Introduction

Odour evaluation is a complementary method to the chemical testing of emissions from building products.

The determination of odour acceptability, intensity and hedonic tone, and intensity of emissions from building products using test chambers has objectives such as:

- to provide manufacturers, builders, and end users with data useful for the evaluation of the odour impact of building products on the indoor air quality;
- to promote the development of improved products.

The method can also be used for building furnishings.

ed for 3 12219[26]-ISO 16017^[31] [32] and ISO 12219^[26]–[30] focus on volatile organic compound (VOC) measurements.

© ISO 2012 - All rights reserved

This document is a previous generated by tills

Indoor air —

Part 28:

Determination of odour emissions from building products using test chambers

1 Scope

This part of ISO 16000 specifies a laboratory test method using test chambers defined in ISO 16000-9 and evaluation procedures for the determination of odours emitted from newly produced building products under defined climate conditions. The method can also, in principle, be applied to aged products. This part of ISO 16000 is applicable to various test chambers used for the determination of emissions from building products.

NOTE This part of ISO 16000 can also be used for other products or materials.

Sampling, transport and storage of materials under test, as well as preparation of test specimens are described in ISO 16000-11.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 554, Standard atmospheres for conditioning and/or testing — Specifications

ISO 16000-9, Indoor air — Part 9: Determination of the emission of volatile organic compounds from building products and furnishing — Emission test chamber method

ISO 16000-11, Indoor air — Part 11: Determination of the emission of volatile organic compounds from building products and furnishing — Sampling, storage of samples and preparation of test specimens

EN 13725, Air quality — Determination of odour concentration by dynamic olfactometry

3 Terms, definitions, symbols, units and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1

odour

pleasant or unpleasant smell caused by chemical compounds emitting to indoor air from a building product or material

3.1.2

acceptability

assessment of an odour emission to indoor air which can be ascertained according to a scale ranging from "clearly acceptable" to "clearly unacceptable" set by value on a defined evaluation scale