## INTERNATIONAL STANDARD

ISO 1452-2

First edition 2009-12-01

Plastics piping systems for water supply and for buried and above-ground drainage and sewerage under pressure — Unplasticized poly(vinyl chloride) (PVC-U) —

Part 2: **Pipes** 

Systèmes de canalisations en plastique pour l'alimentation en eau, pour branchements et collecteurs d'assainissement enterrés et aériens avec pression — Poly(chlorure de vinyle) non plastifié (PVC-U) —

Partie 2: Tubes



#### PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



#### COPYRIGHT PROTECTED DOCUMENT

#### © ISO 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

### **Contents**

•		•														i	٧	
•																	V	
																	1	
																	1	
																	2	
																	3	
•																	3	
																	3	
																	3	
																	3	
																	3	
																	3	
																	3 3	
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		3	

Page

Introdu	ction	٠١
1	Scope	<i>'</i>
2	Normative references	<i>'</i>
3	Terms, deficitions, symbols and abbreviated terms	
4	Material  Pipe material  Density  MRS-value	
4.1	Pipe material	3
4.2	Density	3
4.3	MRS-value	
5	General characteristics Appearance Colour	3
5.1	Appearance	3
5.2	Colour	
5.3	Opacity of pipes intended for the above-ground conveyance of water	3
6	Geometrical characteristics	3
6.1	Measurement of dimensions	3
6.2	Nominal outside diameters	3
6.3	Mean outside diameters and their telerances	4
6.4	Wall thickness and their tolerances	5
6.5	Length of pipe	e
6.6	Pipes with sockets	7
6.7	Wall thickness and their tolerances  Length of pipe  Pipes with sockets  Pipe ends for ring seal or solvent cement joints	1
7	Classification and selection of pipes	11
7.1	Classification	11
7.2	Selection of nominal pressure and pipe series Stor water up to and including 25 °C	11
73	Determination of the allowable operating pressure for water up to 45 °C	11
	Mechanical characteristics	
8	Mechanical characteristics	11
8.1	Impact strength	11
8.2	Resistance to internal pressure	12
9	Physical characteristics	1:
10	Soaling rings	۱۰۰۰۰ ۱۰۰۰۰
10	ocaming rings	1-
11	Physical characteristics  Sealing rings  Adhesives  Performance requirements	14
12	Performance requirements	14
13	Marking	14
13.1	General	1- 1/
13.2	Minimum required marking	
13.3	Additional marking	
	· ·	
	A (normative) Allowable operating pressures	
Annex	B (normative) Imperial (inch)-sized pipes	18
Bibliog	ranhy	23

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in Maison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical control tees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires applying by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 1452-2 was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 155, *Plastics piping systems and ducting systems*, in collaboration with ISO Technical Committee ISO/TC 138, Plastics pipes, fittings and valves for transport of fluids, Subcommittee SC 2, Plastics pipes and fittings for water supplies, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This first edition cancels and replaces ISO 4422-2:1996 and ISO 2045, which have been technically revised.

ISO 1452 consists of the following parts, under the general tile Plastics piping systems for water supply and for buried and above-ground drainage and sewerage under pressure — Unplasticized poly(vinyl chloride) s Jenerated by this (PVC-U):

- Part 1: General
- Part 2: Pipes
- Part 3: Fittings
- Part 4: Valves
- Part 5: Fitness for purpose of the system

Guidance for the assessment of conformity is to form the subject of a part 7.

#### Introduction

The System Standard, of which this is Part 2, specifies the requirements for a piping system and its components made from unplasticized poly(vinyl chloride) (PVC-U). The piping system is intended to be used for water supply and for buried and above-ground drainage and sewerage under pressure.

In respect of potential adverse effects on the quality of water intended for human consumption, caused by the products covered by this part of ISO 1452, the following are relevant.

- a) This part of ISO 1452 provides no information as to whether or not the products can be used without restriction.
- b) Existing national regulations concerning the use and/or the characteristics of these products remain in force.

Requirements and test methods of material and components, other than pipes, are specified in ISO 1452-1, ISO 1452-3 and ISO 1452-4. Characteristics for fitness for purpose (mainly for joints) are established in ISO 1452-5.

This part of ISO 1452 specifies the characteristics of pipes.

Guidance for installation is given in ISO/TR 4191[1].

Guidance for assessment of conformity is provided in ENV 1452-7<sup>[2]</sup>.

© ISO 2009 – All rights reserved

Inis document is a preview denetated by EUS

# Plastics piping systems for water supply and for buried and above-ground drainage and sewerage under pressure — Unplasticized poly(vinyl chloride) (PVC-U) —

### Part 2: Pipes

#### 1 Scope

This part of ISO 1452 specifies the characteristics of solid-wall pipes made from unplasticized poly(vinyl chloride) (PVC-U) for piping systems intended for water supply and for buried and above-ground drainage and sewerage under pressure.

It also specifies the test parameters for the test methods referred to in this part of ISO 1452.

In conjunction with ISO 1452-1 and ISO 1452-5, it is applicable to extruded PVC-U pipes without a socket and pipes with a socket (integral or not), intended to be used for the following:

- a) water mains and services buried in the ground
- b) conveyance of water above ground for both outside and inside buildings;
- c) buried and above-ground drainage and sewerage under pressure.

It is applicable to piping systems intended for the supply of water under pressure up to and including 25 °C (cold water) intended for human consumption and for general surposes as well as for waste water under pressure.

This part of ISO 1452 specifies pipes for the conveyance of water are waste water up to and including 45 °C. For temperatures between 25 °C and 45 °C, Figure A.1 applies.

NOTE 1 The producer and the end-user can come to agreement on the possibilities of use for temperatures above 45 °C on a case-by-case basis.

This part of ISO 1452 specifies a range of pipe sizes and pressure classes and gives requirements concerning colours.

NOTE 2 It is the responsibility of the purchaser or specifier to make the appropriate selections from these aspects, taking into account their particular requirements and any relevant national regulations and installation practices or codes.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1167-1, Thermoplastics pipes, fittings and assemblies for the conveyance of fluids — Determination of the resistance to internal pressure — Part 1: General method

© ISO 2009 – All rights reserved

ISO 1167-2, Thermoplastics pipes, fittings and assemblies for the conveyance of fluids — Determination of the resistance to internal pressure — Part 2: Preparation of pipe test pieces

ISO 1183-1:2004, Plastics — Methods for determining the density of non-cellular plastics — Part 1: Immersion method, liquid pyknometer method and titration method

ISO 1452-1:2009, Plastics piping systems for water supply and for buried and above-ground drainage and sewerage under pressure — Unplasticized poly(vinyl chloride) (PVC U) — Part 1: General

ISO 1452-5, Plastics piping systems for water supply and for buried and above-ground drainage and sewerage under pressure— Unplasticized poly(vinyl chloride) (PVC U) — Part 5: Fitness for purpose of the system

ISO 2505, Thermoplastics pipes — Longitudinal reversion — Test method and parameters

ISO 2507-1:1995, Thermoplastics pipes and fittings — Vicat softening temperature — Part 1: General test method

ISO 3126, Plastics piping systems — Plastics components — Determination of dimensions

ISO 6259-1, Thermoplastics pipes — Decemination of tensile properties — Part 1: General test method

ISO 6259-2, Thermoplastics pipes — Determination of tensile properties — Part 2: Pipes made of unplasticized poly(vinyl chloride) (PVC-U), chlorided poly(vinyl chloride) (PVC-C) and high-impact poly(vinyl chloride) (PVC-HI)

ISO 7387-1, Adhesives with solvents for assembly of PVC-U pipe elements — Characterization — Part 1: Basic test methods

ISO 7686, Plastics pipes and fittings — Determination of opacity

ISO 9311-1, Adhesives for thermoplastic piping systems — Patri: Determination of film properties

ISO 9852, Unplasticized poly(vinyl chloride) (PVC-U) pipes ichloromethane resistance at specified temperature (DCMT) — Test method

ISO 18373-1, Rigid PVC pipes — Differential scanning calorimetry (DSC) method — Part 1: Measurement of the processing temperature

EN 681-1:1996, Elastomeric seals — Materials requirements for pipe joint seals used in water and drainage applications — Part 1: Vulcanized rubber

EN 744:1995, Plastics piping and ducting systems — Thermoplastics pipes — Test method for resistance to external blows by the round-the-clock method

#### 3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the terms, definitions, symbols and abbreviated terms given in ISO 1452-1 and the following apply:

- L length of socket
- m depth of engagement