

---

---

**Road vehicles — Local Interconnect  
Network (LIN) —**

**Part 6:  
Protocol conformance test  
specification**

*Véhicules routiers — Réseau Internet local (LIN) —*

*Partie 6: Spécification du protocole d'essai de conformité*

This document is a preview generated by EBS



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

# Contents

Page

<b>Foreword</b>	<b>vii</b>
<b>Introduction</b>	<b>viii</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Normative references</b>	<b>1</b>
<b>3 Terms, definitions, symbols and abbreviated terms</b>	<b>1</b>
3.1 Terms and definitions	1
3.2 Symbols	2
3.3 Abbreviated terms	3
<b>4 Conventions</b>	<b>4</b>
<b>5 General test specification considerations</b>	<b>4</b>
5.1 General	4
5.2 Test conditions	4
5.3 Mandatory requirements for IUT as master	4
5.4 Mandatory requirements for IUT as slave	5
5.5 Test case architecture	5
5.6 Classification	6
5.7 Test system requirements	6
5.7.1 Generation of LIN frames	6
5.7.2 Standard requirements for the test cases	6
5.7.3 Special requirements for bit timing testing	6
5.7.4 Test system for IUT as slave node	6
5.7.5 Sleep state verification for IUT as slave node	6
5.8 Test system definition	7
5.9 Global predefinitions for the test setup	7
5.9.1 Configuration of IUT and test system	7
5.9.2 Default delays for frame headers	9
5.9.3 Default bit rate	9
5.9.4 Time measurement	9
5.9.5 Default spaces between the different frame parts of a LIN message	9
<b>6 Essential test cases before test start</b>	<b>10</b>
6.1 General	10
6.2 [PT-CT 1] Diagnostic frame “master request”, IUT as slave	10
6.3 [PT-CT 2] Diagnostic frame “slave response”, IUT as slave	10
6.4 [PT-CT 3] Error in received frame, IUT as slave	10
<b>7 Timing parameters</b>	<b>11</b>
7.1 General	11
7.2 [PT-CT 4] Length of break field low phase, IUT as master	11
7.3 [PT-CT 5] Variation of length of break field low phase, IUT as slave	11
7.4 [PT-CT 6] Length of break delimiter, IUT as master	12
7.5 [PT-CT 7] Variation of length of break delimiter, IUT as slave	12
7.6 [PT-CT 8] Inconsistent break field error, IUT as slave	13
7.7 [PT-CT 9] Inconsistent sync byte field error, IUT as slave	13
7.8 [PT-CT 10] Verification of the sync byte field, IUT as master	14
7.9 [PT-CT 11] Incomplete frame reception, IUT as slave	14
7.10 [PT-CT 12] Unknown frame reception, IUT as slave	15
7.11 [PT-CT 13] Length of header, IUT as master	16
7.12 [PT-CT 14] Variation of length of header, IUT as slave	16
7.13 [PT-CT 15] Bit rate tolerance, IUT as master	17
7.14 [PT-CT 16] Bit rate tolerance, IUT as slave without making use of synchronization	17
7.15 [PT-CT 17] Bit rate tolerance, IUT as slave with making use of synchronization	18
7.16 Length of response	18
7.16.1 [PT-CT 18] Length of response, IUT as slave	18

7.16.2	[PT-CT 19] Length of response, IUT as master.....	19
7.16.3	[PT-CT 20] Acceptance of response field, IUT as slave.....	20
7.17	Verification of schedule table timing.....	21
7.17.1	[PT-CT 21] Verification of jitter, IUT as master.....	21
7.17.2	[PT-CT 22] Schedule table management, IUT as master.....	22
7.18	[PT-CT 23] Sample point test, IUT as slave.....	22
7.19	[PT-CT 24] Initialization time, IUT as slave.....	23
<b>8</b>	<b>Communication without failure.....</b>	<b>24</b>
8.1	Variation of LIN identifier.....	24
8.1.1	[PT-CT 25] Variation of LIN PID, IUT as master.....	24
8.1.2	[PT-CT 26] Variation of LIN PIDs of subscribed frames, IUT as slave.....	24
8.1.3	[PT-CT 27] Variation of LIN identifier of published frames, IUT as slave.....	25
8.2	Transmission of the checksum byte.....	25
8.2.1	[PT-CT 28] Transmission of the checksum byte “classic checksum”, IUT as slave.....	25
8.2.2	[PT-CT 29] Transmission of the checksum byte “enhanced checksum”, IUT as slave.....	26
8.2.3	[PT-CT 30] Transmission of the checksum byte “classic checksum”, IUT as master.....	26
8.2.4	[PT-CT 31] Transmission of the checksum byte of unconditional frames, IUT as master.....	26
8.3	Unused bits.....	27
8.3.1	[PT-CT 32] Unused bits, IUT as master.....	27
8.3.2	[PT-CT 33] Unused bits, IUT as slave.....	27
8.4	Reserved frame.....	28
8.4.1	[PT-CT 34] Reserved frame, IUT as slave.....	28
8.5	[PT-CT 35] Diagnostic frame master request, IUT as master.....	28
8.6	Supported frames according to the IUT specification.....	29
8.6.1	[PT-CT 36] Supported Tx frames according to the IUT specification, IUT as slave.....	29
8.6.2	[PT-CT 37] Supported Rx frames according to the IUT specification, IUT as slave.....	29
<b>9</b>	<b>Communication with failure.....</b>	<b>30</b>
9.1	General.....	30
9.2	[PT-CT 38] Bit error, IUT as slave.....	30
9.3	[PT-CT 39] Framing error in header of published frame, IUT as slave.....	31
9.4	[PT-CT 40] Framing error in response field of subscribed frame, IUT as slave.....	32
9.5	[PT-CT 41] Checksum error by inversion, IUT as slave.....	32
9.6	[PT-CT 42] Checksum error by carry, IUT as slave.....	32
9.7	[PT-CT 43] Communication robustness, IUT as slave.....	33
<b>10</b>	<b>Event triggered frames.....</b>	<b>33</b>
10.1	General.....	33
10.2	[PT-CT 44] Event triggered frame, IUT as slave.....	33
10.3	Event triggered frame with collision.....	34
10.3.1	[PT-CT 45] Event triggered frame with collision resolving, IUT as slave.....	34
10.3.2	[PT-CT 46] Event triggered frame with errors in collision resolving, IUT as slave.....	34
10.3.3	[PT-CT 47] Event triggered frame with collision resolving, IUT as master.....	35
10.3.4	[PT-CT 48] Error in transmitted frame with collision, IUT as slave.....	35
<b>11</b>	<b>Status management.....</b>	<b>36</b>
11.1	[PT-CT 49] Error in received frame, IUT as slave.....	36
11.2	[PT-CT 50] Error in transmitted frame, IUT as slave.....	36
11.3	[PT-CT 51] response_error signal handling, IUT as slave.....	37
<b>12</b>	<b>Sleep/wake up/power mode tests.....</b>	<b>37</b>
12.1	[PT-CT 52] Send “go-to-sleep command”, IUT as master.....	37
12.2	[PT-CT 53] Receive “go-to-sleep command”, IUT as slave.....	38
12.3	[PT-CT 54] Receive a wake up signal, IUT as master.....	39

12.4	[PT-CT 55] Receive a wake up signal, IUT as slave.....	39
12.5	Send a wake up signal.....	40
12.5.1	[PT-CT 56] Send a wake up signal, IUT as master and IUT as slave.....	40
12.5.2	[PT-CT 57] Send a block of wake up signals, IUT as slave.....	40
12.5.3	[PT-CT 58] Wait after one block of wake up signals, IUT as slave.....	41
12.5.4	[PT-CT 59] Send a wake up signal, frame header from a master following, IUT as slave.....	41
12.6	[PT-CT 60] ECU power loss, IUT as master.....	42
12.7	[PT-CT 61] Powered up with LIN shorted, IUT as master.....	43
12.8	[PT-CT 62] LIN shorted before scheduling, IUT as master.....	43
12.9	[PT-CT 63] LIN shorted after start of scheduling, IUT as master.....	44
<b>13</b>	<b>Sleep state after bus idle.....</b>	<b>44</b>
13.1	[PT-CT 64] Sleep state after event and bus idle, IUT as slave.....	44
13.2	[PT-CT 65] Sleep state after bus idle with power up and wake up signal, IUT as slave.....	45
13.3	[PT-CT 66] Timeout after bus idle, IUT as slave.....	46
<b>14</b>	<b>Frame ID range assignment.....</b>	<b>46</b>
14.1	[PT-CT 67] Frame ID range assignment with indirect response, IUT as slave.....	46
14.2	[PT-CT 68] Frame ID range unassignment with indirect response, IUT as slave.....	47
<b>15</b>	<b>Wildcards.....</b>	<b>48</b>
15.1	[PT-CT 69] Request with direct response, IUT as slave.....	48
<b>16</b>	<b>ReadByIdentifier command.....</b>	<b>48</b>
16.1	LIN product identification.....	48
16.1.1	[PT-CT 70] LIN product identification request with direct response, IUT as slave.....	48
16.1.2	[PT-CT 71] LIN product identification — With interleaved unconditional frame, IUT as slave.....	49
16.2	[PT-CT 72] ReadByIdentifier command with correct NAD, IUT as slave.....	49
16.3	[PT-CT 73] ReadByIdentifier command with incorrect addressing, IUT as slave.....	50
<b>17</b>	<b>NAD assignment.....</b>	<b>51</b>
17.1	General.....	51
17.2	[PT-CT 74] NAD assignment — Followed by ReadByIdentifier service, IUT as slave.....	51
17.3	[PT-CT 75] NAD assignment — With positive response, IUT as slave.....	51
17.4	[PT-CT 76] NAD assignment — Initial NAD, IUT as slave.....	51
<b>18</b>	<b>Save Configuration.....</b>	<b>52</b>
18.1	General.....	52
18.2	[PT-CT 77] Save Configuration — With positive response, IUT as slave.....	52
18.3	[PT-CT 78] Save Configuration — Save a new NAD, IUT as slave.....	52
18.4	[PT-CT 79] Save Configuration — Save new frame identifiers, IUT as slave.....	53
<b>19</b>	<b>Transport protocol.....</b>	<b>54</b>
19.1	[PT-CT 80] Transport layer functional request, IUT as slave.....	54
19.2	[PT-CT 81] Abort diagnostic communication with new diagnostic request, IUT as slave.....	54
19.3	[PT-CT 82] IUT receives a segmented request as specified, IUT as slave.....	54
19.4	[PT-CT 83] IUT receives a segmented request interleaved with unconditional frame, IUT as slave.....	55
19.5	[PT-CT 84] IUT receives a segmented request with interleaved functional request, IUT as slave.....	56
19.6	IUT shall ignore request after timeout.....	57
19.6.1	[PT-CT 85] IUT shall ignore segmented requests on N_Cr <sub>Max</sub> timeout, IUT as slave.....	57
19.6.2	[PT-CT 86] IUT shall observe transport layer N_As <sub>Max</sub> timeout, IUT as slave.....	58
19.7	[PT-CT 87] IUT shall ignore segmented requests with wrong sequence numbering, IUT as slave.....	59
19.8	[PT-CT 88] IUT shall respond with correct segmented response, IUT as slave.....	60
19.9	IUT sends a segmented response with interleaved unconditional frames.....	61

19.9.1	[PT-CT 89] IUT sends a segmented response with interleaved unconditional frame, IUT as slave.....	61
19.9.2	[PT-CT 90] IUT sends a segmented response with interleaved functional request, IUT as slave.....	62
19.10	[PT-CT 91] IUT shall not respond to slave response header if there is no request before, IUT as slave.....	63
19.11	[PT-CT 92] IUT shall not respond to slave response header if the response is already sent, IUT as slave.....	63
19.12	[PT-CT 93] IUT shall abort segmented response on N_CsMax timeout, IUT as slave.....	64
<b>Bibliography</b> .....		<b>66</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*.

A list of all parts in the ISO 17987 series can be found on the ISO website.

## Introduction

ISO 17987 (all parts) specifies the use cases, the communication protocol and physical layer requirements of an in-vehicle communication network called Local Interconnect Network (LIN).

The LIN protocol as proposed is an automotive focused low speed universal asynchronous receiver transmitter (UART) based network. Some of the key characteristics of the LIN protocol are signal based communication, schedule table based frame transfer, master/slave communication with error detection, node configuration and diagnostic service transportation.

The LIN protocol is for low cost automotive control applications, for example, door module and air condition systems. It serves as a communication infrastructure for low-speed control applications in vehicles by providing:

- signal based communication to exchange information between applications in different nodes;
- bit rate support from 1 kbit/s to 20 kbit/s;
- deterministic schedule table based frame communication;
- network management that wakes up and puts the LIN cluster into sleep state in a controlled manner;
- status management that provides error handling and error signalling;
- transport layer that allows large amount of data to be transported (such as diagnostic services);
- specification of how to handle diagnostic services;
- electrical physical layer specifications;
- node description language describing properties of slave nodes;
- network description file describing behaviour of communication;
- application programmer's interface.

ISO 17987 (all parts) is based on the open systems interconnection (OSI) basic reference model as specified in ISO/IEC 7498-1 which structures communication systems into seven layers.

The OSI model structures data communication into seven layers called (top down) *application layer* (layer 7), *presentation layer*, *session layer*, *transport layer*, *network layer*, *data link layer* and *physical layer* (layer 1). A subset of these layers is used in ISO 17987 (all parts).

ISO 17987 (all parts) distinguishes between the services provided by a layer to the layer above it and the protocol used by the layer to send a message between the peer entities of that layer. The reason for this distinction is to make the services, especially the application layer services and the transport layer services, reusable also for other types of networks than LIN. In this way, the protocol is hidden from the service user and it is possible to change the protocol if special system requirements demand it.

ISO 17987 (all parts) provides all documents and references required to support the implementation of the requirements related to the following.

- ISO 17987-1: This part provides an overview of ISO 17987 (all parts) and structure along with the use case definitions and a common set of resources (definitions, references) for use by all subsequent parts.
- ISO 17987-2: This part specifies the requirements related to the transport protocol and the network layer requirements to transport the PDU of a message between LIN nodes.
- ISO 17987-3: This part specifies the requirements for implementations of the LIN protocol on the logical level of abstraction. Hardware related properties are hidden in the defined constraints.

- ISO 17987-4: This part specifies the requirements for implementations of active hardware components which are necessary to interconnect the protocol implementation.
- ISO 17987-5: This part specifies the LIN application programmers interface (API) and the node configuration and identification services. The node configuration and identification services are specified in the API and define how a slave node is configured and how a slave node uses the identification service.
- ISO 17987-6: This part specifies tests to check the conformance of the LIN protocol implementation according to ISO 17987-2 and ISO 17987-3. This comprises tests for the data link layer, the network layer and the transport layer.
- ISO 17987-7: This part specifies tests to check the conformance of the LIN electrical physical layer implementation (logical level of abstraction) according to ISO 17987-4.



# Road vehicles — Local Interconnect Network (LIN) —

## Part 6: Protocol conformance test specification

### 1 Scope

This document specifies the LIN protocol conformance test. This test verifies the conformance of LIN communication controllers with respect to ISO 17987-2 and ISO 17987-3.

This document provides all necessary technical information to ensure that test results are identical even on different test systems, provided that the particular test suite and the test system are compliant to the content of this document.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 17987-2:2016, *Road vehicles — Local Interconnect Network (LIN) — Part 2: Transport protocol and network layer services*

ISO 17987-3:2016, *Road vehicles — Local Interconnect Network (LIN) — Part 3: Protocol specification*

ISO 17987-4:2016, *Road vehicles — Local Interconnect Network (LIN) — Part 4: Electrical Physical Layer (EPL) specification 12V/24V*

### 3 Terms, definitions, symbols and abbreviated terms

#### 3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

##### 3.1.1

##### **class B device**

µC-based LIN device

Note 1 to entry: These are devices where it is possible to take measurements on the Rx and Tx interface circuits between the µC and the transceiver.

##### 3.1.2

##### **class C device**

integrated LIN devices (ECU) with µC and transceiver

Note 1 to entry: These are devices where it is not possible to take measurements on the Rx and Tx interface circuits between the µC and the transceiver.