

IEC TS 62607-6-4

Edition 1.0 2016-09

TECHNICAL SPECIFICATION



Nanomanufacturing – Key control characteristics – Part 6-4: Graphene – Surface conductance measurement using resonant cavity



THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office	Tel.: +41 22 919 02 11
3, rue de Varembé	Fax: +41 22 919 03 00
CH-1211 Geneva 20	info@iec.ch
Switzerland	www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.





Edition 1.0 2016-09

TECHNICAL SPECIFICATION

inon:



Nanomanufacturing – Key control characteristics – Part 6-4: Graphene – Surface conductance measurement using resonant cavity

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 07.030

ISBN 978-2-8322-3667-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREW	ORD	3
INTROD	UCTION	5
1 Scc	pe	6
2 Nor	mative references	6
3 Ter	ms and definitions	6
3.1	Graphene lavers	6
3.2	Measurement terminology	8
4 Mic	rowave cavity test fixture	9
5 Tes	t specimen	10
6 Mea	asurement procedure	10
6.1	Apparatus	10
6.2	Calibration	11
6.3	Measurements	11
6.3	1 General	11
6.3	2 Empty cavity	11
6.3	3 Specimen	11
6.3	4 Repeated procedure	12
6.3	5 Substrate	12
7 Cal	culations of surface conductance	12
8 Rep	port	12
9 Acc	uracy consideration	13
Annex A layer an	(informative) Case study of surface conductance measurement of single- d few-layer graphene	14
A.1	General	14
A.2	Cavity perturbation procedure	14
A.3	Experimental procedure	15
A.4	Results	15
A.5	Surface conductance of single-layer graphene and few-layer graphene	16
A.6	Summary	17
Bibliogra	aphy	18

Figure 1 – Microwave cavity test fixture	10
Figure A.1 – S ₂₁ magnitude of the resonant peak TE ₁₀₃ as a function of frequency at several specimen insertions (h_x)	16
Figure A.2 – Plots of $1/Q_x - 1/Q_0$ as a function of the normalized specimen area (wh_x)	16
	5

INTERNATIONAL ELECTROTECHNICAL COMMISSION

NANOMANUFACTURING – KEY CONTROL CHARACTERISTICS –

Part 6-4: Graphene – Surface conductance measurement using resonant cavity

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committee; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a Technical Specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical Specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62607-6-4, which is a Technical Specification, has been prepared by IEC technical committee 113: Nanotechnology for electrotechnical products and systems.

The text of this Technical Specification is based on the following documents:

Enquiry draft	Report on voting
113/295/DTS	113/324/RVC

Full information on the voting for the approval of this Technical Specification can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62607 series, published under the general title *Nanomanufacturing – Key control characteristics*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- transformed into an International Standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The microwave resonant cavity test method for surface conductance is non-contact, fast, sensitive and accurate. It is well suited for standards, research and development (R&D), and for quality control in the manufacturing of two-dimensional (2D) nano-carbon materials. These sheet-like or flake-like carbon forms can be assembled into atomically-thin monolayer or multilayer graphene materials, which can be stacked, folded, crumpled or pillared into a variety of nano-carbon architectures with the lateral dimension limited to a few tenths of a nanometre. Many of these materials are new and exhibit extraordinary physical and electrical properties such as optical transparency, anisotropic heat diffusivity and charge transport that are of significant interest to science, technology and commercial applications [1, 2]¹.

Depending on particular morphologies, density of states and structural perfection, the surface conductance of these materials may vary from 1 S to about 10^{-4} S. Conventional direct current (DC) surface conductance measurement techniques require a complex test vehicle and interconnections for making electrical contacts, which affect and alter the measurement, making it difficult to decouple the intrinsic properties of the material.

In comparison, the resonant cavity measurement method is fast and non-contact. Thus, it is well suited for use in R&D and manufacturing environments where the surface conductance is a critical functional parameter. Moreover, it can be employed to measure electrical characteristics of other nano-size structures.

¹ Numbers in square brackets refer to the Bibliography

NANOMANUFACTURING – KEY CONTROL CHARACTERISTICS –

Part 6-4: Graphene – Surface conductance measurement using resonant cavity

1 Scope

This part of IEC 62607 establishes a method for determining the surface conductance of twodimensional (2D) single-layer or multi-layer atomically thin nano-carbon graphene structures. These are synthesized by chemical vapour deposition (CVD), epitaxial growth on silicon carbide (SiC), obtained from reduced graphene oxide (rGO) or mechanically exfoliated from graphite [3]. The measurements are made in an air filled standard R100 rectangular waveguide configuration, at one of the resonant frequency modes, typically at 7 GHz [4].

Surface conductance measurement by resonant cavity involves monitoring the resonant frequency shift and change in the quality factor before and after insertion of the specimen into the cavity in a quantitative correlation with the specimen surface area. This measurement does not explicitly depend on the thickness of the nano-carbon layer. The thickness of the specimen does not need to be known, but it is assumed that the lateral dimension is uniform over the specimen area.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60153-2, Hollow metallic waveguides – Part 2: Relevant specifications for ordinary rectangular waveguides

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60153-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1 Graphene layers

3.1.1 graphene single-layer graphene 1LG single layer of carbon atoms with sp²-electronic hybridization bound to three neighbours in a honeycomb structure

Note 1 to entry: It is an important building block of many carbon nano-objects.