INTERNATIONAL STANDARD

ISO 16610-31

First edition 2016-11-15

Geometrical product specifications (GPS) — Filtration —

Part 31:

Robust profile filters: Gaussian regression filters

Spécification géométrique des produits (GPS) — Filtrage — Partie 31: Filtres de profil robustes: Filtres de régression gaussiens





© ISO 2016, Published in Switzerland

"roduced or utilized '
te internet or an
or ISO's memi All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

COI	ntents	Page
Fore	eword	iv
Intro	oduction	v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Robust Gaussian regression filter 4.1 Weighting function 4.2 Filter equation 4.2.1 General 4.2.2 Filter equation for the robust Gaussian regression filter for open profiles 4.2.3 Filter equation for robust Gaussian regression filter for closed profiles 4.2.4 Transmission characteristics	2 2 2 5
5	Recommendations for nesting index (cutoff values λ_c)	
6	Filter designation	
	ex A (informative) Examples	
	ex B (informative) Relationship to the filtration matrix model	
	ex C (informative) Relationship to the GPS matrix model iography	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 213, *Dimensional and geometrical product specifications and verification*.

This first edition of ISO 16610-31 cancels and replaces ISO/TS 16610-31, which has been technically revised.

A list of all parts in the ISO 16610 series can be found on the ISO website.

Introduction

This document is a geometrical product specification (GPS) standard and is to be regarded as a general GPS standard (see ISO 14638). It influences the chain link C of all chains of standards.

For more detailed information of the relation of this document to the GPS matrix model, see Annex C.

The ISO/GPS matrix model given in ISO 14638 gives an overview of the ISO/GPS system of which this document is a part. The fundamental rules of ISO/GPS given in ISO 8015 apply to this document and the default decision rules given in ISO 14253-1 apply to specifications made in accordance with this document, unless otherwise indicated.

This document develops the concept of the discrete robust Gaussian regression filter. The robust process reduces the influence of the deep valleys and high peaks. The subject of this document is the filte al strat. robust Gaussian regression filter of degree p = 2, which has very good robust behaviour and form approximation for functional stratified engineering surfaces.

This document is a previous generated by tills

Geometrical product specifications (GPS) — Filtration —

Part 31:

Robust profile filters: Gaussian regression filters

1 Scope

This document specifies the characteristics of the discrete robust Gaussian regression filter for the evaluation of surface profiles with spike discontinuities such as deep valleys and high peaks.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 16610-1:2015, Geometrical product specifications (GPS) — Filtration — Part 1: Overview and basic concepts

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC Guide 99, ISO 16610-1, ISO 16610-20, ISO 16610-30 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1

robust filter

filter that is insensitive to output data against specific phenomena in the input data

3.2

regression filter

M-estimator based on the local polynomial modelling of the profile

3.3

robust Gaussian regression filter

regression filter (3.2) based on the Gaussian weighting function and a biweight influence function (3.4)

3.4

biweight influence function

asymmetric function which is scale-invariant, expressed by

$$\psi(x) = \begin{cases} x \times \left(1 - \left(\frac{x}{c}\right)^2\right)^2 & \text{for} & |x| \le c \\ 0 & \text{for} & |x| > c \end{cases}$$

where *c* is the scale parameter.