

Edition 3.0 2016-10

INTERNATIONAL STANDARD

Fixed inductors for use in electronic and telecommunication equipment – Marking codes



THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office Tel.: +41 22 919 02 11 3, rue de Varembé Fax: +41 22 919 03 00

CH-1211 Geneva 20 info@iec.ch Switzerland www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.



Edition 3.0 2016-10

INTERNATIONAL

nic and Fixed inductors for use in electronic and telecommunication equipment – **Marking codes**

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.100.10

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

F	OREWO)RD	3
1	Scop	e	5
2	Norm	native references	5
3	Colo	ur code for fixed inductors	5
	3.1	General rules	5
	3.2	Examples of colour code for fixed inductors	3
4	Digit	and letter code for inductance values	7
	4.1	General rules	7
	4.2	Examples of digit and letter code for inductance values	3
5	Lette	r code for tolerances of inductance values)
	5.1	Symmetrical tolerances)
	5.2	Other tolerances	
6	Date	code system for fixed inductors	
	6.1	Single-character code for year and month	
	6.2	Two-character code for year and month	
	6.3	Four-character code for year and week	
	• .	phy12	
Fi	gure 1 -	- Example for 47 μH ± 10 %6	3
Fi	gure 2 -	- Example for 4,7 μH ± 2 %	7
Fi	gure 3 –	- Example for 4,7 nH ± 5 %	7
		- Example for 47 μH ± 10 %	
Ta	able 1 –	Values corresponding to colours	3
Ta	able 2 –	Cardinal numbers for the multiplier	7
Ta	able 3 –	Examples of digit and letter code for inductance values	3
Ta	able 4 –	Letter code for symmetrical tolerance)
		Single-character code for year and month for a four-year cycle10	
		Code letter for year in a twenty-year cycle10	
		Character code letter for month	
		(1)	ı

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIXED INDUCTORS FOR USE IN ELECTRONIC AND TELECOMMUNICATION EQUIPMENT – MARKING CODES

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61605 has been prepared by IEC technical committee 51: Magnetic components and ferrite materials.

This third edition cancels and replaces the second edition published in 2005. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) The date code system for fixed inductors has been updated.

The text of this standard is based on the following documents:

CDV	Report on voting
51/1135/CDV	51/1147/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

as decided that the content.

dictation. At this date, the publica.

med,

www.

select by a revised edition, or

mender.

billingual vason of this publication may be issued at a later de.

FIXED INDUCTORS FOR USE IN ELECTRONIC AND TELECOMMUNICATION EQUIPMENT – MARKING CODES

1 Scope

This document specifies marking codes for fixed inductors.

The colour code specified in Clause 3 gives a colour coding for fixed inductors. It is intended for use with the values of the E3 to E24 series as specified in IEC 60063.

The code specified in Clause 4 gives a system for marking inductance values by means of digits and letters.

The code specified in Clause 5 gives a system for marking the tolerance on inductance values by means of letters.

The code specified in Clause 6 gives a system for marking of date codes on fixed inductors by means of letters and digits.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8601, Data elements and interchange formats – Information interchange – Representation of dates and times

3 Colour code for fixed inductors

3.1 General rules

Colour codes for fixed inductors should be expressed in "bands". If other shapes than bands are applied, the relevant specification shall prescribe their configuration, placement and identification.

Colour codes for fixed inductors shall consist of four bands. The first three bands shall indicate inductance values and the last band shall indicate tolerances.

Inductance values shall be expressed by two significant figures and another figure expressing multipliers.

Colour corresponding to significant figures, multipliers and tolerances shall be as given in Table 1.

The first two bands represent significant figures and the third band specifies the multiplier. The basic unit for the inductance value shall be expressed in μH . The first band shall be the one nearest to the end of the inductor and the bands shall be so placed and spaced that there can be no confusion in reading the coding.

Any additional coding on fixed inductors shall be applied in such a way as not to confuse the coding for value and tolerance.