
**Geometrical product specifications
(GPS) — Dimensional tolerancing —**

**Part 3:
Angular sizes**

*Spécification géométrique des produits (GPS) — Tolérancement
dimensionnel —*

Partie 3: Tailles angulaires



This document is a preview generated by EBS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	2
3 Terms and definitions	2
4 Specification modifiers and symbols	11
5 Default specification operator for angular size	13
5.1 General	13
5.2 ISO default specification operator for angular size	14
5.3 Drawing-specific default specification operator for angular size	15
6 Drawing indication	16
6.1 Drawing indication for special specification operators for angular size	16
6.2 Indication of the toleranced feature on which the angular size characteristic is defined ..	17
Annex A (normative) Association criteria for two-line angular size (for a revolute or prismatic feature of size)	18
Annex B (informative) Differences between two planes considered as an angular feature of size and two planes considered as two single features	19
Annex C (informative) Overview diagram for angular size	20
Annex D (informative) Relation to ISO GPS matrix	21
Bibliography	22

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is Technical Committee ISO/TC 213, *Dimensional and geometrical product specifications and verification*.

ISO 14405 consists of the following parts, under the general title *Geometrical product specification (GPS) — Dimensional tolerancing*:

- Part 1: Linear sizes
- Part 2: Dimensions other than linear sizes
- Part 3: Angular sizes

Introduction

This part of ISO 14405 is a geometrical product specification (GPS) standard and is to be regarded as a general GPS standard (see ISO 14638). In the general GPS matrix, it influences chain links “Symbols and indications”, “Feature requirements” and “Feature properties” of the size chain of standards.

The ISO/GPS Masterplan given in ISO 14638 gives an overview of the ISO/GPS system of which this part of ISO 14405 is a part. The fundamental rules of ISO/GPS given in ISO 8015 apply to this part of ISO 14405 and the default decision rules given in ISO 14253-1 apply to specifications made in accordance with this part of ISO 14405, unless otherwise indicated.

For more detailed information on the relation of this part of ISO 14405 to other standards and to the GPS matrix model, see [Annex D](#).

Geometrical product specifications (GPS) — Dimensional tolerancing —

Part 3: Angular sizes

1 Scope

This part of ISO 14405 establishes the default specification operator for angular size and defines a number of special specification operators for features of angular size: cone (truncated, i.e. frustum, or not), wedge (truncated or not), two opposite straight lines (intersection of a wedge/truncated wedge and a plane perpendicular to the intersection straight line of the two planes of the wedge/truncated wedge, intersection of a cone/frustum and a plane containing the axis of revolution of the cone/frustum). See [Figure 1](#) and [Figure 2](#).

This part of ISO 14405 also defines the specification modifiers and the drawing indications for these angular sizes.

This part of ISO 14405 covers the following angular sizes:

- local angular size:
 - angular size between two lines;
 - portion angular size;
- global angular size:
 - direct global angular size:
 - least squares angular size;
 - minimax angular size;
 - rank order angular size/indirect global angular size:
 - maximum angular size;
 - minimum angular size;
 - average angular size;
 - range of angular sizes;
 - mid-range angular size;
 - median angular size;
 - standard deviation of angular size.

This part of ISO 14405 defines the meaning of tolerances of angular sizes indicated as

- + and/or - limit deviations, e.g. $0^\circ/-0,5^\circ$, or
- indicated with upper limit of size (ULS) and/or lower limit of size (LLS), e.g. 35° max. or 15° min., $34^\circ/36^\circ$,

— with or without modifiers.

This part of ISO 14405 provides a set of tools to express several types of angular size characteristics. It does not give any information on the relationship between a function or a use and an angular size characteristic.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8015, *Geometrical product specifications (GPS) — Fundamentals — Concepts, principles and rules*

ISO 17450-1, *Geometrical product specifications (GPS) — General concepts — Part 1: Model for geometrical specification and verification*

ISO 17450-2, *Geometrical product specifications (GPS) — General concepts — Part 2: Basic tenets, specifications, operators, uncertainties and ambiguities*

ISO 17450-3, *Geometrical product specification (GPS) — General concepts — Part 3: Toleranced Features*

ISO 14405-1:2016, *Geometrical product specifications (GPS) — Dimensional tolerancing — Part 1: Linear sizes*

ISO 14405-2, *Geometrical product specifications (GPS) — Dimensional tolerancing — Part 2: Dimensions other than linear sizes*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8015, ISO 17450-1, ISO 17450-2, ISO 17450-3, ISO 14405-1, ISO 14405-2 and the following apply.

For association criteria, it is assumed that the terms “least squares” and “Gaussian” are equivalent, as well as “minimax” and “Chebyshev”. In this document, the terms “least squares” and “minimax” are retained. The least squares criterion is understood without material constraint throughout this part of ISO 14405.

3.1

angular size

angular dimension of a cone or between two coplanar opposite straight lines or between two opposite non parallel planes

Note 1 to entry: The angular size is defined from nominal features or from associated features which are angular features of size.

Note 2 to entry: See example of angular size on [Figure 1](#) and [Figure 2](#).

Note 3 to entry: Definition of “angular feature of size (feature of angular size)” is given in ISO 17450-1, the angle dimension cannot be 0° or 180°.

Note 4 to entry: Angular features of size are of two types.

- Revolute angular feature of size: a cone or a frustum. Two opposite straight lines are established from a longitudinal section of a cone/frustum with a plane containing the associated axis of revolution of the cone/frustum.
- Prismatic angular feature of size: a wedge (truncated or not). Two opposite straight lines are established from a cross section of a wedge/truncated wedge with a plane perpendicular to the intersection straight line of the two associated planes of the wedge/truncated wedge.