
INTERNATIONAL STANDARD



2500

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

iso Amyl ethyl ketone for industrial use — List of methods of test

Isoamyl-éthyl-cétone à usage industriel — Liste des méthodes d'essais

First edition — 1974-04-01

UDC 661.727 : 543

Ref. No. ISO 2500-1974 (E)

Descriptors : ketones, *iso*amyl-ethyl-ketone, tests, nomenclature.

Price based on 2 pages

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 2500 was drawn up by Technical Committee ISO/TC 47, *Chemistry*, and circulated to the Member Bodies in September 1971.

It has been approved by the Member Bodies of the following countries :

Austria	Ireland	Spain
Belgium	Israel	Switzerland
Egypt, Arab Rep. of	Netherlands	Thailand
France	New Zealand*	United Kingdom
Germany	Poland	U.S.A.
Hungary	Romania	U.S.S.R.
India	South Africa, Rep. of	

* Disapproved clause 4.

No Member Body expressed disapproval of the document.

*iso*Amyl ethyl ketone for industrial use — List of methods of test

1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies methods of test for *iso*amyl ethyl ketone (5-methylheptan-3-one) $[\text{CH}_3\text{CH}_2\text{CH}(\text{CH}_3)\text{CH}_2\text{COCH}_2\text{CH}_3]$ for industrial use.

2 REFERENCES

ISO/R 758, *Method for the determination of the density of liquids at 20 °C*.

ISO/R 759, *Method for the determination of residue on evaporation on a water bath*.

ISO/R 760, *Determination of water by the Karl Fischer method*.

ISO/R 918, *Test method for distillation (distillation yield and distillation range)*.

ISO 2211, *Liquid chemical products for industrial use — Measurement of colour in Hazen units (platinum-cobalt scale)*.

ISO 2501, *Methyl ethyl ketone, isobutyl methyl ketone and isoamyl ethyl ketone for industrial use — Determination of alcoholic impurities — Volumetric method*.

ISO 2887, *secButyl alcohol, methyl ethyl ketone, isobutyl methyl ketone, isoamyl ethyl ketone, diacetone alcohol and hexylene glycol for industrial use — Determination of acidity to phenolphthalein — Volumetric method*.

3 SAMPLING

Follow the principles given in ISO ...¹⁾. Attention is drawn to the following recommendation: place the laboratory sample, representative of the material taken from the bulk, in a clean, dry, dark coloured, glass-stoppered bottle of such a size that it is nearly filled by the sample.

If it is necessary to seal this bottle, care shall be taken to avoid the risk of contamination.

4 DETERMINATION OF DISTILLATION CHARACTERISTICS

Use the method specified in ISO/R 918, subject to the following modifications appropriate for *iso*amyl ethyl ketone.

4.1 Thermometer (See 3.2 in ISO/R 918)

Use a thermometer conforming to the requirements of ISO/R 918, with a scale including the range 150 to 200 °C or any other suitable range.

4.2 Distillation (See 6.1 in ISO/R 918)

The interval before the first drop of distillate falls from the end of the condenser shall be 10 to 15 min.

4.3 Correction to be applied to the temperatures (See 7.2 in ISO/R 918)

The correction is equal to

$$0,05 (760 - p_1) ^\circ\text{C} \\ \text{or } 0,04 (1\,013 - p_2) ^\circ\text{C}$$

where

p_1 is the barometric pressure in millimetres of mercury;

p_2 is the barometric pressure in kilopascals²⁾.

5 DETERMINATION OF DENSITY AT 20 °C

Use the method specified in ISO/R 758.

1) In preparation.

2) 1 kPa = 1 kN/m².