

International Standard



2631/3

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Evaluation of human exposure to whole-body vibration — Part 3 : Evaluation of exposure to whole-body z -axis vertical vibration in the frequency range 0,1 to 0,63 Hz

Estimation de l'exposition des individus à des vibrations globales du corps — Partie 3 : Estimation de l'exposition des individus à des vibrations globales verticales du corps dans la gamme de fréquences de 0,1 à 0,63 Hz suivant l'axe des z

First edition — 1985-05-01

UDC 534.1 : 614.872.5

Ref. No. ISO 2631/3-1985 (E)

Descriptors : humans, human body, exposure, vibration, ergonomics.

Price based on 4 pages

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 2631/3 was prepared by Technical Committee ISO/TC 108, *Mechanical vibration and shock*, and is an editorially amended version of Addendum 2-1982 to ISO 2631-1978, the latter having been republished as ISO 2631/1.

Evaluation of human exposure to whole-body vibration — Part 3 : Evaluation of exposure to whole-body z -axis vertical vibration in the frequency range 0,1 to 0,63 Hz

0 Introduction

ISO 2631/1 covers vibration in the frequency range 1 to 80 Hz only, although referring to the "special problem in the frequency range below 1 Hz associated with symptoms such as motion sickness". Appreciable vibration in this frequency range occurs in many forms of transport. It causes undesirable effects ranging from discomfort to acute distress due to motion sickness and allied symptoms and interference with activity due to sickness and/or the fluctuating inertial forces it produces in the body.

In some forms of transport at least, it is possible to minimize these unwanted motions by passive or active suspension and control systems, pitch and roll stabilizers, etc., but until recently little or no well-founded guidance existed to help designers optimize such systems. This is probably due firstly to the complexity of the problem, human reaction in this frequency region being extremely variable and depending on factors other than the motion itself, such as vision, odours, age, sex, etc. Secondly there is a surprising lack of worthwhile data from laboratory and field studies which clearly link human reaction with motion input.

The following suggestions for desirable boundaries of vibration below 1 Hz are based on critical surveys and analyses of laboratory and field studies.

The object of these recommendations is firstly to give some design guidance and secondly to stimulate research in this important, neglected area of human response to vibration. Some of the gaps in knowledge have been referred to in this part of ISO 2631, particularly in 3.1.2.

For brevity and clarity of presentation, many of the clauses in ISO 2631/1 which are relevant in principle to vibration below 1 Hz have not been repeated.

1 Scope and field of application

This part of ISO 2631 covers vibration transmitted to the body in the frequency range 0,1 to 0,63 Hz. This part of ISO 2631 applies especially to discrete-frequency and narrow-band vibration and provisionally to random or non-periodic vibrations within the specified frequency range.

The boundaries defined in detail in 3.1 are intended to minimize the severe discomfort associated with motion sickness and allied symptoms. The "severe discomfort" boundary has some similarity to, but is not an extension of, the "exposure limit"

(see 4.1.2 in ISO 2631/1) which is intended to protect against pain and permanent injury rather than temporary incapacity.

Because of lack of data, it is not possible to recommend an extension of the fatigue-decreased proficiency boundary below 1 Hz, but suggestions are made on the unwanted effects on activity due to inertial loading. Reference is also made by a "reduced comfort" boundary in 3.3.

Lack of data also confines the recommendations specifically to z -axis vibration only, applied to unadapted sitting or standing fit young men. Tentative factors are suggested for some of the important variables outside these constraints (see 3.1.2).

The existence of measured level exceeding the boundaries contained in this part of ISO 2631 should not be construed as implying that undesirable effects occur or will occur in random vibration environments where experience shows otherwise.

2 Reference

ISO 2631/1, *Evaluation of human exposure to whole-body vibration — Part 1 : General requirements.*

3 Vibration evaluation

3.1 Severe discomfort boundary

3.1.1 The severe discomfort boundary as a function of frequency and exposure time is shown in the table and the figure for exposure times of 30 min, 2 h and, tentatively, 8 h. With some support from the data used, the acceleration a of the boundary as a function of the exposure time t , follows the relationship $a^2t = \text{constant}$. This relationship should be used if interpolation or summation of a varying acceleration time history is required.

NOTE — The term "severe discomfort" (or "malaise") is used in this part of ISO 2631 to characterize the broad spectrum of motion sickness symptoms occurring successively in order of increasing severity or progressing from pallor and dizziness through nausea to vomiting and complete disability. These symptoms vary from subject to subject in severity and duration and change for the same subject depending on circumstances and habitation.

If accelerations or durations beyond those shown in the figure are exceeded, a significant proportion of inexperienced, that is unadapted, seated or standing men in normal health, will experience severe discomfort and temporary disability. (About