INTERNATIONAL STANDARD

Third edition 2017-02

k Hy lo F Earth-moving machinery — Hydraulic excavator and backhoe loader lowering control device — **Requirements and tests**

err pelles des d'essa Engins de terrassement — Dispositif de contrôle d'abaissement de la flèche des pelles et chargeuses-pelleteuses hydrauliques — Exigences et méthodes d'essai



Reference number ISO 8643:2017(E)



© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Page

Contents

Fore	word			iv
Intro	ductio	n		v
1	Scop	е		
2	Norm	Normative references Terms and definitions		
3	Term			
4	Lowering control device requirements			2
5	Test method			4
	5.1 5.2 5.3	Appar Prepa Testin 5.3.1 5.3.2 5.3.3 5.3.4 5.3.5 5.3.6	atus ration for test g of lowering control device General Testing of internal leakage Testing of holding position Testing during raising Testing during lowering Testing of equalizing lines or signal lines	4 4 7 7 9 9 9 9 9 9 9 9 9
Bibli	ograph	y		
				Š

Bibliography..

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: <u>www.iso.org/iso/foreword.html</u>.

This document was prepared by Technical Committee ISO/TC 127, *Earth-moving machinery*, Subcommittee SC 1, *Test methods relating to safety and machine performance*.

This third edition cancels and replaces the second edition (ISO 8643:1997), which has been technically revised and contains the following changes:

 requirements and test provisions have been extended to support a wider range of lowering control device configurations.

Introduction

Where excavators or backhoe loaders are used for object handling, a failure or rupture in the hydraulic circuit can endanger persons under raised loads.

This risk can be reduced by applying a lowering control device, which ensures controlled lowering of the load in the case of a hydraulic line failure or rupture.

Test procedures are based on the design characteristics of the hydraulic systems of hydraulic excavators and the backhoe part of backhoe loaders, and conditions of use.

this document is a preview demendence of the document is a preview demendence of the document of the document

Earth-moving machinery — Hydraulic excavator and backhoe loader lowering control device — Requirements and tests

1 Scope

This document establishes uniform requirements and test procedures for lowering control devices fitted on the boom, intermediate boom and arm cylinders of hydraulic excavators and backhoe loaders to control the rate of drop in the case of a hydraulic line failure or rupture.

It is applicable to the lowering control devices of hydraulic excavators and the backhoe equipment of backhoe loaders used for object handling which are equipped with the standard linkage as defined by the manufacturer. On machines where alternative linkage combinations are offered, only the standard length defined by the manufacturer is subject to testing.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6165, Earth-moving machinery — Basic types — Identification and terms and definitions

ISO 9248:1992, Earth-moving machinery — Units for dimensions, performance and capacities, and their measurement accuracies

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 6165 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— IEC Electropedia: available at http://www.electropedia.org/

ISO Online browsing platform: available at http://www.iso.org/obp

3.1

linkage control system

hydraulic control components (including pilot and slave valves) used for raising and lowering the lift point in object handling applications

3.2

lifting linkage

assembly of parts that can be a combination of booms and arms used for raising and lowering the lift point in the object handling process

3.3

lowering control device

hydraulic control valves used for controlled linkage lowering in the case of a hydraulic line failure or rupture

3.4

failure-simulation device

hydraulic valves used for simulating a failure or rupture in a hydraulic line in the linkage control system