INTERNATIONAL **STANDARD**

ISO 16873

Second edition 2011-11-01

Hy swin. Transmissic.





© ISO 2011

duced or utilized in any for a from either ISO at the a All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 16873 was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 5, *Control products and components*.

This second edition cancels and replaces the first edition (ISO 16873:2002), which has been technically revised. It also incorporates the Amendment ISO 16873:2002/Amd 1:2005.

ause gure fo. The surface roughness is updated in Clause 5 according to ISO 3601-2. The modification in ISO 16873:2002/Amd.1:2005 concerning the figure footnotes is also incorporated.

Introduction

syste out. Pre i predeterm. In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure circulating within an enclosed circuit. Pressure switches are important components in such systems. They enable actions to be carried out with predetermined pressure values.

Hydraulic fluid power — Pressure switches — Mounting surfaces

1 Scope

This International Standard specifies the mounting surfaces for pressure switches and gives guidelines for the standardized arrangement of the connections for pressure switches and for the mounting of plates and hydraulic valves.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3601-2:2008, Fluid power systems — O-rings — Part 2: Housing dimensions for general applications

ISO 5598, Fluid power systems and components — Vocabulary

ISO 5783, Hydraulic fluid power — Code for identification of valve mounting surfaces and cartridge valve cavities

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5598 apply.

4 Symbols

- **4.1** For the purpose of this International Standard, the following symbols apply:
- a) P and L identify ports;
- b) F identifies threaded holes;
- c) G identifies locating pin holes.
- 4.2 The code system used in this International Standard is defined in ISO 5783.

5 Tolerances

The following requirements shall be applied to the mounting surface, i.e. the area within the chain thick lines in Figures 1 and 2:

- surface roughness: see ISO 3601-2:2008, 5.1.4 and 5.2.3;
- surface flatness: see ISO 3601-2:2008, 5.1.4;
- tolerance for diameters of locating pin holes: H12.