
**Information technology —
Telecommunications and information
exchange between systems — High-rate
ultra-wideband PHY and MAC standard**

*Technologies de l'information — Téléinformatique — Norme PHY et
MAC à bande ultralarge et haut débit*

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

This document is a preview generated by EVS



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents	Page
Foreword	x
Introduction	xi
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Terms and definitions	1
5 Notational conventions	4
6 Abbreviations and acronyms	4
7 General description	7
7.1 PHY general description	7
7.2 MAC general description	8
7.2.1 General description of the architecture	8
7.2.2 Device address	9
7.2.3 Features assumed from the PHY	9
7.2.4 Overview of MAC service functionality	9
7.2.5 MUX sublayer	13
7.2.6 MAC policies	13
7.2.7 Test vectors	13
8 PHY layer partitioning	13
8.1 PHY function	14
8.2 PLCP sublayer	14
8.3 PMD sublayer	14
8.4 PHY layer management entity (PLME)	14
9 Description of signal	14
9.1 Mathematical framework	14
9.2 Tone-Nulling	15
10 PLCP sublayer	16
10.1 PPDU	16
10.1.1 PSDU rate-dependent parameters	18
10.1.2 Timing-related parameters	18
10.1.3 Frame-related parameters	19
10.2 PLCP preamble	20
10.2.1 Standard PLCP preamble	20
10.2.2 Burst PLCP preamble	21
10.3 PLCP header	43
10.3.1 PHY header	44

10.3.2 Reed-Solomon outer code for the PLCP header	48
10.3.3 Header check sequence	50
10.4 PSDU	51
10.4.1 Pad bits	52
10.5 Data scrambler	53
10.6 Tail bits	54
10.7 Convolutional encoder	55
10.8 Bit interleaving	58
10.9 Constellation mapping	60
10.9.1 QPSK	60
10.9.2 Dual-carrier modulation (DCM)	61
10.10 OFDM modulation	63
10.10.1 Implementation considerations	67
10.10.2 Data subcarriers	67
10.10.3 Guard subcarriers	71
10.10.4 Pilot subcarriers	71
11 General requirements	73
11.1 Operating band frequencies	73
11.1.1 Operating frequency range	73
11.1.2 Band numbering	73
11.2 Channelization	74
11.3 PHY layer timing	78
11.3.1 Interframe spacing	78
11.3.2 Receive-to-transmit turnaround time	78
11.3.3 Transmit-to-receive turnaround time	79
11.3.4 Time between successive transmissions	79
11.3.5 Band frequency switch time	79
12 Transmitter specifications	79
12.1 Transmit PSD mask	79
12.2 Transmit centre frequency tolerance	80
12.3 Symbol clock frequency tolerance	80
12.4 Clock synchronization	80
12.5 Phase coherence	80
12.6 Transmit power control	80
12.7 Transmitter constellation error	81
13 Receiver specification	83
13.1 Receiver sensitivity	83
13.2 Receiver CCA performance	83
13.3 Link quality indicator	83
13.4 Receive Signal Strength Indicator	84
14 Ranging and location awareness	85
14.1 Ranging requirements	85

14.2 Ranging reference signal	85
14.3 PHY ranging resources	85
14.4 PHY ranging operation	85
14.5 Ranging calibration constants	85
14.6 Example range measurement (informative)	85
15 PHY and MAC service access points (informative)	86
15.1 Generic MIB management primitives	87
15.1.1 XX-GET.request	88
15.1.2 XX-GET.confirm	88
15.1.3 XX-SET.request	89
15.1.4 XX-SET.confirm	89
15.2 PHY SAP interface	90
15.2.1 Data transfer	90
15.2.2 PHY transmission control	91
15.2.3 PHY reception control	93
15.2.4 PHY CCA control	96
15.3 PLME SAP interface	97
15.3.1 PHY reset	99
15.3.2 PHY ranging timer control	100
15.4 MAC sublayer management primitives	101
15.5 MAC management information base (MIB)	101
15.6 MLME SAP interface	101
15.6.1 Reset	101
15.6.2 Scan	102
15.6.3 Beacon transmission and reception	104
15.6.4 IE management	109
15.6.5 PTK establishment	110
15.6.6 GTK solicitation/distribution	113
15.6.7 Temporal key update	116
15.6.8 Security violation report	118
15.6.9 Pseudo-random function (PRF)	119
15.6.10 Application-specific IE (ASIE) management	120
15.6.11 Multicast address binding	122
15.6.12 Link events	125
15.6.13 Probe	128
15.6.14 Hibernation and sleep cycle	131
15.6.15 Higher layer synchronization support	136
15.6.16 Reservation management	138
15.6.17 Connection configuration primitives	144
15.6.18 Range measurement	146
15.6.19 Application-specific command management	147
15.7 MAC SAP interface	149
15.7.1 MAC-DATA.request	151
15.7.2 MAC-DATA.indication	151

15.7.3 MAC-DATA.confirm	152
16 MAC frame formats	152
16.1 Frame format conventions	152
16.1.1 Figures	152
16.1.2 Octet order	152
16.1.3 Encoding	153
16.2 General MAC frame format	153
16.2.1 Frame control	154
16.2.2 DestAddr	155
16.2.3 SrcAddr	155
16.2.4 Sequence control	155
16.2.5 Access information	156
16.2.6 Frame payload	157
16.2.7 FCS	157
16.3 Beacon frames	158
16.4 Control frames	160
16.4.1 Immediate acknowledgement (Imm-ACK)	161
16.4.2 Block acknowledgement (B-ACK)	161
16.4.3 Request to send (RTS)	162
16.4.4 Clear to send (CTS)	162
16.4.5 Unused DRP reservation announcement (UDA)	162
16.4.6 Unused DRP reservation response (UDR)	162
16.4.7 Application-specific	162
16.5 Command frames	163
16.5.1 DRP reservation request	164
16.5.2 DRP reservation response	164
16.5.3 Probe	165
16.5.4 Pairwise temporal key (PTK)	165
16.5.5 Group temporal key (GTK)	166
16.5.6 Range measurement	167
16.5.7 Application-specific	168
16.6 Data frames	168
16.7 Aggregated data frames	169
16.8 Information elements	169
16.8.1 Application-specific IE (ASIE)	171
16.8.2 Application-specific probe IE	171
16.8.3 Beacon period occupancy IE (BPOIE)	172
16.8.4 BP switch IE	173
16.8.5 Channel change IE	173
16.8.6 Distributed reservation protocol (DRP) IE	173
16.8.7 DRP availability IE	175
16.8.8 Hibernation anchor IE	175
16.8.9 Hibernation mode IE	176
16.8.10 Identification IE	176

16.8.11 Link feedback IE	178
16.8.12 MAC capabilities IE	179
16.8.13 Master key identifier (MKID) IE	180
16.8.14 Multicast address binding (MAB) IE	180
16.8.15 PCA availability IE	181
16.8.16 PHY capabilities IE	181
16.8.17 Probe IE	184
16.8.18 Regulatory Domain IE	184
16.8.19 Relinquish request IE	185
16.8.20 Tone-nulling (TN) IE	186
16.8.21 Traffic indication map (TIM) IE	187
17 MAC sublayer functional description	187
17.1 Frame processing	187
17.1.1 Frame addresses	188
17.1.2 Frame reception	188
17.1.3 Frame transaction	188
17.1.4 Frame transfer	189
17.1.5 Frame retry	190
17.1.6 Inter-frame space (IFS)	190
17.1.7 Duplicate detection	190
17.1.8 RTS/CTS use	191
17.1.9 MAC header fields	191
17.1.10 Information elements	194
17.2 Beacon period	197
17.2.1 Beacon slot state	198
17.2.2 BP length	198
17.2.3 Beacon transmission and reception	199
17.2.4 Beacon slot collision detection	200
17.2.5 BP contraction	201
17.2.6 Merger of multiple BPs	201
17.3 Prioritized contention access (PCA)	204
17.3.1 PCA medium availability	205
17.3.2 NAV	205
17.3.3 Medium status	205
17.3.4 PCA parameters	205
17.3.5 Obtaining a TXOP	206
17.3.6 Using a TXOP	207
17.3.7 Invoking a backoff procedure	208
17.3.8 Decrementing a backoff counter	209
17.4 Distributed reservation protocol (DRP)	209
17.4.1 Reservation type	210
17.4.2 Medium access	211
17.4.3 DRP availability IE	211
17.4.4 DRP reservation negotiation	212

17.4.5	DRP reservation announcements	213
17.4.6	Resolution of DRP reservation conflicts	213
17.4.7	BPST realignment and existing DRP reservations	215
17.4.8	Modification and termination of existing DRP reservations	215
17.4.9	Release of hard or private DRP reservation blocks	215
17.4.10	Retransmit procedures in DRP reservations	216
17.5	Synchronization of devices	216
17.5.1	Clock accuracy	217
17.5.2	Synchronization for devices in hibernation mode	217
17.5.3	Guard times	217
17.6	Fragmentation and reassembly	218
17.7	Aggregation	219
17.8	Acknowledgement policies	219
17.8.1	No-ACK	219
17.8.2	Immediate ACK	219
17.8.3	Block ACK	219
17.9	Probe	221
17.10	Dynamic channel selection	222
17.11	Multi-rate support	222
17.12	Transmit power control	222
17.13	Power management mechanisms	223
17.13.1	Power management modes	223
17.13.2	Device power states	223
17.13.3	Power state transitions	223
17.13.4	Hibernation mode operation	224
17.13.5	Hibernation anchor operation	225
17.14	ASIE operation	226
17.15	Range measurement operation	226
17.16	MAC sublayer parameters	229
18	Security	230
18.1	Security mechanisms	231
18.1.1	Security operation	231
18.1.2	4-way handshake	231
18.1.3	Key transport	231
18.1.4	Freshness protection	231
18.1.5	Data encryption	231
18.1.6	Frame integrity protection	232
18.2	Security modes	232
18.2.1	Security mode 0	234
18.2.2	Security mode 1	234
18.2.3	Security mode 2	234
18.3	Temporal keys	235
18.3.1	Mutual authentication and PTK derivation	235
18.3.2	GTK exchange	236

18.3.3 Pseudo-random function (PRF) definition	237
18.3.4 PTK and KCK derivation	237
18.3.5 PTK MIC generation	238
18.3.6 Random number generation	238
18.4 Frame reception steps and replay prevention measures	239
18.4.1 Frame reception	239
18.4.2 Replay prevention	239
18.4.3 Implications on GTKs	240
18.5 AES-128 CCM Inputs	240
18.5.1 Overview	240
18.5.2 Nonce	240
18.5.3 CCM blocks	241
Annex A (normative) MUX sublayer	243
Annex B (normative) MAC Policies	246
Annex C (normative) Assigned number document	249
Annex D (informative) MAC test vectors	250
Annex E (informative) Example encoding of a PHY packet	261
Annex F (informative) Recommended out-of-band emission limits	306
Annex G (informative) Range measurement calculations	307
Bibliography	311

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 26907 was prepared by Ecma International (as ECMA-368) and was adopted, under a special "fast-track procedure", by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

This second edition cancels and replaces the first edition (ISO/IEC 26907:2007), which has been technically revised.

The second edition adds the following for regulatory flexibility.

- an additional TFI code;
- an additional Band Group;
- tone nulling for interference avoidance.

It also

- relaxes the requirement for Band group 1,
- relocates some assigned numbers to Ecma registries on the website,
- adds an information element for Bluetooth.

Introduction

This International Standard specifies the ultra wideband (UWB) physical layer (PHY) and medium access control (MAC) sublayer for a high-speed, short-range wireless network, utilizing all or part of the spectrum between 3 100 MHz and 10 600 MHz, supporting data rates of up to 480 Mb/s.

This International Standard divides the spectrum into 14 bands, each with a bandwidth of 528 MHz. The first 12 bands are then grouped into four band groups consisting of three bands. The last two bands are grouped into a fifth band group. A sixth band group is also defined within the spectrum of the first four, consistent with usage within worldwide regulatory regulations.

A MultiBand Orthogonal Frequency Division Modulation (MB-OFDM) scheme is used to transmit information. A total of 110 sub-carriers (100 data carriers and 10 guard carriers) are used per band. In addition, 12 pilot sub-carriers allow for coherent detection. Frequency-domain spreading, time-domain spreading, and forward error correction (FEC) coding are provided for optimum performance under a variety of channel conditions.

The MAC sublayer is designed to enable mobility, such that a group of devices may continue communicating while merging or splitting from other groups of devices. To maximize flexibility, the functionality of this MAC is distributed among devices. These functions include distributed coordination to avoid interference between different groups of devices by appropriate use of channels and distributed medium reservations to ensure Quality of Service. The MAC sublayer provides prioritized schemes for isochronous and asynchronous data transfer. To do this, a combination of Carrier Sense Multiple Access (CSMA) and Time Division Multiple Access (TDMA) is used. A Distributed Reservation Protocol (DRP) is used to reserve the medium for TDMA access for isochronous and other traffic. For network scalability, Prioritized Contention Access (PCA) is provided using a CSMA scheme. The MAC has policies that ensure equitable sharing of the bandwidth.

Taken together, the PHY and MAC specified in this Ecma standard are well-suited to high rate, zero infrastructure communications between a mixed population of portable and fixed electronic devices.

This International Standard is not intended to represent the regulatory requirements of any country or region.

This document is a preview generated by EVS

Information technology — Telecommunications and information exchange between systems — High-rate ultra-wideband PHY and MAC standard

1 Scope

This International Standard specifies a distributed medium access control (MAC) sublayer and a physical layer (PHY) for wireless networks.

2 Conformance

Conforming devices implement the MAC sublayer and the PHY layer as specified herein and support:

1. data rates of 53,3 Mb/s, 106,7 Mb/s, and 200 Mb/s for transmitting and receiving;
2. at least one of the band groups;
3. time-frequency codes using both TFI and FFI.

In addition, conforming devices may implement the MAC/PHY Interface as specified in ISO/IEC 26908.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEEE 100, The Authoritative Dictionary of IEEE Standard Terms, Seventh Edition

NOTE 1 IEEE publications are available from the Institute of Electrical and Electronics Engineers, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ 08855-1331, USA (<http://standards.ieee.org/>).

NOTE 2 The IEEE standards referenced are trademarks belonging to the Institute of Electrical and Electronics Engineers, Inc.

4 Terms and definitions

For the purposes of this document, the terms and definitions given in IEEE 100 and the following apply.

4.1

access category

AC

label for the common set of prioritized contention access (PCA) parameters that are used by a device to contend for the medium in order to transmit MAC protocol data units (MPDUs) with certain priorities

4.2

beacon group

BG

set of devices from which a device receives beacons that identify the same beacon period start time (BPST) as the device