

Edition 2.0 2017-03

INTERNATIONAL STANDARD



Power quality measurement in power supply systems – Part 2: Functional tests and uncertainty requirements





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office Tel.: +41 22 919 02 11 3, rue de Varembé Fax: +41 22 919 03 00

CH-1211 Geneva 20 info@iec.ch Switzerland www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.



Edition 2.0 2017-03

INTERNATIONAL STANDARD



Power quality measurement in power supply systems – Part 2: Functional tests and uncertainty requirements

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 17.220.20 ISBN 978-2-8322-4052-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

Ε(ノベニ۷۷ ひに	₹⋃	9
		CTION	
1)	
2		ative references	
3		s, definitions, abbreviated terms, notations and symbols	
		General terms and definitions	
		Terms and definitions related to uncertainty	
		Notations	
	3.3.1	Functions	
	3.3.2	Symbols and abbreviated terms	
	3.3.3	Indices	
4	•	rements	
		Requirements for products complying with class A	
		Requirements for products complying with class S	
5		ional type tests common requirements	
	5.1	General philosophy for testing	
	5.1.1	System topology	
	5.1.2	Stabilization time	
	5.1.3	Measuring ranges	
	5.1.4	Single "power-system influence quantities"	
	5.1.5	"External influence quantities"	
	5.1.6	Test criteria	
		Testing procedure	22
	5.2.1	Device under test	22
	5.2.2	Testing conditions	22
	5.2.3	Testing equipment	22
6	IEC 6	ional testing procedure for instruments complying with class A according to 1000-4-30	
	6.1	Power frequency	22
	6.1.1	General	22
	6.1.2	Measurement method	23
	6.1.3	Measurement uncertainty and measuring range	23
	6.1.4	Measurement evaluation	24
	6.1.5	Measurement aggregation	24
	6.2	Magnitude of supply voltage	24
	6.2.1	Measurement method	24
	6.2.2	Measurement uncertainty and measuring range	24
	6.2.3	Measurement evaluation	
	6.2.4	Measurement aggregation	25
	6.3	Flicker	27
	6.4	Supply voltage interruptions, dips and swells	27
	6.4.1	General	
	6.4.2	Check dips / interruptions in polyphase system	35
	6.4.3	Check swells in polyphase system	37
	6.5	Supply voltage unbalance	38
	6.5.1	General	38

	6.5.2	Measurement method, measurement uncertainty and measuring range	30
	6.5.3		
	6.6	Voltage harmonics	
	6.6.1	Measurement method	
	6.6.2		
	6.6.3		
	6.6.4		
	6.7	Voltage interharmonics	
	6.7.1		
	6.7.2		
	6.7.3		
	6.7.4		
	6.8	Mains signalling voltages on the supply voltage	
	6.8.1		
	6.8.2		
	6.8.3		
	6.9	Measurement of underdeviation and overdeviation parameters	
	6.9.1		
	6.9.2		
	6.9.3		
	6.9.4		
	6.10	Flagging	
	6.11	Clock uncertainty testing	
	6.12	Variations due to external influence quantities	
	6.12.		
	6.12.		
	6.12.		
	6.13.		
	6.13.		
	6.13.		
	6.13.		
	6.13.		
	6.13.		
	6.13.		
	6.14	Magnitude of current	
	6.15	Harmonic current	
	6.16	Interharmonic currents	
	6.17	Current unbalance	
	6.17.		
	6.17.		
7	• • • • •	tional testing procedure for instruments complying with class S according to	76
'		31000-4-30	78
	7.1	Power frequency	78
	7.1.1	General	
	7.1.2	Measurement method	79
	7.1.3	Measurement uncertainty and measuring range	79
	7.1.4	Measurement evaluation	80
	715	Measurement aggregation	80

7.2 M	agnitude of the supply voltage	80
7.2.1	Measurement method	80
7.2.2	Measurement uncertainty and measuring range	80
7.2.3	Measurement evaluation	81
7.2.4	Measurement aggregation	81
7.3 F	icker	83
7.4 S	upply voltage interruptions, dips and swells	83
7.4.1	General requirements	84
7.4.2	Check dips / interruptions in polyphase system	89
7.4.3	Check swells in polyphase system	91
7.5 S	upply voltage unbalance	92
7.5.1	General	92
7.5.2	Measurement method, measurement uncertainty and measuring range	93
7.5.3	Aggregation	93
7.6 V	oltage harmonics	93
7.6.1	General	93
7.6.2	Measurement method	94
7.6.3	Measurement method, measurement uncertainty and measuring range	95
7.6.4	Measurement evaluation	
7.6.5	Measurement aggregation	96
7.7 V	oltage interharmonics	98
	ains signalling voltages on the supply voltage	
7.8.1	General	
7.8.2	Measurement method	
7.8.3	Measurement uncertainty and measuring range	99
7.8.4	Aggregation	
7.9 M	easurement of underdeviation and overdeviation parameters	
	agging	
	lock uncertainty testing	
	ariations due to external influence quantities	
7.12.1	General	
7.12.2	Influence of temperature	
7.12.3	Influence of power supply voltage	105
	apid voltage changes	106
	agnitude of current	
	armonic current	
	terharmonic currents	
	urrent unbalance	
7.17.1	General	
7.17.2	Measurement method, measurement uncertainty and measuring range	
8 Calcula	tion of measurement uncertainty and operating uncertainty	
	rmative) Intrinsic uncertainty and operating uncertainty,	
,	eneral	
	eneral easurement uncertainty easurement	
	•	
	perating uncertaintyformative) Overall system uncertainty	
-		112
	ormative) Calculation of measurement and operating uncertainty for nitude and power frequency	113

C.1 Selection of test points to verify operating uncertainty and uncertainty under reference conditions	11:
C.2 Class A calculation examples	
C.2.1 General	113
C.2.2 Parameter: magnitude of supply voltage, U_{din} = 230 V, 50/60Hz, rated	445
range of temperature −25 °C to +55 °C	113
C.2.3 Parameter: power frequency 50/60 Hz, rated range of temperature -25 °C to +55 °C	11/
Annex D (informative) Further test on dips (amplitude and phase angles changes)	
D.1 Phase-to-phase or phase-to-neutral testing	
D.2 Test method	
E.1 General	
E.2 Phase voltage dips and interruptions	
E.3 Phase swells	
Annex F (normative) Gapless measurements of voltage amplitude and harmonics test	
F.1 Purpose of the test	
F.2 Test set up	121
F.3 Voltage amplitude	121
F.3.1 Test signal	
F.3.2 Result evaluation	121
F.4 Harmonics	
F.4.1 Test signal	
F.4.2 Result evaluation	
F.5 Inter-harmonics	
F.5.1 Test signal	
F.5.2 Result evaluation	120
Annex G (informative) Gapless measurements of voltage amplitude and harmonics	
Annex H (informative) Testing equipment recommendations	
H.1 Testing range	
H.2 Uncertainty and stability of source and reference meter	
H.2.1 Uncertainty of source and reference meter	
H.2.2 Stability of the source	
H.3 Time synchronisation	134
H.4 Power quality functions of source and reference meter	134
H.5 Traceability	135
Annex I (informative) Recommendations related to a declaration of conformity (DoC)	
and a test report	136
I.1 Definitions	136
I.2 Recommendations	136
I.3 Example of IEC 62586-1 declaration of conformity	
I.4 Example of IEC 62586-2 declaration	
I.4.1 General	
I.4.2 Recommendation for IEC 62586-2 test report	
I.4.3 Recommendation for IEC 62586-2 test report	
I.4.4 Recommendation for IEC 62586-2 test equipment information	
I.4.5 Recommendation for IEC 62586-2 tested functions	
Ribliography	1/1

Figure 1 – Overview of test for dips according to test A4.1.1	30
Figure 2 – Detail 1 of waveform for test of dips according to test A4.1.1	31
Figure 3 – Detail 2 of waveform for tests of dips according to A4.1.1	31
Figure 4 – Detail 3 of waveform for tests of dips according to test A4.1.1	32
Figure 5 - Detail 1 of waveform for test of dips according to test A4.1.2	32
Figure 6 – Detail 2 of waveform for tests of dips according to test A4.1.2	33
Figure 7 – Detail 1 of waveform for test of swells according to test A4.1.2	33
Figure 8 – Detail 2 of waveform for tests of swells according to test A4.1.2	34
Figure 9 – Sliding reference voltage test	34
Figure 10 – Sliding reference start up condition	35
Figure 11 – Detail 1 of waveform for test of polyphase dips/interruptions	36
Figure 12 – Detail 2 of waveform for test of polyphase dips/interruptions	36
Figure 13 – Detail 3 of waveform for test of polyphase dips/interruptions	37
Figure 14 – Detail 1 of waveform for test of polyphase swells	38
Figure 15 – Detail 2 of waveform for test of polyphase swells	38
Figure 16 – Flagging test for class A	57
Figure 17 – Clock uncertainty testing	58
Figure 18 – Example of RVC event	62
Figure 19 – A13.1.1 waveform	65
Figure 20 - A13.1.1 waveform with RVC limits and arithmetic mean	65
Figure 21 – A13.1.2 waveform	66
Figure 22 – A13.1.2 waveform with RVC limits and arithmetic means	67
Figure 23 – A13.1.3 waveform	68
Figure 24 – A13.1.3 waveform with RVC limits and arithmetic mean	68
Figure 25 – A13.2.1 waveform	69
Figure 26 – A13.2.1 waveform with RVC limits and arithmetic mean	70
Figure 27 – A13.3.1 waveform	71
Figure 28 – A13.3.1 waveform with RVC limits and arithmetic mean	72
Figure 29 – A13.4.1 waveform	
Figure 30 – A13.5.1 waveform	75
Figure 31 –A13.5.1 waveform with RVC limits and arithmetic mean	75
Figure 32 – A13.5.2 waveform	76
Figure 33 – A13.5.2 waveform with RVC limits and arithmetic mean	77
Figure 34 – Detail 1 of waveform for test of dips according to test S4.1.2	86
Figure 35 – Detail 2 of waveform for tests of dips according to test S4.1.2	87
Figure 36 – Detail 1 of waveform for test of swells according to test S4.1.2	87
Figure 37 – Detail 2 of waveform for tests of swells according to test S4.1.2	88
Figure 38 – Sliding reference voltage test	88
Figure 39 – Sliding reference start-up condition	89
Figure 40 – Detail 1 of waveform for test of polyphase dips/interruptions	90
Figure 41 – Detail 2 of waveform for test of polyphase dips/interruptions	90
Figure 42 – Detail 3 of waveform for test of polyphase dips/interruptions	91

Figure 43 – Detail 1 of waveform for test of polyphase swells	92
Figure 44 – Detail 2 of waveform for test of polyphase swells	92
Figure 45 – Flagging test for class S	101
Figure 46 – Clock uncertainty testing	102
Figure A.1 – Different kinds of uncertainties	110
Figure D.1 – Phase-to-neutral testing on three-phase systems	116
Figure D.2 - Phase-to-phase testing on three-phase systems	116
Figure E.1 – Example for one phase of a typical N cycle injection	118
Figure E.2 – Dip/interruption accuracy (amplitude and timing) test	119
Figure E.3 – Swell accuracy (amplitude and timing) test	120
Figure G.1 – Simulated signal under noisy conditions	124
Figure G.2 – Waveform for checking gapless RMS voltage measurement	125
Figure G.3 – 2,3 Hz frequency fluctuation	125
Figure G.4 – Spectral leakage effects for a missing sample	126
Figure G.5 – Illustration of Q_{RMS} for missing samples	127
Figure G.6 – Detection of a single missing sample	127
Figure G.7 – Q_{RMS} for an ideal signal, sampling error = -300 × 10 ⁻⁶	128
Figure G.8 – Q_{RMS} for an ideal signal, sampling error = 400 × 10 ⁻⁶	128
Figure G.9 – Q_{RMS} for an ideal signal, sampling error = 200 × 10 ⁻⁶	129
Figure G.10 – Q_H (5) with ideal test signal and perfect sampling frequency synchronization	130
Figure G.11 – $Q_{\rm H}$ (5) with 300 × 10 ⁻⁶ sampling frequency error and 100 × 10 ⁻⁶ modulation frequency error	130
Figure G.12 – Q_{RMS} with a 20/24-cycle sliding window with an output every 10/12 cycles	131
Figure G.13 – Amplitude test for fluctuating component	131
Table 1 – Summary of type tests for class A	15
Table 2 – Summary of type tests for class S	16
Table 3 – Testing points for each measured parameter	
Table 4 – List of single "power-system influence quantities"	20
Table 5 – Influence of temperature	21
Table 6 – Influence of auxiliary power supply voltage	21
Table 7 – List of generic test criteria	22
Table 8 – Specification of test A13.1.1	64
Table 9 – Specification of test A13.1.2	66
Table 10 – Specification of test A13.1.3	67
Table 11 – Specification of test A13.2.1	69
Table 12 – Specification of test A13.3.1	71
Table 13 – Specification of test A13.4.1	73
Table 14 – Specification of test A13.5.1	74
Table 15 – Specification of test A13.5.2	76
Table 16 – Uncertainty requirements	109
Table D.1 – Tests pattern	117

blo H.O. Uppertainty of source and reference mater	133
ble H.2 – Uncertainty of source and reference meter	
ble H.3 – Stability of source	
ble I.1 – Example of a DoC related to compliance with IEC 62586-1ble I.2 – Example of DoC related to compliance with IEC 62586-2	
ble 1.2 – Example of Doc related to compliance with 1EC 02300-2	139
6	
	1)/
	50

INTERNATIONAL ELECTROTECHNICAL COMMISSION

POWER QUALITY MEASUREMENT IN POWER SUPPLY SYSTEMS -

Part 2: Functional tests and uncertainty requirements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62586-2 has been prepared by IEC technical committee 85: Measuring equipment for electrical and electromagnetic quantities.

This second edition cancels and replaces the first edition published in 2013. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) test procedures for RVC and current have been added;
- b) mistakes have been fixed.

The text of this standard is based on the following documents:

CDV	Report on voting
85/525/CDV	85/571/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 62586 series, published under the general title *Power quality* measurement in power supply systems, can be found on the IEC website.

The contents of the corrigendum of November 2014 have been included in this copy.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Power quality is more and more important worldwide in power supply systems and is generally assessed by power quality instruments.

This part of IEC 62586 specifies functional and uncertainty tests intended to verify the compliance of a product to class A and class S measurement methods defined in IEC 61000-4-30. Telore C.

Chimodratics and Continuous and Continuo

This document therefore complements IEC 61000-4-30.

POWER QUALITY MEASUREMENT IN POWER SUPPLY SYSTEMS -

Part 2: Functional tests and uncertainty requirements

1 Scope

This part of IEC 62586 specifies functional tests and uncertainty requirements for instruments whose functions include measuring, recording, and possibly monitoring power quality parameters in power supply systems, and whose measuring methods (class A or class S) are defined in IEC 61000-4-30.

This document applies to power quality instruments complying with IEC 62586-1.

This document can also be referred to by other product standards (e.g. digital fault recorders, revenue meters, MV or HV protection relays) specifying devices embedding class A or class S power quality functions according to IEC 61000-4-30.

These requirements are applicable in single-, dual- (split phase) and 3-phase AC power supply systems at 50 Hz or 60 Hz.

It is not the intent of this document to address user interface or topics unrelated to device measurement performance.

The document does not cover post-processing and interpretation of the data, for example with dedicated software.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61000-2-4, Electromagnetic compatibility (EMC) – Part 2-4: Environment – Compatibility levels in industrial plants for low-frequency conducted disturbances

IEC 61000-4-7, Electromagnetic compatibility (EMC) — Part 4-7: Testing and measurement techniques — General guide on harmonics and interharmonics measurements and instrumentation, for power supply systems and equipment connected thereto

IEC 61000-4-15, Electromagnetic compatibility (EMC) – Part 4-15: Testing and measurement techniques – Flickermeter – Functional and design specifications

IEC 61000-4-30:2015, Electromagnetic compatibility (EMC) – Part 4-30: Testing and measurement techniques – Power quality measurement methodsIEC 62586-1:2013, Power quality measurement in power supply systems – Part 1: Power quality instruments (PQI)

ISO/IEC Guide 98-3:2008, Uncertainty of measurement – Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)