### INTERNATIONAL STANDARD



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION •МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ •ORGANISATION INTERNATIONALE DE NORMALISATION

## Information processing — General purpose reels with 8 mm (5/16 in) centre hole for magnetic tape for interchange instrumentation applications

Traitement de l'information — Bobines à usage général, avec trou central de 8 mm (5/16 in), pour bandes magnétiques pour l'enregistrement de mesures

First edition - 1976-10-15

UDC 681.327.64

Ref. No. ISO 3802-1976 (E)

Descriptors: data processing, information interchange, instrumentation recording, magnetic tapes, bobbins, specifications, dimensions.

### **FOREWORD**

ISO (the International Organization) for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaisop with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 3802 was drawn up Technical Committee ISO/TC 97, Computers and information processing, and vas circulated to the Member Bodies in July 1975.

It has been approved by the Member Bodies of the following could

Australia
Belgium Japan
Brazil Mexico
Czechoslovakia Netherlands
France New Zealand U.S.S.R.
Hungary Poland

The Member Body of the following country expressed disapproval of the document on technical grounds:

Germany

## 75

# Information processing — General purpose reels with 8 mm (5/16 in) centre hole for magnetic tape for interchange instrumentation applications

### 1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies the dimensions of general purpose reels with 8 mm (5/16 in) centre hole, designed for use with magnetic tape in interchange instrumentation application.

#### 2 HUB AND REEL DIMENSIONS

- **2.1** The dimensions of the reels shall be as specified in the figure, and tables 1 and 2.
- **2.2** Reels shall be symmetrical to permit mounting from either side.
- **2.3** Bosses, ribs, or raised designs are permitted on the outside surfaces of the flanges provided they do not extend beyond the planes defined by dimension M.
- **2.4** Flanges may have holes of convenient size, shape, and location to facilitate threading.
- **2.5** Reels having diameter C equal to or greater than 45 mm (1.77 in), shall have at least one drive hole (diameter P). Two or three symmetrically spaced drive holes are optional.

**2.6** The reel surfaces defined by dimensions M and L shall be parallel within 0,2 mm (0.008 in).

2.7 The reel surfaces defined by dimensions N and B shall be parallel within 0,5 mm (0.02 in).

- **2.8** The eccentricity of the outside cylindrical surface of the hub (diameter *C*), with respect to the centre hole (diameter *A*) shall not exceed 0,2 mm (0.008 in).
- 2.9 The maximum taper of the outside cylindrical surface of the hub (diameter  $C_{\rm i}$  measured over the length N, shall be 0,08 mm (0.003 in).
- **2.10** The eccentricity of the outside diameter of the flanges (diameter B) with respect to the centre hole (diameter A) shall not exceed 0.5 mm (0.02 in).

### 3 MATERIAL

Plastics material (for example, high impact polystyrene) or metal (for example, aluminium alloy) may be used, dependent upon the duty.