

IEC TR 63079

Edition 1.0 2017-04

TECHNICAL REPORT



Code of practice for hearing-loop systems (HLS)





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office Tel.: +41 22 919 02 11 3, rue de Varembé Fax: +41 22 919 03 00

CH-1211 Geneva 20 info@iec.ch Switzerland www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.





Edition 1.0 2017-04

TECHNICAL REPORT



Code of practice for hearing-loop systems (HLS)

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 17.140.50 ISBN 978-2-8322-4154-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FC	DREWO	RD	7
IN	TRODU	CTION	9
1	Scop	e	. 10
2	Norm	ative references	. 10
3	Term	s, definitions, signs and symbols	. 10
	3.1	Terms and definitions	
	3.2	Signs and symbols	
	3.2.1	Symbol for an induction-loop	
	3.2.2	Symbol for multiple loops	
	3.2.3	Sign for display in premises where an HLS is installed and for HLS equipment identification	. 13
	3.2.4	Identification of areas where reception of the HLS is not satisfactory	
4	Gene	ral	. 14
	4.1	How to use this document	.14
	4.1.1	Persons addressed	. 14
	4.1.2	Objectives	. 14
	4.2	Specialist advice	. 15
	4.3	Safety aspects	. 15
	4.4	Conforming to existing performance documents	. 15
5	Tech	nical advice	. 15
	5.1	Complying with this document	. 15
	5.2	Seeking technical advice	. 15
	5.3	The nature of the advice	
	5.4	Professional (consultancy) advice	.16
6	Purpo	ose of the system	. 16
7	Choo	sing the system supplier	. 16
	7.1	General	
	7.2	Approaching a contractor	
	7.3	Approaching a manufacturer of HLS equipment	
	7.4	Approaching a specialist consultant	
8	Conti	actual provisions	
	8.1	Performance specification	
	8.2	Verifying that the completed system delivers its intended performance	
	8.3	Arbitration	
9	Class	ification of systems	
10		ın	
	10.1	General	
	10.1	Symbols	
	10.3	Basic theory	
	10.3.		
	10.3.	·	
	10.3.		
	10.3.	,	
	10.3.	Relationship between the requirements of IEC 60118-4 and the	
	40.0	characteristics of hearing aids and speech signals	
	10.3.	6 Impedance of the loop	.∠ŏ

10.3.7	Selection of the method of driving the loop	29
10.3.8	B Current-driven loop	29
10.3.9	Voltage-driven loop	30
10.3.1	0 Voltage-driven loop with high-level equalization	31
10.3.1	1 Voltage-driven loop with low-level equalization	33
10.3.	2 Use of transformers	33
10.3.	3 Effects of building construction	34
10.3.1	4 Electromagnetic compatibility (EMC)	35
10.3.1	3	37
10.3.1	6 Equalization, other than for compensating loop impedance characteristics	37
10.3.1	7 Multiple loops	37
10.3.1	8 Protection of loop conductors	40
10.3.1	9 Automatic gain control (AGC), compression, limiting, noise gating and voice control	40
10.3.2	20 Signal-to-noise ratio	41
10.3.2	· ·	
	System components	
10.4.1		
10.4.2		
10.4.3	3	
	Objective measurement of intelligibility	
	Safety and reliability considerations	
	Designing for monitoring and maintenance	
	External factors	
10.8.1	S Comments of the comments of	
10.8.2	2 Effect of metal in the building	52
	Magnetic field overspill	
	The role of the system designer in commissioning	
	onsibility of the installer	
	lation practices and workmanship	
13 Inspe	ction and testing of wiring	55
	nissioning	
15 Docur	nentation	57
16 Certif	cation	58
	otance	
	cation	
	r responsibilities	
	Signage	
	User feedback	
	Staff training	
	ation and maintenance	
	General	
	Routine testing	
	Inspection and servicing	
	Non-routine attention	
	Special inspection on appointment of a new maintenance organization	
	Special inspection on appointment of a new maintenance organization Arrangements for repair of faults or damage	63

20.7	Modifications to the system	63
21 User	responsibilities	64
21.1	Responsible person	64
21.2	Logbook	65
Annex A (informative) HLS monitoring receivers	66
A.1	General	66
A.2	Recommendations for fixed receivers	66
A.3	Recommendations for portable receivers	67
Annex B (informative) What is a hearing-loop system (HLS) and how does it work?	68
B.1	General	68
B.2	Benefits of HLS (for hearing enhancement)	68
B.3	Limitations of HLS	69
Annex C (informative) Explanations of the basis of the design formulas	70
C.1	Magnetic field strength	70
C.1.1	Magnetic field strength produced by an element of conductor	70
C.1.2	Field strength produced by a circular loop at a point on its axis	70
C.2	Magnetic field strength at the centre of a rectangular loop	72
C.3	Magnetic field strength at an arbitrary point	73
C.4	Loop conductor sizes and resistances	78
C.4.1		78
C.4.2	Resistance of the loop conductor and relation between conductor size and cut-off frequency for a voltage-driven loop	78
C.4.3	Quick reference tables (derived from IEC 60228)	79
C.4.4	Inductance of two parallel wires, leading to the inductance of a rectangular loop	79
C.4.5	Variation of the impedance of a loop of fixed dimensions with conductor resistance	
C.4.6	High-level equalizer	82
	informative) Explanation of the specification and measurement of magnetic gth of induction-loop systems	85
Annex E (normative) Specification of the PPM-based field strength meter	87
E.1	General	
E.2	Checking magnetic field strength meters	88
Annex F (informative) Magnetic field direction near the loop conductor	
	informative) Direct-to-reverberant sound pressure ratio	
	informative) Model certificates	
H.1	Design certificate	
H.2	Installation certificate	
H.3	Commissioning certificate	
H.4	Acceptance certificate	
H.5	Verification certificate (optional)	
H.6	Inspection and servicing certificate	
H.7	Modification certificate	
Bibliograp	hy	102
Figure 1 -	- Symbol for use on diagrams	12
Figure 2	Symbol for multiple loops for use on diagrams	13

Figure 3 – Sign for display in premises to indicate that an HLS is installed and for HLS equipment identification	13
Figure 4 – Sign to show seating areas where HLS reception is not satisfactory	14
Figure 5 – Pictorial view of the magnetic field (lines of force) of a rectangular loop	21
Figure 6 – Directional response of a hearing aid telecoil	23
Figure 7 – Variation of the strength of the perpendicular component of the magnetic field across an axis of a rectangular loop, with listening height as parameter	24
Figure 8 – Variation across the median of a square loop of the perpendicular and coplanar components of the magnetic field at a height ratio $h_{\rm n}$ = 1	25
Figure 9 – Variation across the diagonal of a square loop of the perpendicular and coplanar components of the magnetic field at a height ratio $h_{\rm n}$ = 1	25
Figure 10 – Variation with frequency of the logarithm of the impedance of loops of constant inductance <i>L</i> , with the loop resistance <i>R</i> as parameter	29
Figure 11 – Circuit diagram of a "high-level" equalizer (for insertion between the amplifier and the loop)	33
Figure 12 – Preferred loop layout in a steel-framed building	34
Figure 13 – Methods of breaking eddy current paths in metal structures	35
Figure 14 – Filter for attenuating VHF signals picked up by the loop	35
Figure 15 – Methods of "breaking" loops into which interference voltages could be induced by an HLS	36
Figure 16 – Multiple loop layouts	38
Figure 17 – Variation across an axis of the system, at a height ratio of 0,32, of the component of the field strength, for a loop system similar to that shown in Figure 16 c), compared with the corresponding variations for a conventional single loop	39
Figure 18 – Horizontal directional response of an omni-directional microphone with its axis vertical: decibel scale	46
Figure 19 – Directional response of a cardioid microphone: decibel scale	46
Figure 20 – Directional response of a supercardioid microphone: decibel scale	47
Figure 21 – Directional response of a hypercardioid microphone: decibel scale	47
Figure 22 – Directional response of a highly directional shotgun (rifle) microphone where $f = 250$ Hz and barrel length is 275 mm	47
Figure 23 – Directional response of the same microphone where $f = 2.5 \text{ kHz}$	47
Figure 24 – Directional response of the same microphone where $f = 10 \text{ kHz}$	47
Figure 25 – Relative operating distances of directional microphones for equal direct-to-reverberant signal ratios	48
Figure 26 – Two methods of positioning microphones on a conference table	49
Figure 27 – The 3-to-1 ratio for microphone positioning (normal)	
Figure 28 – A reduced 3-to-1 ratio using angled microphones	49
Figure 29 – Illustrations of good and bad microphone placements	50
Figure 30 – Optimization of the height of the microphone above the table	250
Figure 31 – Measuring field strength of type 2 HLS – Plan views	57
Figure C.1 – Generation of magnetic fields	71
Figure C.2 – Diagram for calculating magnetic field strength at the centre of a rectangular loop	73
Figure C.3 – Diagram for calculating magnetic field strength at an arbitrary point	75
Figure C.4 – Diagram for calculating cosΦ and sinΦ	75
Figure C.5 – Diagram for calculating magnetic field strength at point (x, y, z)	77

Figure C.7 – Frequency response obtained with a high-level equalizer	84
	84
Figure E.1 – "EQ" or "wideband" frequency response: target curve and tolerances or response	
Figure F.1 – Magnetic field patterns	89
Figure F.2 – Magnetic field directions for a floor-level loop	90
Figure F.3 – Magnetic field directions for a ceiling-level loop	90
Table 1 – Classes of loop system	19
Table 2 – Relative operating distances of directional microphones for equal direct-to reverberant signal ratios	
Table C.1 – Factor by which the loop current has to be increased, compared with the required for a given magnetic field strength at the centre of a square loop, to obtain the same field strength for a rectangular loop at a point at height ratio of $h_{\rm n}$ above a below the centre of the loop	or
Table C.2 – Class 5 flexible annealed copper conductors for standard single-core a multi-core cables	
Table C.3 – Class 1 solid annealed copper conductors for single-core and multi-core cables	
Table C.4 – Ratio of approximate to exact inductance	82
Table C.5 – Values of $L_{ Z }$	

INTERNATIONAL ELECTROTECHNICAL COMMISSION

CODE OF PRACTICE FOR HEARING-LOOP SYSTEMS (HLS)

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicy Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC TR 63079, which is a Technical Report, has been prepared by IEC technical committee 29: Electroacoustics.

The text of this Technical Report is based on the following documents:

Enquiry draft	Report on voting
29/917/DTR	29/923/RVC

Full information on the voting for the approval of this Technical Report can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT - The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer. is a preview developed of the parties

INTRODUCTION

The performance of induction-loop systems is specified in IEC 60118-4, whereas IEC TR 63079 gives recommendations and guidance for their design, planning, installation, testing, operation and maintenance. Provisions for components of a system are given in IEC 62489-1. Methods of calculation and measurement of the magnetic field, in the context of human exposure, are given in IEC 62489-2.

This document takes the form of guidance and recommendations. It should not be quoted as if it were a specification and particular care should be taken to ensure that claims of compliance are not misleading.

nce mits re Any user claiming compliance with this document is expected to be able to justify any course of action that deviates from its recommendations.

CODE OF PRACTICE FOR HEARING-LOOP SYSTEMS (HLS)

1 Scope

This document, which is a Technical Report, gives recommendations for and guidance on the design, planning, installation, testing, operation and maintenance of a hearing-loop system (HLS) intended for communicating speech, music and/or other signals. It is mainly concerned with HLS for hearing enhancement, in which the signals are communicated to users of hearing aids equipped with magnetic pick-up coils.

This document does not apply to induction-loop systems which use a carrier frequency, nor to other systems for hearing enhancement purposes which do not use magnetic induction.

2 Normative references

There are no normative references in this document.

3 Terms, definitions, signs and symbols

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1 Terms and definitions

3.1.1

hearing-loop system

HLS

system including amplifier(s), microphones and/or other signal sources, in which magnetic fields are created by the flow of audio-frequency current in a conductor arranged in the form of one or more loops or a coil or solenoid

Note 1 to entry: The technical term for a hearing-loop system is "audio-frequency induction-lop system" (AFILS).

3.1.2

HLS for hearing enhancement

HLS in which the intended receivers are hearing aids or specially designed listening devices equipped with coils acting as magnetic antennas

3.1.3

direct-to-reverberant ratio

ratio, at a given point in the sound field, of the sound pressure due to the wanted sound source to the sound pressure due to reverberation

3.1.4

hearing aid

personal amplification system, worn entirely on the listener, which is designed to enable a person with impaired hearing to hear more easily