

Aerospace series - Passive UHF RFID tags intended for aircraft use

This document is a preview generated by EVS

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 4817:2012 sisaldab Euroopa standardi EN 4817:2012 ingliskeelset teksti.	This Estonian standard EVS-EN 4817:2012 consists of the English text of the European standard EN 4817:2012.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 16.05.2012.	Date of Availability of the European standard is 16.05.2012.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 35.240.60, 49.035

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:
Aru 10, 10317 Tallinn, Eesti; www.evs.ee; telefon 605 5050; e-post info@evs.ee

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:
Aru 10, 10317 Tallinn, Estonia; www.evs.ee; phone 605 5050; e-mail info@evs.ee

ICS 35.240.60; 49.035

English Version

**Aerospace series - Passive UHF RFID tags intended for aircraft
use**

Série aérospatiale - Tags passifs d'identification par
radiofréquence Ultra Haute Fréquence (RFID UHF) pour
usage aéronautique

Luft- und Raumfahrt - UHF Passiv RFID-Tags für
Luftfahrtverwendung

This European Standard was approved by CEN on 25 February 2012.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	6
4 General requirements	9
5 General configuration	10
6 Applicability.....	10
7 Requirements	10
Bibliography	15

Foreword

This document (EN 4817:2012) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by November 2012, and conflicting national standards shall be withdrawn at the latest by November 2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

The requirements for RFID tags to be used in the aerospace industry are very different from non-aviation uses. The parts identified by the RFID tags are high value items, which are often used for ten years or more. Reading and writing across a moderate distance, and over the life-spans of these tagged-parts, is expected to improve data accuracy and cost savings. Furthermore, the aerospace industry is subject to unique considerations regarding qualification, regulations, and safety, which are enforced by aviation authorities such as the EASA, FAA, etc.

These requirements, coupled with the relatively low manufacturing volumes, will drive up the per-part cost of tags developed for the aerospace industry. This will generate the need for a set of RFID tags specifically designed for use on aircraft. Adherence to this European Standard will decrease the development cost of these low-volume, high-capability RFID tags.

1 Scope

The scope of this European Standard is to:

- Provide a requirements document for RFID Tag Manufacturers to produce passive UHF tags for the Aerospace industry.
- Identify the minimum performance requirements specific to passive UHF tags used on aircraft parts, accessed only during ground operations.
- Specify the test requirements specific to passive UHF tags for airborne use, in addition to EUROCAE ED-14 / RTCA DO-160 latest issue compliance requirements separately called out in this document.
- Identify existing standards applicable to passive UHF tags.
- Provide a qualification standard for passive UHF tags which will use permanently-affixed installation on aircraft and aircraft parts.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained. All RFID applications must be compliant with local regulation in force (i.e. FCC for US, CEPT/ETSI for Europe).

ISO/IEC 18000-6, *Information technology — Radio frequency identification for item management — Part 6: Parameters for air interface communications at 860 MHz to 960 MHz* ¹⁾

ISO/IEC 18046-3, *Information technology — Radio frequency identification device performance test methods — Part 3: Test methods for tag performance* ¹⁾

ISO/IEC TR 18047-6, *Information technology — Radio frequency identification device conformance test methods — Part 6: Test methods for air interface communications at 860 MHz to 960 MHz* ¹⁾

DO-160 / ED-14, *Environmental Conditions and Test Procedures for Airborne Equipment* ²⁾

ATA SPEC 2000, *E-Business Specification for Materials Management* ³⁾

1) Published by: ISO International Organization for Standardization <http://www.iso.ch/>.

2) Published by: International Radio Technical Commission for Aeronautics <http://www.rtca.com/> and by EUROCAE Regional (EU) EUROpean Organisation for Civil Aviation Equipment <http://www.eurocae.org/>.

3) Published by: Air Transport Association Publications.

MIL-STD-810, *Department of Defense Test Method Standard for Environmental Engineering Considerations and Laboratory Tests* ⁴⁾

FAR 14 CFR 25, *Aeronautics and Space — Part 25: Airworthiness standards: Transport Category Airplanes*

AC 20-162, *Airworthiness Approval and Operational Allowance of RFID Systems*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

AEROSPACE APPLICATIONS

used on products created for the aerospace industry

3.2

AIRBORNE USE

used on aircraft while in flight—as opposed to Ground Service Equipment, which is used on aircraft, but only while, the aircraft is on the ground

3.3

ATA: AIR TRANSPORT ASSOCIATION

airline trade association whose purpose is to foster a business and regulatory environment that ensures safe and secure air transportation. ATA coordinates standards-creation in support of this purpose.

3.4

BACKSCATTER

the Radio Frequency (RF) energy reflected by the tag to transmit information to the interrogator. The RFID tag's chip and antenna modulates the incident energy and reflects it back (same orientation but opposite direction). Backscatter is what the interrogator device "reads." An inert piece of aluminium will reflect RF energy, but in the absence of modulation, it is "reflection", not "backscatter."

3.5

BAP

Battery Assisted Passive — RFID tags that have an on-board battery to power the electronics in the tag, minimizing the power required from the interrogator Radio Frequency Beam. They backscatter like a passive UHF tag only when they are interrogated. BAP tags have greater read ranges than purely passive tags.

3.6

BAR-CODE

a standard method of identifying items based on lines of varying widths and spacing that are visually read by a scanner

3.7

BLINK RATE

the rate at which an active Chip/Tag sends out a signal to look for, this can be adjusted from hours to seconds depending on the application and desired battery life of the RFID tag

4) Published by: DoD National (US) Mil. Department of Defense <http://www.defenselink.mil/>.