RAUDTEEALASED RAKENDUSED. PIDURDAMINE. PIDURIKLOTSID

Railway applications - Braking - Brake blocks



EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 16452:2015+A1:2019 sisaldab Euroopa standardi EN 16452:2015+A1:2019 ingliskeelset teksti.	This Estonian standard EVS-EN 16452:2015+A1:2019 consists of the English text of the European standard EN 16452:2015+A1:2019.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 06.03.2019.	Date of Availability of the European standard is 06.03.2019.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 45.040, 45.060.01

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega: Koduleht <u>www.evs.ee</u>; telefon 605 5050; e-post <u>info@evs.ee</u>

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 16452:2015+A1

March 2019

ICS 45.040; 45.060.01

Supersedes EN 16452:2015

English Version

Railway applications - Braking - Brake blocks

Applications ferroviaires - Freinage - Semelles de frein

Bahnanwendungen - Bremse - Bremsklotzsohlen

This European Standard was approved by CEN on 28 February 2015 and includes Amendment 1 approved by CEN on 21 December 2018.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents Page

Forew	vord	8
Intro	ductionduction	9
1	Scope	10
2	Normative references	10
3	Terms and definitions	11
4	Abbreviations	13
5	Overall requirements	
5.1	Deviations from requirements	13
5.2	Functions	
5.3	Operational criteria	14
5.3.1	Friction material performance	14
5.3.2	Service performance	14
5.3.3	Brake block characteristics	15
6	Acceptance procedure	
6.1	Brake block performance requirements	
6.1.1	General	
6.1.2	Category A	
6.1.3	Category B	
6.1.4	Category C	
6.2	Approval test requirements	
6.3	Dynamometer specification	
7	Category A requirements	
7.1	Brake block characteristics	
7.1.1	Standard design	19
7.1.2	Brake block characterization test	19
7.1.3	Brake block mechanical characteristics for service operation	20
7.2	Dynamic friction performance	20
7.2.1	Generic requirements for assessment process	
7.2.2	Bedded and non bedded performance	
7.2.3	Variation in mean coefficient of friction in dry condition for a brake to rest	21
7.2.4	Mean friction coefficient variation under wet conditions	21
7.2.5	Mean friction coefficient variation at high initial temperature	21
7.2.6	Mean friction coefficient variation after simulation of a downhill brake application	21
7.2.7	Instantaneous friction coefficient variation during simulation of a downhill brake	21
720	applicationVariation in instantaneous friction for a brake to rest	
7.2.8		
7.3	Static friction coefficient	
7.4	Extreme winter conditions (freight wagons)	
7.4.1	General	
7.4.2	A) Dynamometer test	
7.4.3	Train brake test	
7.5	Locked brake (fusibility)	
7.5.1	Generic prescriptions	
7.5.2	Specific prescriptions for freight wagons	26

8	Category B requirements	
8.1	Vehicle brake test	
8.2 8.3	Dynamometer wear test (friction couple) Dynamic friction performance	
8.4	In service assessment	
9	Category C requirements	28
9.1	Metal pick up	
9.2	Influence on track circuit operation (shuntage)	28
10	Environmental issues	
10.1 10.2	General	
10.2	NoiseOdour	
10.4	Smoke, fumes and sparkling	
10.5	Recycling and disposal	29
11	Marking	29
Annex	A (normative) Summary of Dynamometer test programs and acceptance criteria	30
Annex	B (normative) General requirements for conducting dynamometer test programmes	32
B.1	General	32
B.2	Rotation and ventilation conditions	
B.3	Brake application timing t _s	
B.4	Bedding	
B.5	Wear	
B.6	Roughness index of the wheel tread	
B.7	Interruption of the tests	
B.8	Temperatures	
B.9	Wet conditions	
B.10	Test of simulation of downhill	34
B.11	Test wheels	34
Annex	C (normative) Composite brake blocks (K) (2Bg – 2Bgu) – Demonstration of friction properties for S and SS (S/SS) – braked freight wagons ($v_{\rm max}$ = 120 km/h)	35
C.1	Program for performance tests	
C.2	Program for simulation brake assessment	
C.3	Dispersion range of mean friction coefficients	42
C.4	Dispersion range of instantaneous friction coefficients	46
Annex	D (normative) Composite brake blocks (LL) – Demonstration of friction properties for S and SS (S/SS) – braked freight wagons (v_{max} = 120 km/h)	
D.1	Program for performance tests	47
D.2	Program for simulation brake assessment	52
D.3	Dispersion range of mean friction coefficients	54
D.4	Dispersion range of instantaneous friction coefficients	56

Anne	ex E (normative) Composite brake blocks (K) (1Bg)- Demonstration of friction properties for S and SS (S/SS) - braked freight wagons ($v_{max} = 120 \text{ km/h}$)	57
E.1	Program for performance tests	57
E.2	Dispersion range of mean friction coefficients	60
E.3	Dispersion range of instantaneous friction coefficients	62
Anne	ex F (normative) Composite brake blocks (L) – Demonstration of friction properties for extra tread brake of coach	63
F.1	Program for performance tests	63
F.2	Program for simulation brake assessment	67
F.3	Dispersion range of mean friction coefficients in dry condition	68
F.4	Dispersion range of mean friction coefficients in wet condition	69
F.5	Dispersion range of instantaneous friction coefficients	70
Anne	ex G (normative) Composite brake blocks (K) – Demonstration of friction properties for locomotives	72
G.1	Program for performance tests	72
G.2	Program for simulation brake assessment	76
G.3	Dispersion range of mean friction coefficients in dry condition	77
G.4	Dispersion range of mean friction coefficients in wet condition	78
G.5	Dispersion range of instantaneous friction coefficients	79
Anne	ex H (normative) Composite brake blocks (K) – Demonstration of friction properties for EMU – DMU	
H.1	Program for performance tests	81
H.2	Program for simulation brake assessment	86
Н.3	Dispersion range of mean friction coefficients in dry condition	87
H.4	Dispersion range of mean friction coefficients in wet condition	88
H.5	Dispersion range of instantaneous friction coefficients	89
Anne	ex I (normative) Composite brake blocks (K) - Demonstration of friction properties for High speed train (motor bogie)	
I.1	Program for performance tests	91
I.2	Program for simulation brake assessment	94
I.3	Dispersion range of mean friction coefficients in dry condition	95
I.4	Dispersion range of mean friction coefficients in wet condition	97
I.5	Dispersion range of instantaneous friction coefficients	98
Anne	ex J (🗗 normative 街) Dynamometer test program – Generic test program	
J.1	General	100
J.2	Generic test program	100
J.3	Definitions	104
I.4	(A) Values to be determined in order to define the area of use	.104

J.5	Al Principle of assessment and pass/fail criteria	. 106
Annex	K (normative) Dynamometer Test program to detect the formation of metal pick-up at the brake block	. 107
K.1	Test program for freight wagons with brake blocks type K and LL	. 107
K.2	Test program for locomotives with brake blocks type K	. 109
К.3	Test program for EMU - DMU with brake blocks type K	. 112
K.4	Test program for High speed train with brake blocks type K	. 115
Annex	L (normative) Dynamometer test program to demonstrate the extreme winter braking properties	. 118
L.1	Test program for freight wagons with brake blocks type K	. 118
L.2	Test program for freight wagons with brake blocks type LL	. 120
L.3	Specific requirements for conducting Test Programs L.1 and L.2	
L.4	Process of assessment and past fail criteria for test programs L.1 and L.2	. 122
L.5	Generic flow chart to perform test program	. 123
L.6	Detailed flow chart to perform test program (example brake block K)	. 124
Annex	M (normative) Test run to demonstrate the extreme winter braking properties brake blocks K - LL for freight wagons	
M.1	♠ Test program to demonstrate the braking properties under severe snowy conditions	. 127
M.2	Values to be determined in order to define the area of use	. 130
M.3	Assessment of measurement data and pass/fail criteria	. 130
Annex	x N (normative) Dynamometer Test program to simulate "Locked brake"	. 132
N.1	Test program for freight wagons with brake blocks type K and LL	. 132
N.2	Test program for locomotives with brake blocks type K	. 133
N.3	Test program for EMU - DMU with brake blocks type K	. 134
N.4	Test program for High speed train with brake blocks type K	. 135
Annex	o (normative) Dynamometer test program to demonstrate the compatibility with track circuits	. 136
0.1	General	. 136
0.2	Short description of the measuring method used	. 136
0.3	Schematic diagram of test set up	. 136
0.4	Flow chart to perform test program	. 138
0.5	Preparation of the disc and the rollers	. 138
0.6	Preparation of the samples of brake block	. 139
0.7	Contamination of disc	. 139
0.8	Measurements	. 140
0.9	Assessment of the results	
Annex	x P (informative) Vehicle test to demonstrate the compatibility with track circuits	143

P.1	General	143
P.2	Test conditions	143
P.3	Assessment of results	144
P.4	Pass/fail criteria	145
Annex	x Q (informative) Dynamometer test program – Determination of static friction coefficient	147
Q.1	(A1) Generic test program for freight wagons with brake blocks type K and LL	147
Q.2	A) Specific test program for S and/or SS freight wagons with brake blocks type K and LL (A)	147
Q.3	Test program for EMU - DMU and Locomotive with brake blocks type K	149
Q.4	Test program for High speed train with brake blocks type K	150
Q.5	A ₁) Specific Requirements for conducting dynamometer test programmes Q.1 to Q.4 (A ₁)	150
Annex	x R (informative) Dynamometer test program – Simulation of service conditions for freight wagons	
R.1	Simulation freight wagon with brake block type K 2Bgu	153
R.2	Simulation freight wagon with brake block type LL 2Bgu	
Annex	x S (normative) Interchangeability, rejection lugs and critical dimensions	158
Annex	x T (normative) Brake block shear and flexural strength tests	161
T.1	General	161
T.2	Shear strength test	
T.3	Flexural strength test	162
Anne	x U (normative) Limitation of permissible mechanical damage of brake block	164
U.1	General	
U.2	Cracked through to back-plate	164
U.3	Crumbling of the friction material	165
U.4	Metal pick-up	
U.5	Detachment from back-plate	
U.6	Cracks in the direction of wheel circumference	
U.7	Detachment of the friction material	166
U.8	Interface with the brake block holder	167
Annex	x V (normative) In service assessment of brake block	168
V.1	General	168
V.2	Freight wagon	168
V.3	Coach	169
V.4	Locomotive	169
V.5	EMU-DMU	170
V.6	High speed train	170

V.7	Description of areas to be monitored and additional measures	171
V.8	Pass/fail criteria	172
Anne	x W (informative) Complementary definitions and abbreviations	173
Anne	x X (informative) Brake block characterization test	175
Anne	ex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC aimed to be covered	176
Biblic	ography	179
	ography	

Foreword

This document (EN 16452:2015+A1:2019) has been prepared by Technical Committee CEN/TC 256 "Railway applications", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2019, and conflicting national standards shall be withdrawn at the latest by September 2019.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document includes Amendment 1 approved by CEN on 28 October 2018.

This document supersedes At EN 16452:2015 At.

The start and finish of text introduced or altered by amendment is indicated in the text by tags (A).

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive 2008/57/EC.

For relationship with EU Directive 2008/57/EC, see informative Annex ZA, which is an integral part of this document.

Compared to the previous edition, the following changes have been made:

- a) 7.3 "Static friction coefficient" has been modified;
- b) 7.4.2 "Dynamometer test" has been modified;
- c) 7.5.1 "Generic prescriptions" has been modified;
- d) 7.4.3 "Train brake test" has been modified;
- e) Annex A "Summary of Dynamometer test programs and acceptance criteria" has been modified;
- f) Annex J "Dynamometer test program Generic test program" has been modified;
- g) Annex M "Test run to demonstrate the extreme winter braking properties brake blocks K LL for freight wagons" has been modified;
- h) Annex Q "Dynamometer test program Determination of static friction coefficient" has been modified;
- i) Annex T "Brake block shear and flexural strength tests" has been modified;
- j) Annex ZA has been updated.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

For environmental reasons (reduction of rolling noise), this European Standard does not cover cast iron brake block requirements, although cast iron brake block technology is still widely used in Europe. Cast iron has already been replaced by composite materials for new rolling stock builds and major steps have been taken by EEC (TSI) and UIC in 2004 to accelerate the change from cast iron to composite materials.

When published this European Standard will replace the current UIC requirements for technical approval of brake blocks. The requirements of this EN are based on the state of art form UIC leaflet and a European project "Euro Rolling Silently".

1 Scope

This European Standard gives the requirements for the design, dimensions, performance, and testing of a brake block (otherwise known as brake shoe insert) that acts on the wheel tread as part of a tread brake system. This European Standard does not cover cast iron brake block requirements.

This European Standard is applicable to brake blocks of either "K", "L", or "LL" friction level designed to be fitted to tread braked rail vehicles.

This European Standard contains the requirements for interfacing the brake block with the rail vehicle, the testing procedures in order to confirm that it satisfies the basic safety and technical interchangeability requirements, the material control procedures to ensure product quality, reliability and conformity and considers health and environmental needs.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13452-1, Railway applications — Braking — Mass transit brake systems — Part 1: Performance requirements

EN 13452-2, Railway applications — Braking — Mass transit brake systems — Part 2: Methods of test

EN 13715, Railway applications — Wheelsets and bogies — Wheels — Tread profile

EN 13979-1:2003+A2:2011, Railway applications — Wheelsets and bogies — Monobloc wheels — Technical approval procedure — Part 1: Forged and rolled wheels

EN 14033-1, Railway applications — Track — Railbound construction and maintenance machines — Part 1: Technical requirements for running

EN 14033-2:2008+A1:2011, Railway applications — Track — Railbound construction and maintenance machines — Part 2: Technical requirements for working

EN 14198, Railway applications — Braking — Requirements for the brake system of trains hauled by a locomotive

EN 14478, Railway applications — Braking — Generic vocabulary

EN 15179, Railway applications — Braking — Requirements for the brake system of coaches

EN 15313, Railway applications — In-service wheelset operation requirements — In-service and off-vehicle wheelset maintenance

EN 15663, Railway applications — Definition of vehicle reference masses

EN 15734-1, Railway applications — Braking systems of high speed trains — Part 1: Requirements and definitions

EN 15734-2, Railway applications — Braking systems of high speed trains — Part 2: Test methods

EN 16185-1, Railway applications — Braking systems of multiple unit trains — Part 1: Requirements and definitions

EN 16185-2, Railway applications — Braking systems of multiple unit trains — Part 2: Test methods

EN 50126-1, Railway applications — The specification and demonstration of Reliability, Availability, Maintainability and Safety (RAMS) — Part 1: Basic requirements and generic process

EN ISO 4287, Geometrical product specifications (GPS) — Surface texture: Profile method — Terms, definitions and surface texture parameters (ISO 4287)

EN ISO 4288, Geometrical product specifications (GPS) — Surface texture: Profile method — Rules and procedures for the assessment of surface texture (ISO 4288)

UIC 544-1, *Brakes — Braking power*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 14478 and the following apply.

3.1

application parameter

configuration parameters refer to vehicle mass, operating speed, wheel diameter, braked mass, brake block configuration, brake block force

3.2

Bg configuration

one brake block 320 mm per brake block holder

Note 1 to entry: Bg comes from UIC and means "Bremsklotzsohle geteilt".

3.3

Bgu configuration

two brake blocks 250 mm per brake block holder

Note 1 to entry: Bgu comes from UIC and means "Bremse geteilt mit unterteilter Sohle".

3.4

brake block

stator part of a tread brake adapted to generate a friction force when engaged with a wheel tread

3.5

brake block force

force with which the brake block is made to come into contact with the wheel tread

3.6

friction material

consumable portion of the brake block that acts on the wheel tread in order to provide the specified brake performance