

**Televisiooni-, heli- ja interaktiivse multimeedia signaalide kaabeljaotussüsteemid. Osa 2: Seadmete elektromagnetiline ühilduvus**

**Cable networks for television signals, sound signals and interactive services - Part 2: Electromagnetic compatibility for equipment**

## EESTI STANDARDI EESSÕNA

## NATIONAL FOREWORD

See Eesti standard EVS-EN 50083-2:2012 sisaldab Euroopa standardi EN 50083-2:2012 ingliskeelset teksti.	This Estonian standard EVS-EN 50083-2:2012 consists of the English text of the European standard EN 50083-2:2012.
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 02.03.2012.	Date of Availability of the European standard is 02.03.2012.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile [standardiosakond@evs.ee](mailto:standardiosakond@evs.ee).

ICS 33.060.40

Võtmesõnad: electromagnetic compatibility, multimedia, television,

### Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega:  
Aru 10, 10317 Tallinn, Eesti; [www.evs.ee](http://www.evs.ee); telefon 605 5050; e-post [info@evs.ee](mailto:info@evs.ee)

### The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:  
Aru 10, 10317 Tallinn, Estonia; [www.evs.ee](http://www.evs.ee); phone 605 5050; e-mail [info@evs.ee](mailto:info@evs.ee)

**Cable networks for television signals, sound signals and interactive services -  
Part 2: Electromagnetic compatibility for equipment**

Réseaux de distribution par câbles pour  
signaux de télévision, signaux de  
radiodiffusion sonore et services  
interactifs -  
Partie 2: Compatibilité électromagnétique  
pour les matériels

Kabelnetze für Fernsehsignale,  
Tonsignale und interaktive Dienste -  
Teil 2: Elektromagnetische Verträglichkeit  
von Geräten

This European Standard was approved by CENELEC on 2011-12-21. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Management Centre: Avenue Marnix 17, B - 1000 Brussels**

## Contents

<b>Contents</b>	<b>2</b>
<b>Foreword</b>	<b>5</b>
<b>1 Scope</b>	<b>7</b>
1.1 General	7
1.2 Specific scope of EN 50083-2	7
<b>2 Normative references</b>	<b>9</b>
<b>3 Terms, definitions, symbols and abbreviations</b>	<b>10</b>
3.1 Terms and definitions	10
3.2 Symbols	15
3.3 Abbreviations	16
<b>4 Methods of measurements</b>	<b>16</b>
4.1 General operating conditions	16
4.2 Disturbance voltages from equipment	17
4.3 Radiation from active equipment	18
4.4 Immunity of active equipment	28
4.5 Screening effectiveness of passive equipment	40
4.6 Electrostatic discharge immunity test for active equipment	42
4.7 Electrical fast transient/burst immunity test for AC power ports	42
4.8 Methods of measurement for telecom signal ports of multimedia network equipment	42
4.9 Measurement of indoor receiving antennas for broadcast signals	42
<b>5 Performance requirements</b>	<b>43</b>
5.1 General	43
5.2 Disturbance voltages from equipment	43
5.3 Radiation	44
5.4 Immunity of active equipment	45
5.5 Screening effectiveness of passive equipment	51
5.6 Electrostatic discharge immunity test for active equipment	52
5.7 Electrical fast transient/burst immunity test for AC power ports	52
5.8 Performance requirements for telecom signal ports of multimedia network equipment	52
5.9 Applicability of EMC performance requirements and methods of measurement to different types of equipment	52
<b>Annex ZZ (informative) Coverage of Essential Requirements of EU Directives</b>	<b>55</b>
<b>Bibliography</b>	<b>56</b>

## Figures

Figure 1 - Measurement set-up for radiation measurements in the frequency range 5 MHz to 30 MHz using the "coupling unit" method.....	21
Figure 2 - Absorbing clamp method (30 MHz to 1 000 MHz) .....	23
Figure 3 - Example of general measurement set-up .....	24
Figure 4 - Example of measurement set-up for measurements on the input port of an active equipment .....	24
Figure 5 - Measurement set-up for the "substitution" radiation method – First measurement step .....	26
Figure 6 - Measurement set-up for the "substitution" radiation method – Second measurement step .....	27
Figure 7 - Frequency allocation for out-of-band immunity measurement of active equipment with nominal upper frequency limit $\leq 1\,000$ MHz.....	30
Figure 8 - Frequency allocation for out-of-band immunity measurement of active equipment with nominal lower frequency limit $\geq 950$ MHz .....	30
Figure 9 - Frequency allocation for in-band immunity measurement of active equipment with nominal upper frequency limit $\leq 1\,000$ MHz .....	33
Figure 10 - Frequency allocation for in-band immunity measurement of active equipment with nominal lower frequency limit $\geq 950$ MHz .....	33
Figure 11 - Measurement set-up for internal immunity test.....	35
Figure 12 - Levels of wanted and unwanted signals for the internal immunity of FSS receiving outdoor units .....	38
Figure 13 - Levels of wanted and unwanted signals for the internal immunity of BSS receiving outdoor units .....	39
Figure 14 - Levels of unwanted signals for the internal immunity of active equipment in Band I (47 MHz to 68 MHz).....	47
Figure 15 - Levels of unwanted signals for the internal immunity of active equipment in Band II (87,5 MHz to 108 MHz) .....	48
Figure 16 - Levels of unwanted signals for the internal immunity of active equipment in Band III (174 MHz to 230 MHz) .....	49
Figure 17 - Levels of unwanted signals for the internal immunity of active equipment in Band IV/V (470 MHz to 862 MHz) .....	50

## Tables

Table 1 - Port structure of different network equipment .....	8
Table 2 - Limits of mains terminal disturbance voltage .....	43
Table 3 - Limits of input terminal disturbance voltages for equipment directly connected to receiving antennas .....	44
Table 4 - Limits of input terminal disturbance voltages for equipment directly connected to satellite outdoor units .....	44
Table 5 - Limits of radiated disturbance power .....	44
Table 6 - Limit of local oscillator terminal power .....	45
Table 7 - Limits of out-of-band immunity .....	45
Table 8 - Limits of in-band immunity .....	46
Table 9 - Test specification for internal immunity .....	46
Table 10 - Limits of immunity to image frequency signals in terms of image suppression ratio .....	51
Table 11 - Limits of screening effectiveness of passive equipment within the nominal frequency ranges .....	51
Table 12 - Test specifications for electrostatic discharge immunity test for active equipment .....	52
Table 13 - Test specifications for electrical fast transient/burst immunity test .....	52
Table 14 - Port types and environmental conditions for EMC performance requirements and methods of measurement .....	52
Table 15 - Emission parameters .....	53
Table 16 - Immunity and screening effectiveness parameters .....	54

Preview generated by EVS

## Foreword

This document (EN 50083-2:2012) has been prepared by CLC/TC 209 "Cable networks for television signals, sound signals and interactive services".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2012-12-21
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2013-06-21

This document supersedes EN 50083-2:2006.

EN 50083-2:2012 includes the following significant technical changes with respect to EN 50083-2:2006:

### 1. Frequency extensions

- 1.1. The upper frequency limit of conventional cable network equipment was extended from 862 MHz to 1 000 MHz due to market demands.
- 1.2. The first intermediate frequency range (1<sup>st</sup> IF range) for satellite signal transmission was extended to cover now frequencies from 950 MHz up to 3 500 MHz.
- 1.3. The methods of measurement and the EMC requirements in the overlapping frequency range from 950 MHz to 1 000 MHz were allocated in relation to the upper frequency limit, 1 000 MHz, respectively the lower frequency limit, 950 MHz, of the relevant equipment under test.

### 2. New EMC environment in the 800 MHz band

- 2.1. The European Commission has requested CENELEC and ETSI to draft immunity requirements for equipment, to protect against disturbance from the new wireless service in the 790-862 MHz band.
- 2.2. A CENELEC/ETSI Joint Working Group "Digital Dividend" was formed to describe the new EMC environment and to advise on appropriate test methods and limits.
- 2.3. EN 50083-2 is the standard specifying immunity requirements for active and passive cable network equipment.
- 2.4. The method of measurement and the requirements for in-band immunity were extended taking into account this new EMC environment due to the allocation of broadband wireless services in the frequency band 790 MHz to 862 MHz. As a consequence, the limits of in-band immunity were specified for analogue and additionally for digital signals in this frequency range.
- 2.5. Consequently it is recommended, that, where cable networks and wireless networks coexist, only the transmission of digitally modulated signals should be used in the frequency range 790 MHz to 862 MHz.
- 2.6. For passive equipment, Class A and Class B specifications were kept in the standard but a note was added recommending that only Class A equipment should be used in the planning and implementation of new networks.

### 3. Indoor antennas

The methods of measurement for all kinds of indoor antennas were combined in the new 4.9.

#### 4. Bibliography

A Bibliography was added at the end of the document referencing i.a. to CEPT Report 30 on *“The identification of common and minimal (least restrictive) technical conditions for 790-862 MHz for the digital dividend in the European Union”*.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For the relationship with EU Directive(s) see informative Annex ZZ, which is an integral part of this document

---



# 1 Scope

## 1.1 General

Standards of the EN 50083 and EN 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television signals, sound signals and their associated data signals and for processing, interfacing and transmitting all kinds of signals for interactive services using all applicable transmission media.

This includes

- CATV-networks <sup>1)</sup>,
- MATV-networks and SMATV-networks,
- individual receiving networks

and all kinds of equipment, systems and installations installed in such networks.

The extent of this standardisation work is from the antennas and/or special signal source inputs to the headend or other interface points to the network up to the terminal input.

The standardisation of any user terminals (i.e., tuners, receivers, decoders, multimedia terminals, etc.) as well as of any coaxial, balanced and optical cables and accessories thereof is excluded.

## 1.2 Specific scope of EN 50083-2

This European Standard

- applies to the radiation characteristics and immunity to electromagnetic disturbance of EM-active equipment (active and passive equipment) for the reception, processing and distribution of television, sound and interactive multimedia signals as dealt with in the following parts of EN 50083 or EN 60728 series:
  - EN 60728-3 "Active wideband equipment for cable networks";
  - EN 60728-4 "Passive wideband equipment for coaxial cable networks";
  - EN 60728-5 "Headend equipment";
  - EN 60728-6 "Optical equipment";
- covers the following frequency ranges:
 

disturbance voltage injected into the mains	150 kHz to 30 MHz;
radiation from active equipment	5 MHz to 25 GHz;
immunity of active equipment	150 kHz to 25 GHz <sup>2)</sup> ;
screening effectiveness of passive equipment	5 MHz to 3,5 GHz (25 GHz) <sup>3)</sup> ;

<sup>1)</sup> 'CATV-networks' encompasses the HFC networks used nowadays to provide telecommunications services, voice, data, audio and video both broadcast and narrowcast.

<sup>2)</sup> For „Inband immunity of active equipment" and „Out-of-band immunity of active equipment, no requirements apply at present for the frequency range 3,5 GHz to 25 GHz. Methods of measurement and limits are investigated for inclusion in a future amendment or revised edition.

<sup>3)</sup> For "Screening effectiveness of passive equipment", no requirements apply at present for the frequency range 3,5 GHz to 25 GHz. Methods of measurement and limits are investigated for inclusion in a future amendment or revised edition.

- specifies requirements for maximum allowed radiation, minimum immunity and minimum screening effectiveness;
- describes test methods for conformance testing.

No measurement needs to be performed at frequencies where no requirement is specified.

Due to the fact that cable networks, the former cabled distribution systems for television and sound signals are more and more used for interactive services, these networks may incorporate also equipment that carry besides the cable network equipment ports also one or more telecom signal port(s). This equipment shall be named as "multimedia network equipment".

The EMC behaviour of cable network equipment, telecommunication network equipment and multimedia network equipment may be described by the following port structure (Table 1):

**Table 1 - Port structure of different network equipment**

Port name	Cable network equipment	Telecommunication network equipment	Multimedia network equipment
Enclosure	X	X	X
Earth	X	X	X
AC/DC power supply	X	X	X
Control (e.g. alarm)	X	X	X
Antenna input port	X		X
RF network port	X		X
Telecom signal port		X	X

Table 1 shows that cable network equipment and telecommunication network equipment have four common ports and, respectively, two and one individual ports. Multimedia network equipment carry besides the common ports an antenna input port and/or a RF network port as well as a telecom signal port.

The electromagnetic compatibility requirements for "telecommunication network equipment only" are standardised in ETSI EN 300 386 (mainly) and in ETSI EN 301 489-4, those for "cable network equipment only" are given in this EN 50083-2.

Equipment for multimedia networks of the above-mentioned type has to work under the same EMC conditions as equipment that is falling under the cable network and the telecommunication network EMC-standards. Due to the fact, that this equipment has to work in close proximity, e.g. in the same operating room, the EMC environmental conditions for all three types of equipment are the same.

This means that multimedia network equipment has to fulfil the EMC requirements of one of the above mentioned standards and in addition the EMC requirements, laid down in the other EMC standard, for the additional port, by which it is connected to the other network.

By this procedure it is ensured that multimedia network equipment fulfils the EMC conditions of one of the above mentioned networks and will neither disturb the respective other system nor will be disturbed by the respective other system via the connecting port.

Coaxial cables for cable networks do not fall under the scope of this standard; reference is made to EN 50117 series. Coaxial cable assemblies for radio and TV receivers (receiver leads) do not fall under the scope of this standard; reference is made to EN 60966 series. Requirements for the electromagnetic compatibility of receiver leads are laid down in EN 60966-2-4, EN 60966-2-5 and EN 60966-2-6.

This European Standard also covers indoor receiving antennas for broadcast signals for which the requirements and the applicable methods of measurement are limited to the emission and the electrostatic discharge phenomena.

Standardisation in the field of "Electromagnetic compatibility" for any broadcast terminals (e.g. tuners, receivers, decoders, etc.) is covered by EN 55013 and EN 55020 and for multimedia terminals by EN 55022 and EN 55024.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 55013	2001	Sound and television broadcast receivers and associated equipment – Radio disturbance characteristics – Limits and methods of measurement
+A1	2003	(CISPR 13:2001+A1:2003+A2:2006)
+A2	2006	
+IS1	2009	
EN 55016-1-1	2010	Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus (CISPR 16-1-1:2010 + corrigendum 2011 + A1:2010)
+A1	2010	
EN 55020	2007	Sound and television broadcast receivers and associated equipment – Immunity characteristics – Limits and methods of measurement
+IS1	2009	(CISPR 20:2006)
+IS2	2010	
+A11	2011	
EN 60728-3	2011	Cable networks for television signals, sound signals and interactive services – Part 3: Active wideband equipment for cable networks (IEC 60728-3: 2010)
EN 61000-3-2	2006	Electromagnetic compatibility (EMC) – Part 3-2: Limits – Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)
+A1	2009	(IEC 61000-3-2:2005 + A1:2008 + A2:2009)
+A2	2009	
EN 61000-4-2	2009	Electromagnetic compatibility (EMC) – Part 4-2: Testing and measurement techniques – Electrostatic discharge immunity test (IEC 61000-4-2:2008)
EN 61000-4-3	2006	Electromagnetic compatibility (EMC) – Part 4-3: Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test
+A1	2008	(IEC 61000-4-3:2006 +A1:2007 + A2:2010)
+A2	2010	
+IS1	2009	
EN 61000-4-4	2004	Electromagnetic compatibility (EMC) – Part 4-4: Testing and measurement techniques – Electrical fast transient/burst immunity test (IEC 61000-4-4:2004 + A1:2010)
+A1	2010	
EN 61000-4-6	2009	Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields (IEC 61000-4-6:2008)
EN 61000-6-1	2007	Electromagnetic compatibility (EMC) – Part 6-1: Generic standards – Immunity for residential, commercial and light-industrial environments (IEC 61000-6-1:2005)
EN 61079-1	1993	Methods of measurement on receivers for satellite broadcast transmissions in the 12 GHz band – Part 1: Radiofrequency measurements on outdoor units (IEC 61079-1:1992)

ETSI EN 300 386 V1.5.1	2010	Electromagnetic compatibility and Radio spectrum Matters (ERM); Telecommunication network equipment; ElectroMagnetic Compatibility (EMC) requirements
IEC 60050-161	1990	International Electrotechnical Vocabulary (IEV) Chapter 161: Electromagnetic compatibility
+A1	1997	
+A2	1998	

### 3 Terms, definitions, symbols and abbreviations

#### 3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-161:1990 and the following apply.

Note 1 to entry: The most important definitions of IEC 60050-161:1990 are repeated hereafter with the IEC-numbering given in brackets. In addition, some more specific definitions, used in this standard, are listed.

##### 3.1.1

##### **AC power port**

point at which a cable for the AC power supply is connected to the equipment

##### 3.1.2

##### **active equipment**

equipment (e.g. amplifiers, converters, etc.), performing signal processing by means of external or internal power supply in a certain frequency range

##### 3.1.3

##### **antenna input port**

point at which the equipment under test is directly connected to the receiving antenna(s)

##### 3.1.4

##### **band**

nominal operating frequency range of the equipment

##### 3.1.5

##### **burst** (of pulses or oscillations)

sequence of a limited number of distinct pulses or an oscillation of limited duration

[SOURCE: IEC 161-02-07]

##### 3.1.6

##### **cable network equipment**

equipment from which cable networks for television signals, sound signals and interactive services are built

Note 1 to entry: Examples of typical cable network equipment could be found in EN 60728-3, EN 60728-4, EN 60728-5, EN 60728-6 and EN 60728-10.

##### 3.1.7

##### **carrier-to-interference ratio**

minimum level difference measured at the output of an active equipment between the wanted signal and

- intermodulation products of the wanted signal and/or unwanted signals generated due to non-linearities,
- harmonics generated by an unwanted signal,
- unwanted signals that have penetrated into the operating frequency range,