
**Photography — Electronic still-picture
imaging — Noise measurements**

*Photographie — Imagerie des prises de vue électroniques —
Mesurages du bruit*



This document is a preview generated by EBS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test conditions	3
4.1 General	3
4.2 Illumination	3
4.2.1 Characteristics	3
4.2.2 Daylight illumination	3
4.2.3 Tungsten illumination	3
4.2.4 Uniformity of illumination and reflection test chart illumination geometry	4
4.2.5 Light source amplitude variations	4
4.3 Temperature and relative humidity	4
4.4 White balance	4
4.5 Infrared (IR) blocking filter	4
4.6 Photosite integration time	4
4.7 Colour noise weighting	4
4.8 Compression	5
5 Noise measurement procedures	5
5.1 General	5
5.1.1 Uniform field noise measurement methods	5
5.1.2 Test densities	5
5.1.3 Adjustment of illumination, test density placement and camera lens focus	6
5.2 Measurement of a DSC having a removable lens	6
5.3 Measurement of a DSC having manual exposure control	7
5.4 Measurement of a DSC using a test chart	7
6 Calculation and reporting of results	9
6.1 General	9
6.2 Signal-to-noise ratios — large area	9
6.3 DSC dynamic range	12
Annex A (normative) Noise component analysis	14
Annex B (normative) Visual noise measurements	18
Annex C (informative) Removing low frequency variations from the image data	27
Annex D (informative) Procedure for determining signal-to-noise ratio	29
Annex E (informative) Practical viewing conditions for various output media	30
Bibliography	31

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 42, *Photography*.

This third edition cancels and replaces the second edition (ISO 15739:2013), of which it constitutes a minor revision with the addition of IEC 61966-2-1:1999 to [Clause 2](#) and changes in [Annex B](#).

Introduction

Noise is an important attribute of electronic photographic systems. Camera noise measurements described in this document are performed in the digital domain, using digital analysis techniques. Since the noise performance of an image sensor may vary significantly with exposure time and operating temperature, these operating conditions are specified. The visibility of noise to human observers depends on the magnitude of the noise, the apparent tone of the area containing the noise and the spatial frequency of the noise. The magnitude of the noise present in an output representation depends on the noise present in the stored image data and the contrast amplification or gain applied to the data in producing the output. The noise visibility is different for the luminance (or monochrome) channel and the colour (or colour difference) channels. Therefore, this document accounts for these factors in measuring and reporting the camera noise measurements. [Annex A](#) specifies the method for determining the components of the digital camera noise from a number of samples. The perceptibility of noise in an image can vary depending on the viewing distance, spatial frequency, density, colour and viewing conditions. [Annex B](#) describes a procedure for measuring the visual noise level using a human visual model as a method for weighting the spectral components of the noise. A method for removing low frequency variations in the patch data resulting, for example, from luminance shading is given in [Annex C](#). A recommended step-by-step procedure for determining the signal-to-noise ratio and incremental gain is provided in [Annex D](#). In [Annex E](#), recommendations for practical viewing conditions for various output media are given.

Photography — Electronic still-picture imaging — Noise measurements

1 Scope

This document specifies methods for measuring and reporting the noise versus signal level and dynamic range of digital still cameras. It applies to both monochrome and colour electronic digital still cameras.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 554, *Standard atmospheres for conditioning and/or testing — Specifications*

ISO 7589:2002, *Photography — Illuminants for sensitometry — Specifications for daylight, incandescent tungsten and printer*

ISO 12232:2006, *Photography — Digital still cameras — Determination of exposure index, ISO speed ratings, standard output sensitivity, and recommended exposure index*

ISO 14524:2009, *Photography — Electronic still-picture cameras — Methods for measuring opto-electronic conversion functions (OECFs)*

ITU-R BT.709-5, *Parameter values for the HDTV Standards for production and International programme exchange*

IEC 61966-2-1:1999, *Multimedia systems and equipment — Colour measurement and management — Part 2-1: Colour management — Default RGB colour space — sRGB*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

camera opto-electronic conversion function

camera OECF

relationship between the input scene log luminances and the pixel values for an opto-electronic digital capture system

Note 1 to entry: The unit of measurement for this function are \log_{10} cd/m².

3.2

clipping value

pixel value that remains constant for further increases in exposure (highlight clipping value) or for further decreases in exposure (dark clipping value)