EHITUSKLAAS. TERMILISELT KARASTATUD KALTSIUMSILIKAAT-OHUTUSKLAAS. OSA 1: MÄÄRATLUS JA KIRJELDUS

Glass in building - Thermally toughened soda lime silicate safety glass - Part 1: Definition and description



EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

See Eesti standard EVS-EN 12150-1:2015+A1:2019 sisaldab Euroopa standardi EN 12150-1:2015+A1:2019 ingliskeelset teksti.	12150-1:2015+A1:2019 consists of the English text
Standard on jõustunud sellekohase teate avaldamisega EVS Teatajas.	This standard has been endorsed with a notification published in the official bulletin of the Estonian Centre for Standardisation.
Euroopa standardimisorganisatsioonid on teinud Euroopa standardi rahvuslikele liikmetele kättesaadavaks 08.05.2019.	Date of Availability of the European standard is 08.05.2019.
Standard on kättesaadav Eesti Standardikeskusest.	The standard is available from the Estonian Centre for Standardisation.

Tagasisidet standardi sisu kohta on võimalik edastada, kasutades EVS-i veebilehel asuvat tagasiside vormi või saates e-kirja meiliaadressile standardiosakond@evs.ee.

ICS 81.040.20

Standardite reprodutseerimise ja levitamise õigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonsesse süsteemi või edastamine ükskõik millises vormis või millisel teel ilma Eesti Standardikeskuse kirjaliku loata on keelatud.

Kui Teil on küsimusi standardite autorikaitse kohta, võtke palun ühendust Eesti Standardikeskusega: Koduleht <u>www.evs.ee</u>; telefon 605 5050; e-post <u>info@evs.ee</u>

The right to reproduce and distribute standards belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without a written permission from the Estonian Centre for Standardisation.

If you have any questions about copyright, please contact Estonian Centre for Standardisation:

Homepage www.evs.ee; phone +372 605 5050; e-mail info@evs.ee

EUROPEAN STANDARD NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 12150-1:2015+A1

May 2019

ICS 81.040.20

English Version

Glass in building - Thermally toughened soda lime silicate safety glass - Part 1: Definition and description

Verre dans la construction - Verre de silicate sodocalcique de sécurité trempé thermiquement - Partie 1: Définition et description Glas im Bauwesen - Thermisch vorgespanntes Kalknatron-Einscheiben-Sicherheitsglas - Teil 1: Definition und Beschreibung

This European Standard was approved by CEN on 8 August 2015 and includes Amendment 1 approved by CEN on 6 January 2019.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Conti	ents	Page
Europ	ean foreword	4
Introd	uction	5
1	Scope	6
2	Normative references	
3	Terms and definitions	
4	Glass products	
5	Fracture characteristics	
6	Dimensions and tolerances	
6.1	Nominal thickness and thickness tolerances	
6.2	Width and length (sizes)	
6.2.1	General	
6.2.2	Maximum and minimum sizes	
6.2.3	Tolerances and squareness	
6.2.4	Edge deformation produced by the vertical process	
6.3	Flatness	
6.3.1 6.3.2	General Measurement of overall bow	
6.3.3	Measurement of A ₁) wave distortion and roller wave distortion (A ₁)	
6.3.4	Measurement of edge lift (for horizontally toughened glass only)	
6.3.5	Measurement of perimeter deformation of glass produced by air cushion toughening	
	process	
6.3.6	Measurement of local distortion (for vertically toughened glass only)	18
6.3.7	Limitation on overall bow, roller waves and edge lift for horizontally toughened	40
6.3.8	glassLimitation on overall bow, wave and perimeter deformation for toughened glass	18
0.3.0	manufactured by air cushion process	10
6.3.9	Limitation on overall bow and local distortion for vertically toughened glass	
	Other distortions	
7	Edge and/or surface work, holes, notches and cut-outs	
, 7.1	Warning	21 21
7.1 7.2	Edge working of glass for toughening	21 21
7.2 7.3	Profiled edges	22
7.4	Round holes	
7.4.1	General	22
7.4.2	Diameter of holes	22
7.4.3	Limitations on position of holes	
7.4.4	Tolerances on hole diameters	
7.4.5	Tolerances on position of holes	
7.5	Holes/others	
7.6 7.7	Notches and cut-outsShaped panes	
	• •	
8	Fragmentation test	26

8.1	General	
8.2	Dimensions and number of test specimens	
8.3	Test procedure	
8.4 8.5	Assessment of fragmentationMinimum values from the particle count	
8.6	Selection of the longest particle	
8.7	Maximum length of longest particle	
9	Other physical characteristics	29
9.1	Optical distortion	
9.1.1 9.1.2	Thermally toughened soda lime silicate safety glass produced by vertical toughening Thermally toughened soda lime silicate safety glass produced by horizontal	
9.2	tougheningAnisotropy (iridescence)	
9.3	Thermal durability	
9.4	Mechanical strength	
9.5	Classification of performance under accidental human impact	30
10	Marking	30
Annex	A (informative) Curved thermally toughened soda lime silicate safety glass	31
Annex	x B (informative) Alternative method for the measurement of roller wave distortion	
B.1	Apparatus	
B.2	Method	32
B.3	Limitations	33
B.4	Alternative use of apparatus	33
Annex	c C (informative) Examples of particle count	34
Annex	D (informative) Risk of spontaneous breakage of toughened glass due to nickel	
	sulfide inclusion	
Biblio	graphy	38

European foreword

This document (EN 12150-1:2015+A1:2019) has been prepared by Technical Committee CEN/TC 129 "Glass in building", the secretariat of which is held by NBN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by November 2019, and conflicting national standards shall be withdrawn at the latest by November 2019.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document includes Amendment 1 approved by CEN on 2019-01-06.

This document supersedes At EN 12150-1:2015 (At

The start and finish of text introduced or altered by amendment is indicated in the text by tags 🗗 街.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

EN 12150, *Glass in building* — *Thermally toughened soda lime silicate safety glass*, consists of the following parts:

- Part 1: Definitions and description;
- Part 2: Evaluation of conformity/Product standard.

A_1 Deleted text A_1

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

Thermally toughened soda lime silicate safety glass has a safer breakage behaviour when compared s. ed so.

129/WG t. a method. with annealed glass. When it should be used to offer protection under accidental human impact, thermally toughened soda lime silicate safety glass also should be classified according to EN 12600.

CEN/TC 129/WG 8 is producing standards for the determination of the design strength of glass and is preparing a design method.

1 Scope

This European Standard specifies tolerances, flatness, edgework, fragmentation and physical and mechanical characteristics of monolithic flat thermally toughened soda lime silicate safety glass for use in buildings.

Information on curved thermally toughened soda lime silicate safety glass is given in Annex A, but this product does not form part of this European Standard.

Other requirements, not specified in this European Standard, can apply to thermally toughened soda lime silicate safety glass which is incorporated into assemblies, e.g. laminated glass or insulating glass units, or undergo an additional treatment, e.g. coating. The additional requirements are specified in the appropriate glass product standard. Thermally toughened soda lime silicate safety glass, in this case, does not lose its bending strength characteristics and its resistance to temperature differentials.

Surface finished glasses (e.g. sandblasted, acid etched) after toughening are not covered by this European Standard.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 572-1, Glass in building — Basic soda lime silicate glass products — Part 1: Definitions and general physical and mechanical properties

EN 572-2, Glass in building — Basic soda lime silicate glass products —Part 2: Float glass

EN 572-4, Glass in building — Basic soda lime silicate glass products — Part 4: Drawn sheet glass

EN 572-5, Glass in building — Basic soda lime silicate glass products — Part 5: Patterned glass

EN 572-8, Glass in building — Basic soda lime silicate glass products — Part 8: Supplied and final cut sizes

EN 1096-1, Glass in building — Coated glass - Part 1: Definitions and classification

EN 1288-3, Glass in building — Determination of the bending strength of glass — Part 3: Test with specimen supported at two points (four point bending)

·30/2/5

EN 14428, Shower enclosures — Functional requirements and test methods