

International Standard



4867

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Code for the measurement and reporting of shipboard vibration data

Code pour l'exécution des mesurages de vibrations à bord des navires et présentation des résultats

First edition — 1984-12-01

UDC 534.1 : 629.12

Ref. No. ISO 4867-1984 (E)

Descriptors : ships, vibration, measurement, definitions, recording instruments, testing conditions, technical data sheets.

Price based on 18 pages

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 4867 was prepared by Technical Committee ISO/TC 108, *Mechanical vibration and shock*.

Contents

	Page
0 Introduction	1
1 Scope and field of application	1
2 References	2
3 Definitions	2
4 Measurement of data	2
5 Analysis and reporting of data	4
6 Rules for presentation of vibration test results	5
Tables 1 to 7	6
Figures 1 to 5	13
Bibliography	18

This document is a preview generated by EVS

This page intentionally left blank

Code for the measurement and reporting of shipboard vibration data

0 Introduction

The need for comparative data on ship vibration requires uniform test conditions. In general, comparative data can best be obtained during ship trials with known ballast loading. The relatively uniform vibration resulting from propulsion machinery excitation (turbine or diesel drive) can be masked or distorted by transient vibrations due to wave impact or slamming. Changes in wake distribution due to rudder angle and yaw can produce large increases in exciting forces. Operation in shallow water also has a significant effect on hull vibration. Propeller emergence, whether continuous or periodic, causes large increases in exciting forces. The effect of lateral vibration of the aft part of line shafting on hull and superstructure vibration should also be considered.

The aft part of the line shaft may have a lateral resonant frequency within the speed range of the ship which can be excited to strong vibrations by either unbalance or propeller forces.

Alternating thrust forces may cause dangerous vibration of the thrust bearing or machinery as a result of a longitudinal resonance in the propulsion system.

Diesel engines may vibrate about the three rotational axes and three translational axes and generate large forces which in turn may cause large ship vibrations.

The principal response of a ship hull is usually similar to that of a free-free beam in its lower modes. At higher frequencies, the response of the hull girder is equivalent to a forced response with ill-defined resonances and maximum response in the stern area. The stern area is an antinode for all bending and torsional modes excited by the propulsion system and is an appropriate reference point for the measurement of beam-like vibration and forced response. The response of superstructures and local structures may be evaluated in terms of the ratio of their vibratory amplitude to the amplitude of hull girder vibration at that location.

In this International Standard, the term "vibration severity" is used to describe the vibration conditions in the ship and, based on long-established practice in the industry, the peak value of vibration velocity has been chosen as the primary quantity of measurement; since, however, much data have been accumulated in terms of vibration acceleration and vibration displacement, a plotting sheet has been adopted on which data may easily be plotted using any of these quantities of measurement.

1 Scope and field of application

This International Standard establishes uniform procedures for gathering and presenting data:

- a) on hull vibration in single or multiple-shaft sea-going merchant ships;
- b) for vibration of propulsion-shaft systems as it affects hull vibration.

Such data are necessary to establish uniformly the vibration characteristics of hull and propulsion-shaft systems and to provide a basis for design predictions, improvements and comparison against vibration reference levels.

The procedures, where applicable, can also be used for inland ships and tug boats. In special cases, where objectionable vibration is found to exist, specific investigative studies may be required.

This International Standard is concerned with:

- a) vibration of the main hull girder and superstructure excited by the propulsion system
 - at shaft rotational frequency,
 - at propeller blade rate, harmonics of blade rate and
 - at frequencies associated with the major components of machinery;
- b) excitation of the propulsion shaft and main machinery system.

It does not deal with other aspects of ship vibration at this time. Local vibration is dealt with in ISO 4868.

Anchor drop-and-snub tests in calm water may be an effective means of obtaining the first few vertical hull modes of vibration and their damping constants (see warning in 4.5.5).

Detailed design information on the ship is required to assist in developing empirical constants useful in evaluating the vibration of hull and machinery vibratory characteristics.

This International Standard gives general principles of vibration measurement on board ships to improve vibration engineering. Therefore, in individual cases, items to be measured may be selected or added to meet the aims of the vibration measurement of each ship.