
**Information technology — Real-time
locating systems (RTLS) —**

Part 22:

**Direct Sequence Spread Spectrum
(DSSS) 2,4 GHz air interface protocol:
Transmitters operating with multiple
spread codes and employing a QPSK
data encoding and Walsh offset QPSK
(WOQPSK) spreading scheme**

*Technologies de l'information — Systèmes de localisation en temps réel
(RTLS) —*

*Partie 22: Protocole d'interface d'air à 2,4 GHz d'étalement de spectre à
séquence directe (DSSS): Émetteurs fonctionnant avec des codes
d'étalement multiples et utilisant un codage de données QPSK et un
schéma*

This document is a preview generated by EVS



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviated terms	4
5 Requirements.....	4
5.1 Frequency range.....	4
5.2 2,4 GHz spread spectrum air interface attributes	4
5.3 Compliance requirements	5
5.4 Manufacturer tag ID.....	5
5.5 Physical layer parameters	5
6 Mandatory air interface protocol specification	7
6.1 General	7
6.2 Physical layer specification	9
Annex A (informative) Reader synchronization by the RTLS reference tag	17
Bibliography.....	19

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 24730-22 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

This first edition of ISO/IEC 24730-22, together with ISO/IEC 24730-2 and ISO/IEC 24730-21, cancels and replaces the first edition of ISO/IEC 24730-2:2006, which has been technically revised.

ISO/IEC 24730 consists of the following parts, under the general title *Information technology — Real-time locating systems (RTLS)*:

- *Part 1: Application program interface (API)*
- *Part 2: Direct Sequence Spread Spectrum (DSSS) 2,4 GHz air interface protocol*
- *Part 5: Chirp spread spectrum (CSS) at 2,4 GHz air interface*
- *Part 21: Direct Sequence Spread Spectrum (DSSS) 2,4 GHz air interface protocol: Transmitters operating with a single spread code and employing a DBPSK data encoding and BPSK spreading scheme*
- *Part 22: Direct Sequence Spread Spectrum (DSSS) 2,4 GHz air interface protocol: Transmitters operating with multiple spread codes and employing a QPSK data encoding and Walsh offset QPSK (WOQPSK) spreading scheme*

The following parts are under preparation:

- *Part 6: Ultra Wide Band Air Interface protocol*
- *Part 61: Low rate pulse repetition frequency Ultra Wide Band (UWB) air interface*
- *Part 62: High rate pulse repetition frequency Ultra Wide Band (UWB) air interface*

Introduction

ISO/IEC 24730 defines a single application program interface (API) for real-time locating systems (RTLs) for use in asset management and is intended to allow for compatibility and to encourage interoperability of products for the growing RTLS market. ISO/IEC 24730 also defines three air interface protocols, as follows: ISO/IEC 24730-2, based on a direct sequence spread spectrum (DSSS), ISO/IEC 24730-5, based on a chirp spread spectrum (CSS) technique, and ISO/IEC 24730-6 Ultra Wide Band Air Interface protocol.

This part of ISO/IEC 24730, the direct sequence spread spectrum (DSSS) 2,4 GHz air interface protocol, establishes a technical standard for real-time locating systems that operate at an internationally available 2,4 GHz frequency band and is intended to provide approximate location with frequent updates (for example, several times a minute). In order to be compliant with this part of ISO/IEC 24730 compliance with ISO/IEC 24730-1 is also required.

Real-time locating systems are wireless systems with the ability to locate the position of an item anywhere in a defined space (local/campus, wide area/regional, global) at a point in time that is, or is close to, present time. Position is derived by measurements of the physical properties of the radio link.

This part of ISO/IEC 24730 specifies the air interface for a system that locates an asset in a controlled area, e.g. warehouse, campus, airport (area of interest is instrumented) with accuracy to 3 m or less.

There are two additional methods of locating an object which are really RFID rather than RTLs:

- locating an asset by virtue of the fact that the asset has passed point A at a certain time and has not passed point B;
- locating an asset by virtue of providing a homing beacon whereby a person with a handheld device can find an asset.

The method of location is through identification and location, generally through multi-lateration. The different types are

- time of Arrival (ToA) / Time of Flight Ranging Systems,
- amplitude / Received Signal Strength Triangulation,
- time Difference of Arrival (TDoA), and
- angle of Arrival (AoA).

This part of ISO/IEC 24730 defines the air interface protocol needed for the creation of an RTLS system.

Although there are many types of location algorithms that could be used, one example of a location algorithm is provided in Annex A of ISO/IEC 24730-21.

This part of ISO/IEC 24730 also defines the physical layer for compliant RTLS transmitters operating with multiple spread codes and employing a QPSK data encoding and Walsh offset QPSK (WOQPSK) spreading scheme, and defines the air interface protocol needed for the reader synchronization essential for the location method based on timing information, such as Time Difference of Arrival (TDOA).

Although there are many types of reader synchronization methods that could be used, an example of RTLS reader synchronization is provided in Annex A.

Information technology — Real-time locating systems (RTLS) —

Part 22:

Direct Sequence Spread Spectrum (DSSS) 2,4 GHz air interface protocol: Transmitters operating with multiple spread codes and employing a QPSK data encoding and Walsh offset QPSK (WOQPSK) spreading scheme

1 Scope

ISO/IEC 24730-2 is comprised of a main document and two additional parts, ISO/IEC 24730-21 and ISO/IEC 24730-22, and defines a networked location system that provides X-Y coordinates and data telemetry. The system utilizes real-time locating systems (RTLS) transmitters that autonomously generate a direct sequence spread spectrum radio frequency beacon. These devices can be field programmable and support an optional exciter mode that allows modification of the rate of location update and location of the RTLS device. ISO/IEC 24730-2 defines these modes, but does not define the means by which they are accomplished.

This part of ISO/IEC 24730 is the mode of ISO/IEC 24730-2 transmitters operating with multiple spread codes and employing a quadrature phase shift keying (QPSK) data encoding and Walsh offset QPSK(WOQPSK) spreading scheme.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 24730-1, *Information technology — Real-time locating systems (RTLS) — Part 1: Application program interface (API)*

ISO/IEC 24730-2, *Information technology — Real-time locating systems (RTLS) — Part 2: Direct Sequence Spread Spectrum (DSSS) 2,4 GHz air interface protocol*

ISO/IEC 18000-4:2008, *Information technology — Radio frequency identification for item management — Part 4: Parameters for air interface communications at 2,45 GHz*

ISO/IEC 19762-1, *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary — Part 1: General terms relating to AIDC*

ISO/IEC 19762-3, *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary — Part 3: Radio frequency identification (RFID)*

ISO/IEC 15963, *Information technology — Radio frequency identification for item management — Unique identification for RF tags*

ISO/IEC 8802-11:2005, *Information technology — Telecommunications and information exchange between systems — Local and metropolitan area networks — Specific requirements — Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) specifications*

IEEE Std 1451.7™-2010, *IEEE Standard for A Smart Transducer Interface for Sensors and Actuators — Transducers to Radio Frequency Identification (RFID) Systems Communication Protocols and Transducer Electronic Data Sheet Formats*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 19762-1, ISO/IEC 19762-3 and the following apply.

3.1

air interface

wireless communications protocol and signal structure used to communicate data between RTLS transmitters and other RTLS devices

3.2

host applications

customer's management information systems

3.3

RTLS infrastructure

system components existing between the air interface protocol and the RTLS server API

3.4

real-time locating system

set of radio frequency receivers and associated computing equipment used to determine the position of a transmitting device relative to the placement of the aforementioned receivers that is capable of reporting that position within several minutes of the transmission used for determining the position of the transmission

NOTE Refer to Figure 1 for clarity regarding elements of RTLS infrastructure.