

---

---

**Pneumatic fluid power —  
Determination of flow-rate  
characteristics of components using  
compressible fluids —**

**Part 1:  
General rules and test methods for  
steady-state flow**

*Transmissions pneumatiques — Détermination des caractéristiques  
de débit des composants traversés par un fluide compressible —*

*Partie 1: Règles générales et méthodes d'essai en régime stationnaire*



This document is a preview generated by EBS



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

|   |           |
|---|-----------|
| <b>Foreword</b>   | <b>iv</b> |
| <b>Introduction</b>   | <b>v</b>  |
| <b>1 Scope</b>  | <b>1</b>  |
| <b>2 Normative references</b>   | <b>2</b>  |
| <b>3 Terms and definitions</b>  | <b>2</b>  |
| 3.1 Terms and definitions related to pressures  | 2         |
| 3.2 Terms and definitions related to temperature  | 2         |
| 3.3 Terms and definitions related to flow   | 3         |
| 3.4 Terms and definitions related to flow-rate characteristics  | 3         |
| 3.5 Miscellaneous terms and definitions   | 4         |
| <b>4 Symbols and units</b>  | <b>4</b>  |
| <b>5 Test installation</b>  | <b>5</b>  |
| 5.1 Test circuit for constant upstream pressure test  | 5         |
| 5.2 Test circuit for variable upstream pressure test  | 6         |
| 5.3 General requirements  | 7         |
| 5.4 Pressure-measuring tubes (items 6 and 10)   | 7         |
| 5.5 Transition connectors (items 7 and 9)   | 9         |
| 5.6 Special requirements  | 12        |
| <b>6 Test procedures</b>  | <b>13</b> |
| 6.1 Test conditions   | 13        |
| 6.2 Measuring procedures  | 14        |
| 6.3 Calculation of characteristics  | 16        |
| <b>7 Presentation of test results</b>   | <b>18</b> |
| <b>8 Identification statement (reference to this part of ISO 6358)</b>  | <b>19</b> |
| <b>Annex A (normative) Alternative test procedure</b>   | <b>20</b> |
| <b>Annex B (informative) Flowmeter calibration</b>  | <b>23</b> |
| <b>Annex C (informative) Evaluation of measurement uncertainty</b>  | <b>25</b> |
| <b>Annex D (informative) Observations on error in test results</b>  | <b>30</b> |
| <b>Annex E (informative) Equations and graphical representations of flow-rate characteristics</b>   | <b>41</b> |
| <b>Annex F (informative) Use of practical units</b>   | <b>46</b> |
| <b>Annex G (informative) Results of testing performed on commercially available pneumatic components</b>  | <b>47</b> |
| <b>Annex H (informative) Procedures for calculating critical back-pressure ratio, <math>b</math>, and subsonic index, <math>m</math>, by the least-square method using the Solver function in Microsoft Excel</b> | <b>57</b> |
| <b>Bibliography</b>   | <b>61</b> |

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 6358-1 was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 5, *Control products and components*.

This first edition of ISO 6358-1, together with ISO 6358-2 and ISO 6358-3, cancels and replaces ISO 6358:1989, which has been technically revised. However, ISO 6358-2 and ISO 6358-3 are new standards whose scopes were not included in ISO 6358:1989.

ISO 6358 consists of the following parts, under the general title *Pneumatic fluid power — Determination of flow-rate characteristics of components using compressible fluid*:

*Part 1: General rules and test methods for steady-state flow*

*Part 2: Alternative test methods*

The following parts are under preparation:

— *Part 3: Method for calculating steady-state flow-rate characteristics of assemblies*

## Introduction

In pneumatic fluid power systems, power is transmitted and controlled through a gas under pressure within a circuit. Components that make up such a circuit are inherently resistive to the flow of the gas and it is necessary, therefore, to define and determine the flow-rate characteristics that describe their performance.

ISO 6358:1989 was developed to determine the flow-rate characteristics of pneumatic valves, based upon a model of converging nozzles. The method included two characteristic parameters: sonic conductance,  $C$ , and critical pressure ratio,  $b$ , used in a proposed mathematical approximation of the flow behaviour. The result described flow performance of a pneumatic valve from choked flow to subsonic flow, based on static pressure. This new edition uses stagnation pressure instead, to take into account the influence of flow velocity on the measurement of pressures.

Experience has demonstrated that many pneumatic valves have converging-diverging characteristics that do not fit the ISO 6358:1989 model very well. Furthermore, new developments have allowed the application of this method to additional components beyond pneumatic valves. However, this now requires the use of four parameters ( $C$ ,  $b$ ,  $m$ , and  $\Delta p_c$ ) to define the flow performance in both the choked and subsonic flow regions.

This part of ISO 6358 describes a set of four flow-rate characteristic parameters determined from test results. These parameters are described as follows and are listed in decreasing order of priority:

The sonic conductance,  $C$ , corresponding to the maximum flow rate (choked) is the most important parameter. This parameter is defined by the upstream stagnation conditions.

The critical back-pressure ratio,  $b$ , representing the boundary between choked and subsonic flow is second in importance. Its definition differs here from the one in ISO 6358:1989 because it corresponds to the ratio of downstream to upstream stagnation pressures.

The subsonic index,  $m$ , is used if necessary to represent more accurately the subsonic flow behaviour. For components with a fixed flow path,  $m$  is distributed around 0,5. In these cases, only the first two characteristic parameters  $C$  and  $b$  are necessary. For many other components,  $m$  varies widely. In these cases, it is necessary to determine  $C$ ,  $b$ , and  $m$ .

The parameter  $\Delta p_c$  is the cracking pressure. This parameter is used only for pneumatic components that open with increasing upstream pressure, such as non-return (check) valves or one-way flow control valves.

Several changes to the test equipment were made to overcome apparent violations of the theory of compressible fluid flow. This includes expanded inlet pressure-measuring tubes to satisfy the assumptions of negligible inlet velocity to the item under test and to allow the inlet stagnation pressure to be measured directly. Expanded outlet tubes allow the direct measurement of downstream stagnation pressure to better accommodate the different component models. The difference between stagnation pressure at upstream and downstream of component means a loss of pressure energy.

For testing a component with a large nominal bore, to shorten testing time or to reduce energy consumption, it is desirable to apply the methods specified in ISO 6358-2, which covers a discharge test and a charge test as alternative test methods.

ISO 6358-3 can be used to calculate without measurements an estimate of the overall flow-rate characteristics of an assembly of components and piping, using the characteristics of each component and piping determined in accordance with this part of ISO 6358 or ISO 6358-2.

It should be noted that performance characteristics measured in accordance with this edition of ISO 6358 differ from those measured in accordance with ISO 6358:1989.



# Pneumatic fluid power — Determination of flow-rate characteristics of components using compressible fluids —

## Part 1:

## General rules and test methods for steady-state flow

### 1 Scope

This part of ISO 6358 specifies a steady-state method for testing pneumatic fluid power components that use compressible fluids, i.e. gases, and that have internal flow paths that can be either fixed or variable in size, to determine their flow-rate characteristics. However, this part of ISO 6358 does not apply to components whose flow coefficient is unstable during use, i.e. components that exhibit remarkable hysteretic behaviour (because they can contain flexible parts that deform under the flow) or that have an internal feedback phenomenon (such as regulators). In addition, it does not apply to components that exchange energy with the fluid during flow-rate measurement, e.g. cylinders, accumulators, etc.

[Table 1](#) provides a summary of which parts of ISO 6358 can be applied to various components.

**Table 1 — Application of ISO 6358 test methods to components**

| Components |   | Constant upstream pressure test            |                        | Variable upstream pressure test            |                           |
|------------|---|--|------------------------|--|---------------------------|
|            |   | ISO 6358-1 constant upstream pressure test | ISO 6358-2 charge test | ISO 6358-1 variable upstream pressure test | ISO 6358-2 discharge test |
| Group 1    | Directional control valves                | yes  | yes                    | yes  | yes                       |
|            | Flow control valves                       | yes  | yes                    | yes  | yes                       |
|            | Connectors                                | yes  | yes                    | yes  | yes                       |
|            | Valve manifolds                           | yes  | yes                    | yes  | yes                       |
|            | Group of components                       | yes  | yes                    | yes  | yes                       |
| Group 2    | Filters and lubricators                   | yes  | no                     | no   | no                        |
|            | Non-return (check) valves                 | yes  | no                     | no   | no                        |
|            | Tubes and hoses                           | yes  | no                     | no   | no                        |
| Group 3    | Silencers and exhaust oil mist separators | no   | no                     | yes  | yes                       |
|            | Blow nozzles                              | no   | no                     | yes  | yes                       |
|            | Quick-exhaust valves                      | no   | no                     | yes  | yes                       |
|            | Cylinder end heads                        | no   | no                     | yes  | yes                       |

This part of ISO 6358 specifies requirements for the test installation, the test procedure, and the presentation of results for the steady-state method.

This part of ISO 6358 includes several test procedures, including the one described in [Annex A](#), which is from ISO 6358:1989. Flowmeter calibration is described in [Annex B](#). Evaluation of measurement uncertainties is described in [Annex C](#). Observations of the error in the test results are described in [Annex D](#). Equations and graphical representations of flow-rate characteristics are given in [Annex E](#). Guidance on the use of practical units for the presentation of results is given in [Annex F](#). Test results

using commercially available pneumatic components are given in [Annex G](#). Guidance on calculating the flow-rate characteristics is given in [Annex H](#).

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 228-1, *Pipe threads where pressure-tight joints are not made on the threads — Part 1: Dimensions, tolerances and designation*

ISO 1219-1, *Fluid power systems and components — Graphical symbols and circuit diagrams — Part 1: Graphical symbols for conventional use and data-processing applications*

ISO 5598, *Fluid power systems and components — Vocabulary*

ISO 8778, *Pneumatic fluid power — Standard reference atmosphere*

ISO 14743:2004, *Pneumatic fluid power — Push-in connectors for thermoplastic tubes*

ISO 16030, *Pneumatic fluid power — Connections — Ports and stud ends*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5598 and the following apply. The terms and definitions given in [3.1](#) through [3.3](#) are those for which it seems useful to emphasize the meaning. The terms and definitions in [3.4](#) and [3.5](#) are given for the purposes of this part of ISO 6358.

### 3.1 Terms and definitions related to pressures

#### 3.1.1

##### **static pressure**

pressure measured perpendicularly to the flow direction without influence of disturbances

Note 1 to entry: Static pressure can be measured by connecting a pressure-measuring device to a pressure-tapping mounting in a wall.

#### 3.1.2

##### **stagnation pressure**

pressure that would exist in a flowing gas stream if the stream were brought to rest by an isentropic process

Note 1 to entry: In this part of ISO 6358, the static pressure measured in the pressure-measuring tubes is effectively the stagnation pressure within 6 %.

### 3.2 Terms and definitions related to temperature

#### 3.2.1

##### **static temperature**

temperature that would be measured by a device that moves with the flowing gas at its velocity

#### 3.2.2

##### **stagnation temperature**

temperature that would exist in a flowing gas stream if the stream were brought to rest by an isentropic process

Note 1 to entry: In this part of ISO 6358, the temperature measured in the pressure-measuring tubes with either an immersed temperature probe or a probe in the side wall of the tube is effectively the stagnation temperature within 1 %.