INTERNATIONAL STANDARD

ISO 10211

Second edition 2017-06

Thermal bridges in building construction — Heat flows and surface temperatures — Detailed calculations

s the.

upératur Ponts thermiques dans les bâtiments — Flux thermiques et



Reference number ISO 10211:2017(E)



© ISO 2017, Published in Switzerland

nroduced or utilized 'be internet or an or ISO's mem' All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Coı	ntents		Page										
Fore	word		v										
Intro	oduction	L	vi										
1	Scope		1										
2		ative references											
3		s and definitions											
4	Symb 4.1	ols and subscripts Symbols	7										
	4.1	Subscripts											
5	Description of the method												
3	5.1	Output											
	5.2	General description											
6	Outn	ıt data and input data	8										
	6.1	Output data	8										
	6.2	Calculation time intervals											
	6.3	Input data	9										
7	Mode	lling of the construction											
	7.1	Dimension systems											
	7.2	Rules for modelling											
		 7.2.1 General 7.2.2 Cut-off planes for a 3-D geometrical model for calculation of total heat 	9										
		flow and/or surface temperatures	9										
		7.2.3 Cut-off planes for a 2-D geometrical model											
		7.2.4 Cut-off planes in the ground											
		7.2.5 Periodic heat flows via the ground	13										
		7.2.6 Adjustments to dimensions											
		7.2.7 Auxiliary planes											
	7.3	7.2.8 Quasi-homogeneous layers and materials Conditions for simplifying the geometrical model											
	7.3	7.3.1 General	15 15										
		7.3.2 Conditions for adjusting dimensions to simplify the geometrical model											
		7.3.3 Conditions for using quasi-homogeneous material layers to simplify the											
		geometrical model	17										
8	Input	data specifications	20										
	8.1	General	20										
	8.2	Thermal conductivities of materials	21										
	8.3	Surface resistances											
	8.4 8.5	Boundary temperaturesThermal conductivity of quasi-homogeneous layers	21 21										
	8.6	Equivalent thermal conductivity of air cavities	21										
	8.7	Determining the temperature in an adjacent unheated room	22										
9	Calcu	lation method											
J	9.1	Solution technique											
	9.2	Calculation rules											
		9.2.1 Heat flows between material cells and adjacent environment	22										
		9.2.2 Heat flows at cut-off planes											
		9.2.3 Solution of the formulae											
		9.2.4 Calculation of the temperature distribution											
10		mination of thermal coupling coefficients and heat flow rate from 3-D calculat	ions23										
	10.1 10.2	Two boundary temperatures, unpartitioned model											
	10.4	Two boundary temperatures, partitioned model	∠3										

ISO 10211:2017(E)

	10.3	More than two boundary temperatures	24
11	11.1	lations using linear and point thermal transmittances from 3-D calculations Calculation of thermal coupling coefficient Calculation of linear and point thermal transmittances	25
12	Deter	mination of thermal coupling coefficient, heat flow rate and linear thermal mittance from 2-D calculations. Two boundary temperatures. More than two boundary temperatures. Determination of the linear thermal transmittance. Determination of the linear thermal transmittance for wall/floor junctions. 12.4.1 All cases. 12.4.2 Option A. 12.4.3 Option B.	26 26 27 27
	12.5	Determination of the external periodic heat transfer coefficient for ground floors	
13	13.1	Determination of the temperature at the internal surface Determination of the temperature at the internal surface from 3-D calculations 13.1.1 Two boundary temperatures 13.1.2 More than two boundary temperatures	32 32 32
	13.2	Determination of the temperature at the internal surface from 2-D calculations	33
14	Repo	·t	33
	14.1 14.2	Input data Output data 14.2.1 General 14.2.2 Calculation of the heat transmission using the thermal coupling coefficient 14.2.3 Calculation of the surface temperatures using weighting factors 14.2.4 Additional output data 14.2.5 Estimate of error	33 34 34 34
Anne	x A (no	mative) Input and method selection data sheet — Template	36
Anne	x B (inf	ormative) Input and method selection data sheet — Default choices	38
Anne	x C (no	mative) Validation of calculation methods	40
Anne		rmative) Examples of the determination of the linear and point nal transmittances	47
Anne		mative) Determination of values of thermal coupling coefficient and erature weighting factor for more than two boundary temperatures	50
Bibli	ograph		55

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

ISO 10211 was prepared by ISO Technical Committee ISO/TC 163, Thermal performance and energy use in the built environment, Subcommittee SC 2, Calculation methods, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 89, Thermal performance of buildings and building components, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 10211:2007), which has been technically revised.

The changes in the second edition are mostly editorial. The standard has been re-drafted according to CEN/TS 16629:2014.

Introduction

This document is part of a series aimed at the international harmonization of the methodology for assessing the energy performance of buildings. Throughout, this series is referred to as a "set of EPB standards".

All EPB standards follow specific rules to ensure overall consistency, unambiguity and transparency.

All EPB standards provide a certain flexibility with regard to the methods, the required input data and references to other EPB standards, by the introduction of a normative template in <u>Annex A</u> and <u>Annex B</u> with informative default choices.

For the correct use of this document, a normative template is given in <u>Annex A</u> to specify these choices. Informative default choices are provided in <u>Annex B</u>.

The main target groups for this document are architects, engineers and regulators.

Use by or for regulators: In case the document is used in the context of national or regional legal requirements, mandatory choices may be given at national or regional level for such specific applications. These choices (either the informative default choices from Annex B or choices adapted to national/regional needs, but in any case following the template of Annex A) can be made available as national annex or as separate (e.g. legal) document (national data sheet).

NOTE 1 So in this case:

- the regulators will specify the choices;
- the individual user will apply the document to assess the energy performance of a building, and thereby use the choices made by the regulators.

Topics addressed in this document can be subject to public regulation. Public regulation on the same topics can override the default values in Annex B. Public regulation on the same topics can even, for certain applications, override the use of this document. Legal requirements and choices are in general not published in standards but in legal documents. In order to avoid double publications and difficult updating of double documents, a national annex may refer to the legal texts where national choices have been made by public authorities. Different national annexes or national data sheets are possible, for different applications.

It is expected, if the default values, choices and references to other EPB standards in <u>Annex B</u> are not followed due to national regulations, policy or traditions, that:

- national or regional authorities prepare data sheets containing the choices and national or regional values, according to the model in <u>Annex A</u>. In this case a national annex (e.g. NA) is recommended, containing a reference to these data sheets;
- or, by default, the national standards body will consider the possibility to add or include a national annex in agreement with the template of <u>Annex A</u>, in accordance to the legal documents that give national or regional values and choices.

Further target groups are parties wanting to motivate their assumptions by classifying the building energy performance for a dedicated building stock.

More information is provided in the Technical Report accompanying this document (ISO/TR 52019-2).

The subset of EPB standards prepared under the responsibility of ISO/TC 163/SC 2 cover inter alia:

- calculation procedures on the overall energy use and energy performance of buildings;
- calculation procedures on the internal temperature in buildings (e.g. in case of no space heating or cooling);
- indicators for partial EPB requirements related to thermal energy balance and fabric features;

 calculation methods covering the performance and thermal, hygrothermal, solar and visual characteristics of specific parts of the building and specific building elements and components, such as opaque envelope elements, ground floor, windows and facades.

ISO/TC 163/SC 2 cooperates with other technical committees for the details on appliances, technical building systems, indoor environment, etc.

This document sets out the specifications for a geometrical model of a thermal bridge for the numerical calculation of linear thermal transmittances, point thermal transmittances and internal surface temperatures.

<u>Table 1</u> shows the relative position of this document within the set of EPB standards in the context of the modular structure as set out in ISO 52000-1.

NOTE 2 In ISO/TR 52000-2 the same table can be found, with, for each module, the numbers of the relevant EPB standards and accompanying technical reports that are published or in preparation.

NOTE 3 The modules represent EPB standards, although one EPB standard could cover more than one module and one module could be covered by more than one EPB standard, for instance, a simplified and a detailed method respectively. See also <u>Tables A.1</u> and <u>B.1</u>.

Table 1 — Position of this document (*in casu* M2-5) within the modular structure of the set of EPB standards

	Overarching		Building (as such)		Technical Building Systems									
Sub- module	Descriptions		Descrip- tions		Descriptions	Heat- ing	Cool- ing	Ven- tila- tion	Humidi- fication	Dehu- midifi- cation	Domestic hot water	Lighting	Building automa- tion and control	PV, wind,
sub1		M1		M2		М3	M4	M5	М6	М7	М8	М9	M10	M11
1	General		General		General		1							
2	Common terms and definitions; symbols, units and subscripts		Building en- ergy needs		Needs					\(\sigma_{}\)			a	
3	Applications		(Free) indoor conditions without systems		Maximum load and power					6	0			
4	Ways to express energy performance		Ways to express energy per- formance		Ways to express energy performance						4		, (
5	Building categories and building boundaries		Heat trans- fer by trans- mission	ISO 10211	Emission and control								0,	
a The shaded modules are not applicable.														

 Table 1 (continued)

	Overarchin	Buildin (as such	g ı)	Technical Building Systems										
Sub- module	Descriptions		Descrip- tions		Descriptions	Heat- ing	Cool- ing	Ven- tila- tion	Humidi- fication	Dehu- midifi- cation	Domestic hot water	Lighting	Building automa- tion and control	PV, wind,
sub1		M1		M2		М3	M4	М5	M6	M7	M8	M9	M10	M11
6	Building oc- cupancy and operating conditions	,	Heat trans- fer by infil- tration and ventilation	2	Distribution and control									
7	Aggregation of energy services and energy carriers		Internal heat gains		Storage and control									
8	Building zoning		Solar heat gains		Generation and control	10								
9	Calculated energy per- formance		Building dynamics (thermal mass)		Load dis- patching and operating conditions		0							
10	Measured energy per- formance		Measured energy per- formance		Measured Energy Per- formance				9	0				
11	Inspection		Inspection		Inspection					O				
12	Ways to ex- press indoor comfort				BMS						0			
13	External environment conditions											0		
14	Economic calculation													
a The shaded modules are not applicable.														

Thermal bridges in building construction — Heat flows and surface temperatures — Detailed calculations

1 Scope

This document sets out the specifications for a three-dimensional and a two-dimensional geometrical model of a thermal bridge for the numerical calculation of

- heat flows, in order to assess the overall heat loss from a building or part of it, and
- minimum surface temperatures, in order to assess the risk of surface condensation.

These specifications include the geometrical boundaries and subdivisions of the model, the thermal boundary conditions, and the thermal values and relationships to be used.

This document is based upon the following assumptions:

- all physical properties are independent of temperature;
- there are no heat sources within the building element.

This document can also be used for the derivation of linear and point thermal transmittances and of surface temperature factors.

NOTE Table 1 in the Introduction shows the relative position of this document within the set of EPB standards in the context of the modular structure as set out in ISO 52000-1.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6946, Building components and building elements — Thermal resistance and thermal transmittance — Calculation method

ISO 7345, Thermal insulation — Physical quantities and definitions

ISO 13370, Thermal performance of buildings — Heat transfer via the ground — Calculation methods

ISO 13788, Hygrothermal performance of building components and building elements — Internal surface temperature to avoid critical surface humidity and interstitial condensation — Calculation methods

ISO 10456, Building materials and products — Hygrothermal properties — Tabulated design values and procedures for determining declared and design thermal values

ISO 13789, Thermal performance of buildings — Transmission and ventilation heat transfer coefficients — Calculation method

ISO 52000-1:2017, Energy performance of buildings — Overarching EPB assessment — Part 1: General framework and procedures

NOTE 1 Default references to EPB standards other than ISO 52000-1 are identified by the EPB module code number and given in $\frac{Annex\ A}{Annex\ B}$ (informative default choice in Table B.1).

ISO 10211:2017(E)

EXAMPLE EPB module code number: M5–5, or M5–5,1 (if module M5–5 is subdivided), or M5–5/1 (if reference to a specific clause of the standard covering M5–5).

NOTE 2 In this document, there are no choices in references to other EPB standards. The sentence and note above is kept to maintain uniformity between all EPB standards.

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 7345, ISO 52000-1, and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1

thermal bridge

part of the building envelope where the otherwise uniform thermal resistance is significantly changed by full or partial penetration of the building envelope by materials with a different thermal conductivity, and/or a change in thickness of the fabric, and/or a difference between internal and external areas, such as occur at wall/floor/ceiling junctions

3.2

linear thermal bridge

thermal bridge (3.1) with a uniform cross-section along one of the three orthogonal axes

3.3

point thermal bridge

localized *thermal bridge* (3.1) whose influence can be represented by a *point thermal transmittance* (3.20)

3.4

three-dimensional geometrical model

3-D geometrical model

geometrical model, deduced from building plans, such that for each of the orthogonal axes, the cross-section perpendicular to that axis changes within the boundary of the model

Note 1 to entry: See Figure 1.

3.5

three-dimensional flanking element

3-D flanking element

part of a 3-D geometrical model (3.4) which, when considered in isolation, can be represented by a 2-D geometrical model (3.7)

Note 1 to entry: See Figure 1 and Figure 2.

3.6

three-dimensional central element

3-D central element

part of a 3-D geometrical model (3.4) which is not a 3-D flanking element (3.5)

Note 1 to entry: See Figure 1.

Note 2 to entry: A central element is represented by a 3-D geometrical model (3.4).