

**Lennuväljade valgustuse ja majakasüsteemide
elektripaigaldised. Arendatud visuaalsed
dokkimisjuhindussüsteemid**

Electrical installations for lighting and beaconing of
aerodromes - Advanced Visual Docking Guidance Systems
(A-VDGS)

EESTI STANDARDI EESSÕNA

NATIONAL FOREWORD

Käesolev Eesti standard EVS-EN 50512:2009 sisaldab Euroopa standardi EN 50512:2009 ingliskeelset teksti.

Standard on kinnitatud Eesti Standardikeskuse 27.03.2009 käskkirjaga ja jõustub sellekohase teate avaldamisel EVS Teatajas.

Euroopa standardimisorganisatsioonide poolt rahvuslikele liikmetele Euroopa standardi teksti kättesaadavaks tegemise kuupäev on 13.02.2009.

Standard on kättesaadav Eesti standardiorganisatsioonist.

This Estonian standard EVS-EN 50512:2009 consists of the English text of the European standard EN 50512:2009.

This standard is ratified with the order of Estonian Centre for Standardisation dated 27.03.2009 and is endorsed with the notification published in the official bulletin of the Estonian national standardisation organisation.

Date of Availability of the European standard text 13.02.2009.

The standard is available from Estonian standardisation organisation.

ICS 93.120

Standardite reprodutseerimis- ja levitamiseõigus kuulub Eesti Standardikeskusele

Andmete paljundamine, taastekitamine, kopeerimine, salvestamine elektroonilisse süsteemi või edastamine ükskõik millises vormis või millisel teel on keelatud ilma Eesti Standardikeskuse poolt antud kirjaliku loata.

Kui Teil on küsimusi standardite autorikaitse kohta, palun võtke ühendust Eesti Standardikeskusega:
Aru 10 Tallinn 10317 Eesti; www.evs.ee; Telefon: 605 5050; E-post: info@evs.ee

Right to reproduce and distribute belongs to the Estonian Centre for Standardisation

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying, without permission in writing from Estonian Centre for Standardisation.

If you have any questions about standards copyright, please contact Estonian Centre for Standardisation:
Aru str 10 Tallinn 10317 Estonia; www.evs.ee; Phone: 605 5050; E-mail: info@evs.ee

**Electrical installations for lighting and beaconing of aerodromes -
Advanced Visual Docking Guidance Systems (A-VDGS)**

Installations électriques pour l'éclairage
et le balisage des aérodromes -
Systèmes Avancés de Guidage Visuel
pour l'Accostage (SAGVA)

Elektrische Anlagen für Beleuchtung
und Befeuerung von Flugplätzen -
Erweitertes optisches
Andockführungssystem (A-VDGS)

This European Standard was approved by CENELEC on 2008-12-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: avenue Marnix 17, B - 1000 Brussels

Foreword

This European Standard was prepared by Working Group 3 of the Technical Committee CENELEC TC 97, Electrical installations for lighting and beaconing of aerodromes.

The text of the draft was submitted to the Unique Acceptance Procedure and was approved by CENELEC as EN 50512 on 2008-12-01.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2009-12-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2011-12-01

This European Standard has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association and covers essential requirements of EC Directive 2004/108/EC. See Annex ZZ.

This document is a preview generated by EVS

Contents

Introduction	4
1 Scope	4
2 Normative references	4
3 Definitions	5
4 Requirements	8
4.1 System performance	8
4.2 Design	10
4.3 Safety	13
4.4 Installation and maintenance	14
4.5 Verification of equipment quality	14
5 Test	15
5.1 Type tests	15
5.2 Factory test	26
5.3 Site test	26
Annex A (informative) Best practices for an A-VDGS and proved methods – Functions to support the operation particular on busy airports	27
Annex ZZ (informative) Coverage of Essential Requirements of EC Directives	30
Figures	
Figure 1 – Area covered by the A-VDGS	8
Figure 2 – Principle test configuration	19
Figure 3 – Measurement configuration	20
Figure 4 – Measurement area	21
Tables	
Table 1 – A-VDGS accuracy	9
Table 2 – Maximum aircraft taxi speed during the docking procedure	9
Table 3 – Minimum luminance ratios (<i>LR</i>) for various colours, at test angles on the reference axis and off the reference axis	11
Table 4 – Temperature tests	16
Table 5 – Vibration test	23
Table A.1 – Information provided by the A-VDGS display	28

Introduction

This European Standard contains the requirements for an Advanced Visual Docking Guidance System (A-VDGS) as it is described in the ICAO Annex 14. This standard covers the characteristics of the electrical and mechanical components. This standard includes the software design where this affects the required system performance and safety.

An A-VDGS is to be designed to achieve safe and precise guidance during the docking procedure of an aircraft. The system provides at least a display which shows information of azimuth guidance and stop information.

The use of an A-VDGS is in principle limited to a defined area with an opening angle and a border distance to the stop point related to the centre line. The reference point for all distances and guidance information at the aircraft is the central axis of the nose wheel.

It has to be considered that in some cases the topographical situation of an airport requires a reduced working area for an A-VDGS which will result in the area being different from the requirements stated herein.

For practical use on the airport it has to be considered that the detection range can be limited due to the actual weather and visibility condition prevailing (fog, rain, snow, etc.).

1 Scope

This European Standard specifies requirements of electrical and mechanical design, installation, maintenance and testing procedures for advanced visual docking guidance systems.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 60068-2-1, Environmental testing - Part 2-1: Tests - Test A: Cold (IEC 60068-2-1)

EN 60068-2-2, Environmental testing - Part 2-2: Tests - Test B: Dry heat (IEC 60068-2-2)

EN 60068-2-5, Environmental testing - Part 2-5: Tests - Test Sa: Simulated solar radiation at ground level (IEC 60068-2-5)

EN 60068-2-30, Environmental testing - Part 2-30: Tests - Test Db: Damp heat, cyclic (12 h + 12 h cycle) (IEC 60068-2-30)

EN 60068-2-64, Environmental testing - Part 2-64: Tests - Test Fh: Vibration, broadband random and guidance (IEC 60068-2-64)

EN 60439-1:1999, Low-voltage switchgear and control gear assemblies - Part 1: Type-tested and partially type-tested assemblies (IEC 60439-1:1999)

EN 60529, Degrees of protection provided by enclosures (IP Code) (IEC 60529)

EN 60825-1, Safety of laser products - Part 1: Equipment classification and requirements (IEC 60825-1)

EN 61000-3-2, Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current ≤ 16 A per phase) (IEC 61000-3-2)

EN 61000-3-3, Electromagnetic compatibility (EMC) - Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection (IEC 61000-3-3)

EN 61000-3-11, Electromagnetic compatibility (EMC) - Part 3-11: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems - Equipment with rated current ≤ 75 A and subject to conditional connection (IEC 61000-3-11)

EN 61000-3-12, Electromagnetic compatibility (EMC) - Part 3-12: Limits - Limits for harmonic currents produced by equipment connected to public low-voltage systems with input current > 16 A and ≤ 75 A per phase (IEC 61000-3-12)

EN 61000-6-2, Electromagnetic compatibility (EMC) - Part 6-2: Generic standards - Immunity for industrial environments (IEC 61000-6-2)

EN 61000-6-3, Electromagnetic compatibility (EMC) - Part 6-3: Generic standards - Emission standard for residential, commercial and light-industrial environments (IEC 61000-6-3)

HD 472, Nominal voltages for low-voltage public electricity supply systems (IEC 60038 'IEC standard voltages', mod.)

HD 60364 series, Low voltage electrical installations (IEC 60364 series, mod.)

3 Definitions

For the purposes of this document, the following terms and definitions apply.

The following definitions were developed to be included in international standards relating to A-VDGS on aerodromes.

3.1

Advanced Visual Docking Guidance System (A-VDGS)

those systems that provide additional guidance information to pilots, e.g. aircraft type indication, distance-to-go information and closing speed. Docking guidance information is provided on an A-VDGS display. Advanced-VDGS also permit interfacing to external management, guidance or allocation systems

3.2

A-VDGS display

display which presents the guidance and other information to the pilots in the left and/or right hand seats and to the drivers and to any other persons assisting the aircraft docking procedure

3.3

aircraft type

the aircraft manufacturer's designation for an aircraft grouping with similar design or style of structure

3.4

ambient brightness

the overall brightness level in the viewing environment surroundings