
**Geotechnical investigation and testing —
Field testing —**

**Part 4:
Ménard pressuremeter test**

Reconnaissance et essais géotechniques — Essais en place —

Partie 4: Essai au pressiomètre de Ménard



This document is a preview generated by EVS



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	2
3 Terms, definitions and symbols	2
3.1 Terms and definitions	2
3.2 Symbols	4
4 Equipment	6
4.1 General description	6
4.2 Pressuremeter probe	7
4.3 Pressure and volume control unit (CU)	11
4.4 Connecting lines	11
4.5 Injected liquid	11
4.6 Measurement and control	11
4.7 Data logger	12
5 Test procedure	12
5.1 Assembling the parts	12
5.2 Calibration and corrections	12
5.3 Pressuremeter pocket and probe placing	12
5.4 Preparation for testing	13
5.5 Establishing the loading programme	13
5.6 Establishing the differential pressure	14
5.7 Expansion	15
5.8 Back-filling of the pockets	15
5.9 Safety requirements	15
6 Test results	16
6.1 Data sheet and field print-out	16
6.2 Corrected pressuremeter curve	17
6.3 Calculated results	17
7 Reporting	18
7.1 General	18
7.2 Field report	18
7.3 Test report	18
Annex A (normative) Geometrical features of pressuremeter probes	20
Annex B (normative) Calibration and corrections	23
Annex C (normative) Placing the pressuremeter probe in the ground	31
Annex D (normative) Obtaining pressuremeter parameters	38
Annex E (normative) Resolution and uncertainties	46
Annex F (normative) Pressuremeter test records	47
Bibliography	51

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 22476-4 was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 341, *Geotechnical investigation and testing*, in collaboration with Technical Committee ISO/TC 182, *Geotechnics*, Subcommittee SC 1, *Geotechnical testing*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

ISO 22476 consists of the following parts, under the general title *Geotechnical investigation and testing — Field testing*:

- *Part 1: Electrical cone and piezocone penetration test*
- *Part 2: Dynamic probing*
- *Part 3: Standard penetration test*
- *Part 4: Ménard pressuremeter test*
- *Part 5: Flexible dilatometer test*
- *Part 7: Borehole jack test*
- *Part 9: Field vane test*
- *Part 10: Weight sounding test* [Technical Specification]
- *Part 11: Flat dilatometer test* [Technical Specification]
- *Part 12: Mechanical cone penetration test (CPTM)*

Geotechnical investigation and testing — Field testing —

Part 4: Ménard pressuremeter test

1 Scope

This part of ISO 22476 specifies the equipment requirements, execution of and reporting on the Ménard pressuremeter test.

NOTE 1 This part of ISO 22476 fulfils the requirements for the Ménard pressuremeter test, as part of the geotechnical investigation and testing according to EN 1997-1 and EN 1997-2.

This part of ISO 22476 describes the procedure for conducting a Ménard pressuremeter test in natural soils, treated or untreated fills and in weak rocks, either on land or off-shore.

The pressuremeter test results of this part of ISO 22476 are suited to a quantitative determination of ground strength and deformation parameters. They may yield lithological information. They can also be combined with direct investigation (e.g. sampling according to ISO 22475-1) or compared with other *in situ* tests (see EN 1997-2:2007, 2.4.1.4(2) P, 4.1 (1) P and 4.2.3(2) P).

The Ménard pressuremeter test is performed by the radial expansion of a tricell probe placed in the ground (see Figure 1). During the injection of the liquid volume in the probe, the inflation of the three cells first brings the outer cover of the probe into contact with the pocket wall and then presses on them resulting in a soil displacement. Pressure applied to and the associated volume expansion of the probe are measured and recorded so as to obtain the stress-strain relationship of the soil as tested.

Together with results of investigations with ISO 22475-1 being available, or at least with identification and description of the ground according to ISO 14688-1 and ISO 14689-1 obtained during the pressuremeter test operations, the test results of this part of ISO 22476 are suited to the quantitative determination of a ground profile, including

- the Ménard E_M modulus,
- the Ménard limit pressure p_{LM} and
- the Ménard creep pressure p_{fM} .

This part of ISO 22476 refers to a probe historically described as the 60 mm G type probe. This part of ISO 22476 applies to test depths limited to 50 m and test pressure limited to 5 MPa.

NOTE 2 Ménard pressuremeter tests are carried out with other probe diameters and pocket dimensions such as shown below.

Probe		Drilling diameter (mm)	
Designation	Diameter (mm)	min	max
AX	44	46	52
BX	58	60	66
NX	70/74	74	80

Two alternative methods of measurement are provided as follows.

- Procedure A: data are recorded manually.
- Procedure B: data are recorded automatically.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 14688-1, *Geotechnical investigation and testing — Identification and classification of soil — Part 1: Identification and description*

ISO 14689-1, *Geotechnical investigation and testing — Identification and classification of rock — Part 1: Identification and description*

ISO 22475-1, *Geotechnical investigation and testing — Sampling methods and groundwater measurements — Part 1: Technical principles for execution*

ENV 13005:1999, *Guide to the expression of uncertainty in measurement*

3 Terms, definitions and symbols

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1

pressuremeter

whole equipment which is used to carry out a Ménard pressuremeter test, excluding the means necessary to place the pressuremeter probe into the ground

NOTE 1 A pressuremeter includes a pressuremeter probe, a pressure and volume control unit, called CU, lines to connect the probe to the CU and, in the case of procedure B, a data logger which is either built into the CU or linked to it.

NOTE 2 See Figure 2.

3.1.2

pressuremeter test pocket

circular cylindrical cavity formed in the ground to receive a pressuremeter probe

3.1.3

pressuremeter borehole

borehole in which pressuremeter pockets with circular cross sections are made in the ground, and into which the pressuremeter probe is to be placed

3.1.4

pressuremeter test

process during which a pressuremeter probe is inflated in the ground and the resulting pocket expansion is measured by volume as a function of time and pressure increments according to a defined programme

NOTE See Figure 4 and F.1.

3.1.5

pressuremeter sounding

whole series of sequential operations necessary to perform Ménard pressuremeter testing at a given location, i.e. forming pressuremeter test pockets and performing pressuremeter tests in them

NOTE See F.2.

3.1.6

pressuremeter pressure reading, p_r

pressure p_r as read at the CU elevation in the liquid circuit supplying the central measuring cell