

INTERNATIONAL STANDARD

ISO
5599-2

First edition
1990-01-15

Pneumatic fluid power — Five-port directional control valves —

Part 2: Mounting interface surfaces with optional electrical connector

*Transmissions pneumatiques — Distributeurs à cinq orifices principaux —
Partie 2: Plans de pose avec connecteur électrique facultatif*



Reference number
ISO 5599-2 : 1990 (E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 5599-2 was prepared by Technical Committee ISO/TC 131, *Fluid power systems*.

This first edition of ISO 5599-2 cancels and replaces the first edition of ISO 5599-1 : 1978, of which it constitutes a technical revision in part.

ISO 5599-1 : 1978 specified requirements both for mounting interface surfaces without electrical connector and for mounting interface surfaces with optional electrical connector. This part of ISO 5599 specifies requirements for mounting interface surfaces with optional electrical connector only. Part 1 specifies requirements for mounting interface surfaces without electrical connector.

ISO 5599 consists of the following parts, under the general title *Pneumatic fluid power — Five-port directional control valves — Mounting interface surfaces*:

- *Part 1: Mounting interface surfaces without electrical connector*
- *Part 2: Mounting interface surfaces with optional electrical connector*
- *Part 3: Code system for communication of valve functions*

Annex A of this part of ISO 5599 is for information only.

© ISO 1990

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Introduction

In pneumatic fluid power systems, power is transmitted and controlled through gas under pressure within an enclosed circuit.

The various devices for gas distribution and control can be either mounted directly onto the pipeline, or mounted on interface surfaces, allowing quicker dismantling and promoting equipment interchangeability.

Pneumatic directional control valves of the five-port, four-way type, mounted on interface surfaces complying with the requirements of this part of ISO 5599 control the flow of compressed gas. When the valve is electrically operated, it may be desirable to use an electrical connector at the interface of the valve body and sub-base. Users of pneumatic valves benefit when this electrical connector is standardized, allowing easy electrical connection interchangeability between valves produced by different manufacturers.

Standardization of port and orifice identification, the result of operator actuation and a system of dimensional tolerances are provided to enhance mounting interchangeability of pneumatic control valves used on the mounting interface surfaces complying with the requirements of this part of ISO 5599.

This document is a preview generated by EVS

This page intentionally left blank

Pneumatic fluid power — Five-port directional control valves —

Part 2: Mounting interface surfaces with optional electrical connector

1 Scope

This part of ISO 5599 is applicable to mounting interface surfaces and electrical connectors for five-port pneumatic directional control valves for a maximum working pressure of 1,6 MPa [16 bar¹⁾]. It specifies

- dimensions and tolerances of the interface features;
- port identification;
- identification of the result of operator actuation;
- dimensions, tolerances and specifications for optional interface electrical connector mateability.

It does not apply to the functional characteristics of interfaces.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 5599. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 5599 are encouraged to investigate the possibility of applying the most recent editions of the standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 468 : 1982, *Surface roughness — Parameters, their values and general rules for specifying requirements*.

ISO 1101 : 1983, *Technical drawings — Geometrical tolerancing — Tolerancing of form, orientation, location and run-out — Generalities, definitions, symbols, indications on drawings*.

ISO 1302 : 1978, *Technical drawings — Method of indicating surface texture on drawings*.

ISO 5598 : 1985, *Fluid power systems and components — Vocabulary*.

3 Definitions

For the purposes of this part of ISO 5599, the definitions given in ISO 5598, together with the following, apply.

3.1 electrical connector: A device consisting of two parts (contact and housing) which, when they are joined, provide electrical and mechanical continuity.

3.2 contact: A current-carrying component used at a removable junction of an electric circuit.

3.3 socket: A contact with an opening or hollow designed to be the mechanical holder of a pin-type contact.

3.4 pin: A pointed contact designed to mate with a socket contact.

3.5 housing: A device designed to orient, secure and insulate contacts.

4 Dimensional requirements and tolerances


4.1 Dimensional requirements for sizes 1E, 2E and 3E are shown in figure 1 and given in table 1.

4.2 Dimensional requirements for sizes 4E, 5E and 6E are shown in figure 2 and given in table 2.

4.3 The main dimensions and tolerances of form and location of the interface features are shown in figures 3, 4, 5 and 6, and given in table 3.

4.4 Tolerances on surface condition, within the continuous line, shall be as follows:

- Surface roughness: 1,6 µm (class N7) (see ISO 468 and ISO 1302)
- Surface flatness: 0,1 mm over a distance of 100 mm (see ISO 1101)



1) 1 bar = 0,1 MPa = 10⁵ N/m²