INTERNATIONAL STANDARD

ISO 5783

Second edition 1995-12-15

Hydraulic fluid power — Code for identification of valve mounting surfaces and cartridge valve cavities

Transmissions hydrauliques — Code pour l'identification des plans de pose et des logements de cartouche



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bedies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the Dember bodies casting a vote.

International Standard ISO 5783 was prepared by Technical Committee ISO/TC 131, Fluid power systems, Subcommittee SC 5, Control products and components.

This second edition cancels and replaces the first edition (ISO \$783:1981), which has been technically revised.

Annex A of this International Standard is for information only.

© ISO 1995

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

This document is a preview denetated by EVS In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within an enclosed circuit. The control and regulation of the fluid are accomplished by valves which can be directly connected to fluid conductors, mounted on sub-plates, or installed as

This document is.

This page intentionally left blank of the content of the conte

Hydraulic fluid power — Code for identification of valve mounting surfaces and cartridge valve cavities

1 Scope

This International Standard defines an identification code for hydraulic valve mounting surfaces and for hydraulic cartridge valve cavities that are defined in International Standards.

Mounting surfaces and cartridge valve wities that do not conform to International Standards should not be identified by this code.

This International Standard does not require that the hardware be marked with the identification code.

2 Identification code

Designate the mounting surfaces or the cartridge cavities to the five groups of numbers indicated below, written in the order given, and separated by spaced hyphens:

- a) the number of the International Standard in which the mounting surface or the cartridge cavity is described;
- b) two numerals representing
 - either the size of the valve mounting surface (see clause 3),
 - or the size of the slip-in cartridge valve (see clause 3),
 - or the cavity thread diameter of the screw-in cartridge valve;
- c) two numerals indicating which figure in the International Standard describes the mounting surface or the cavity;
- d) one numeral indicating whether an option exists
 - numeral 0 is used for the basic version,
 - numerals 1 to 9 are used to indicate all the different options;
- e) two numerals indicating the year of the latest edition of the International Standard that defines the specific mounting surface or cavity.

3 Size code

A size code shall be established in accordance with table 1 at the time a valve mounting surface or a slip-in cartridge valve cavity is first standardized, or when the codification defined in this International Standard is first applied to an existing standard. Any subsequent changes to the main port diameter shall not affect the size code.